
Formerly Utilized Sites Remedial
Action Program (FUSRAP)

Maywood Chemical Company Superfund Site

ADMINISTRATIVE RECORD

Document Number

MISS- 023.



**US Army Corps
of Engineers®**

LEGAL NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

CHARACTERIZATION REPORT FOR THE
NEW JERSEY VEHICLE INSPECTION STATION PROPERTY
LODI, NEW JERSEY

JUNE 1987

Prepared for

UNITED STATES DEPARTMENT OF ENERGY
OAK RIDGE OPERATIONS OFFICE
Under Contract No. DE-AC05-81OR20722

By

N. C. Ring and S. K. Livesay
Bechtel National, Inc.
Oak Ridge, Tennessee

Bechtel Job No. 14501

TABLE OF CONTENTS

	<u>Page</u>
1.0 Introduction and Summary	1
1.1 Introduction	1
1.2 Purpose and Objectives	1
1.3 Summary	3
2.0 Site Description and Background	4
3.0 Radiological Characterization	6
3.1 Remedial Action Guidelines	6
3.2 Surface Characterization	6
3.3 Subsurface Characterization	9
3.4 Building Survey Procedures	18
References	56
Appendix A Geologic Drill Logs for the Maywood Interim Storage Site - New Jersey Vehicle Inspection Station	A-1

LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
1-1	Location of the Maywood Interim Storage Site, the Former Lodi Brook, and the New Jersey Vehicle Inspection Station Property	2
2-1	Location of the New Jersey Vehicle Inspection Station Property	5
3-1	Surface Soil Sampling Locations at the New Jersey Vehicle Inspection Station Property	8
3-2	Areas of Surface Contamination at the New Jersey Vehicle Inspection Station Property	10
3-3	Borehole Locations at the New Jersey Vehicle Inspection Station Property	12
3-4	Contours of Subsurface Contamination at the New Jersey Vehicle Inspection Station Property	13
3-5	Locations of the Present Lodi Brook (Conduit) and the Original Streambed	14
3-6	Geologic Cross Section of the Former Lodi Brook Streambed	15
3-7	Exposure Rate Measurement Locations at the New Jersey Vehicle Inspection Station Property	20

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
3-1	Summary of Residual Contamination Guidelines for the Maywood Site	21
3-2	Surface Soil Sampling Results for the New Jersey Vehicle Inspection Station Property	23
3-3	Downhole Gamma Logging Results for the New Jersey Vehicle Inspection Station Property	25
3-4	Gamma Radiation Exposure Rate Measurements for the New Jersey Vehicle Inspection Station Property	55

ABBREVIATIONS

cm	centimeter
cm ²	square centimeter
cpm	counts per minute
dpm	disintegrations per minute
ft	foot
h	hour
in.	inch
l	liter
l/min	liters per minute
m	meter
m ²	square meter
μR/h	microroentgens per hour
mi	mile
mi ²	square mile
mrad/h	millirad per hour
mrem	millirem
mrem/yr	millirem per year
min	minute
pCi/g	picocuries per gram
pCi/l	picocuries per liter
WL	working level

1.0 INTRODUCTION AND SUMMARY

1.1 INTRODUCTION

The 1984 Energy and Water Appropriations Act authorized the U.S. Department of Energy (DOE) to conduct a decontamination research and development project at four sites, including the site of the former Maywood Chemical Works (now owned by the Stepan Company) and its vicinity properties. The act was reauthorized in 1985. DOE has constructed the Maywood Interim Storage Site (MISS) on 11.7 acres of land west of the Stepan Company property. The New Jersey Vehicle Inspection Station property is included as one of the Maywood vicinity properties (Figure 1-1). The work is being administered by the Formerly Utilized Sites Remedial Action Program (FUSRAP), one of two remedial action programs under the direction of the DOE Division of Facility and Site Decommissioning Projects.

The U.S. Government initiated FUSRAP in 1974 to identify, clean up, or otherwise control sites where low-activity radioactive contamination (exceeding current guidelines) remains from the early years of the nation's atomic energy program or from commercial operations that resulted in conditions Congress has mandated DOE to remedy (Ref. 1).

FUSRAP is currently being managed by the DOE Oak Ridge Operations Office (ORO). As the Project Management Contractor (PMC) for FUSRAP, Bechtel National, Inc. (BNI) is responsible to DOE for planning, managing, and implementing FUSRAP.

1.2 PURPOSE AND OBJECTIVES

A radiological characterization of the New Jersey Vehicle Inspection Station (NJVIS) property has been conducted to establish the horizontal and vertical limits of radioactive contamination and to determine ranges of radionuclide concentrations. The information obtained from this characterization work will be used in planning




FIGURE 1-1 LOCATION OF THE MAYWOOD INTERIM STORAGE SITE, THE FORMER LODI BROOK, AND THE NEW JERSEY VEHICLE INSPECTION STATION

any required remedial action. The results will also be used to satisfy an important secondary objective, which is to provide data to aid in the identification and evaluation of pathways by which contamination might have migrated from the property.

1.3 SUMMARY

This report summarizes the procedures and results of the radiological characterization of the NJVIS property conducted in July and December 1986 and the additional characterization work performed in February 1987.

The radiological characterization confirmed that thorium-232 is the primary radioactive contaminant. The surface soil sample results showed the maximum concentration of thorium-232 to be 12.5 pCi/g, which is in excess of the DOE guideline of 5.0 pCi/g plus background of 1.0 pCi/g for surface soils. The maximum concentration for radium-226 was 1.6 pCi/g above background, which does not exceed the guideline. The maximum uranium-238 concentration was less than 14.3 pCi/g above background, but no site-specific DOE guidelines for uranium have been established.

The results of downhole gamma logging indicate subsurface contamination at depths ranging from 1 to 7 ft.

2.0 SITE DESCRIPTION AND BACKGROUND

The New Jersey Vehicle Inspection Station (NJVIS) is located in a highly developed area of the Borough of Lodi, County of Bergen, New Jersey. The population density of the area is approximately 10,000 people per square mile. It is located approximately 12 mi north-northwest of downtown Manhattan (New York City) and 13 mi northeast of Newark, New Jersey. The property (14.3 acres) is bordered on the north by Hancock Street, the south by Gregg Street, the east by another commercial property, and the west by Columbia Lane (Figure 2-1).

The NJVIS property was shown to be radioactively contaminated during a radiological survey conducted in August 1984 by the Oak Ridge National Laboratory (ORNL) at the request of DOE (Ref. 2). The available data indicates that the contamination originated from the processing of monazite sand (thorium ore) by the Maywood Chemical Works from 1916 through 1956. During this time, slurry containing process wastes from the thorium operations was pumped to diked areas west of the plant. The area west of the plant was generally low and swampy at that time. In 1932, New Jersey Route 17 was built through this disposal area. Some of these process wastes were removed from the Maywood Chemical Works for use as mulch and fill on nearby properties, thereby contaminating them with radioactive thorium (Ref. 3). Additional waste apparently migrated off-site via the natural drainage provided by the former Lodi Brook.

In 1954, the Atomic Energy Commission (AEC) issued License R-103 to the Maywood Chemical Works allowing it to continue to ship, receive, possess, and process radioactive materials under the authority of the Atomic Energy Act of 1954. The Maywood Chemical Works stopped processing thorium in 1956 after approximately 40 years of production. The Maywood Chemical Works was sold to the Stepan Company in 1959 (Ref. 3).




FIGURE 2-1 LOCATION OF THE NEW JERSEY STATE VEHICLE INSPECTION STATION PROPERTY

3.0 RADIOLOGICAL CHARACTERIZATION

To provide sufficiently detailed information regarding the limits of radioactive contamination and to provide data for the development of cost-effective measures for any potential remedial action, both surface and subsurface investigations were performed.

To facilitate the collection of data in a systematic manner, a 50-ft grid was established over the area to be characterized. This grid was correlated with the New Jersey state grid system to ensure that it could be reestablished if remedial action is undertaken. All data correspond to coordinates on the characterization grid.

3.1 REMEDIAL ACTION GUIDELINES

Information collected during the radiological survey conducted by ORNL (Ref. 2) indicated that the radioactive contamination at the NJVIS property consists primarily of thorium-232, with typically much lower levels of radium-226 and uranium-238. Thorium is also known to be the primary contaminant at the MISS (Ref. 3). Table 3-1 lists the DOE residual contamination guidelines governing the release of formerly contaminated property for unrestricted use (Ref. 4).

3.2 SURFACE CHARACTERIZATION

Surface characterization was conducted with a shielded gamma scintillation detector. Near-surface gamma radiation measurements were taken 12 in. from the ground at the grid line intersections spaced 10 ft apart. The shielded detector was used to ensure that radiation detected by the probe originated from the ground directly beneath the unit. By shielding against lateral gamma flux, the shielded detector minimizes possible sources of error in the measurements. Furthermore, this detector was calibrated at the Technical Measurements Center (TMC) in Grand Junction, Colorado, to provide a correlation of counts per minute (cpm) to picocuries per gram (pCi/g). Based on this relationship, locations with

measurements of more than 11,000 cpm were noted as exceeding the DOE guideline of 5 pCi/g for thorium-232 in surface soils. To better define the limits of contamination, soil sampling locations were chosen by evaluating locations with measurements of more than 11,000 cpm, locations with measurements at or near 11,000 cpm, and the potential for lateral gamma flux. The sampling locations are shown in Figure 3-1. It should be noted that not all surface soil samples indicated contamination because some samples were taken from locations where the gamma measurement was at or near the guideline. The data in Table 3-2 show the maximum concentration of thorium-232 to be 12.5 pCi/g, which exceeds the DOE guideline for surface soils. Use of the "less than" ($<$) notation indicates that the radionuclide was not present in measurable concentrations. The value following the less than notation is the minimum detectable amount (MDA). The MDA is based on various factors, including the volume, size, and weight of the sample; the type of detector used; the counting time, and the background count rate. In addition, since radioactive decay is a random process, a correlation between the rate of disintegration and a given radionuclide concentration cannot be precisely established; therefore, the exact concentration of the radionuclide cannot be determined. As such, each value that is equal to or greater than the MDA has an associated uncertainty term (\pm), which represents the maximum amount by which the actual value can be expected to differ from the value given in the table. The uncertainty term has an associated confidence level of 95 percent.

The maximum concentration of radium-226 was 1.6 pCi/g, which is within the guideline. The maximum concentration of uranium-238 was less than 14.3 pCi/g, but no site-specific DOE guideline for uranium in soil has been established.

Although the concentrations for uranium-238 have higher values than thorium-232 concentrations, thorium-232 is considered the primary contaminant. As shown in Table 3-1, the guidelines for thorium-232 are 5 pCi/g for surface soil and 15 pCi/g for subsurface soil. Although no specific guidelines have been determined for




FIGURE 3-1 SURFACE SOIL SAMPLING LOCATIONS AT THE NEW JERSEY VEHICLE INSPECTION STATION PROPERTY

uranium-238, using a typical (as opposed to a site-specific) value to calculate the guideline would result in a guideline of approximately 75 pCi/g. Because the measured concentrations of thorium-232 exceed its guidelines by a greater percentage than uranium-238, thorium-232 is considered the primary contaminant.

Analysis of the surface soil sample taken at Coordinates E1210, N1340 indicated the presence of cesium-137 at a concentration of 12 pCi/g. This appears to be an isolated occurrence as no evidence of cesium was found in other radiological samples. No explanation for the presence of this radionuclide has been determined.

The largest area of surface contamination exists north and east of the NJVIS building beginning at the property boundaries (north, east, and west) and extending southward to within approximately 150 ft of the building (Figure 3-2).

Additional small areas of surface contamination exist near the southeastern corner of the property near Gregg Street and near the northeastern corner of the NJVIS building. Areas of surface contamination are shown in Figure 3-2.

3.3 SUBSURFACE CHARACTERIZATION

After surface characterization was completed, a subsurface investigation was conducted to determine the depth of previously identified surface contamination and to locate subsurface contamination with no surface manifestation. The subsurface investigation was conducted using downhole gamma logging of the drill holes. This technique is significantly more cost effective than soil sampling, because the procedure can be completed more quickly and eliminates the need for laboratory analysis.

A 2-in. by 2-in. sodium iodide gamma scintillation detector was used to perform the downhole logging. The instrument was calibrated at TMC, where it was determined that a count rate of approximately 40,000 cpm corresponds to the 15-pCi/g guideline for thorium-232 in




FIGURE 3-2 AREAS OF SURFACE CONTAMINATION AT THE NEW JERSEY VEHICLE INSPECTION STATION PROPERTY

subsurface soils. This relationship has been corroborated in results from previous characterizations where thorium-232 was found (Ref. 5). However, analysis of trends and marginal readings is necessary to predict the contamination boundaries.

During the course of the subsurface investigation, 113 radiological boreholes were drilled (Figure 3-3) and gamma logged to determine the depth of radioactive contamination. Detailed gamma logging data are presented in Table 3-3.

As shown in Figure 3-4, the largest area of subsurface contamination exists in the same location as surface contamination (north and east of the NJVIS building). The depths of this contamination range from 1 to 7 ft. Contamination is believed to have resulted primarily from stream sediment deposition and possibly from fill emplacement. This belief is based on information obtained during additional drilling activities conducted to better define the location of the original Lodi Brook streambed. It was determined that the streambed flowed through the northern section of the property. Radiological and geological data can be used to infer the streambed location on the basis of the presence of stream sediments and their degree of contamination. A logical assumption would be that the original streambed was probably located where the deepest and most contaminated stream sediments are found. Lodi Brook currently flows through a buried conduit in the northern section of the property. The conduit is parallel to Hancock Street (Figure 3-5).

Geological information regarding the location of the former Lodi Brook streambed also indicates that the exposed relic channel (Coordinates E1500, N1800, approximately) was not incised but rather was a broad, open channel, and contamination is not evenly distributed (Figure 3-6). This offers further explanation as to why some gamma logs from boreholes in or near the channel indicate concentrations below guidelines. It also explains why so little fill was needed to bring the concave channel up to its present grade. Fill depths in the former streambed vary from 0 to 6 ft.




FIGURE 3-3 BOREHOLE LOCATIONS AT THE NEW JERSEY VEHICLE INSPECTION STATION PROPERTY




FIGURE 3-4 CONTOURS OF SUBSURFACE CONTAMINATION AT THE NEW JERSEY VEHICLE STATION INSPECTION PROPERTY




FIGURE 3-5 LOCATIONS OF THE PRESENT LODI BROOK (CONDUIT) AND THE ORIGINAL STREAMBED

A




FIGURE 3-6 GEOLOGIC CROSS SECTION OF THE FORMER LODI BROOK STREAMBED

These fill depths conform to the natural 1-percent grade of the former streambed. The shallowness of fill (moved indigenous soil) also explains why the fill is so thoroughly contaminated with underlying black, thorium-bearing stream sediments. The former streambed and the present conduit converge in the northwestern corner of the property with contamination indicated above the conduit. Although drilling data in this area suggest that this contamination is mostly surficial, it may extend around the conduit in the northwestern corner of the property. Contamination appears to trend off the property to the north under Hancock Street as well as to the east and west toward properties contiguous with the NJVIS property.

Subsurface contamination (0.5 to 1.0 ft) found in a small area near the northeastern corner of the NJVIS building (Figure 3-3) is thought to result from fill emplacement. Contamination is not thought to exist beneath the building itself for four reasons: (1) no other areas of subsurface contamination were found either adjacent to or in close proximity to the building; (2) no subsurface contamination was indicated by any of the near-surface measurements taken close to the building; (3) the building may be founded on bedrock; no contamination has been found in any of the boreholes that have penetrated bedrock in this area (depth of bedrock is approximately 6 ft in this area), and the bedrock in this area has an extremely low primary hydraulic conductivity; and (4) interior exposure rate measurements were all within background levels. On the basis of this information, drilling inside the building was considered unnecessary and therefore was not performed.

The presence of subsurface contamination (0.5 to 1.5 ft) was also indicated in the southeastern corner of the property near Gregg Street (Figure 3-4) in an area where surface contamination is also present.

On the basis of geological information gained as a result of the borehole drilling during this characterization, it was determined that the property is relatively flat (total measured relief of

6.7 ft) and is underlain in most areas by at least two types of soil, fill, and naturally occurring sediments over the red, consolidated sandstone of the Brunswick Formation. There are competent sandstone outcrops in the southeastern section of the property. The sandstone layer extends beneath the surface of the property from depths of as much as 6 ft facing northwest toward the NJVIS building to depths greater than 20 ft below the surface in the central and northwestern areas of the property.

Unconsolidated materials of dark yellowish brown sandstone covered by a moderately brown, residual sandy soil are present in the slightly higher areas of the property. Three soil sequences are present in the low-lying areas of the property. The property south of the NJVIS building has a soil sequence of decomposed sandstone covered by a thin lens (1 to 2 ft) of black silty organic soil. These materials are buried by 1 to 3 ft of fill. In the area north of the NJVIS building, exposed black organic silt overlying decomposed Brunswick sandstone delineates the original Lodi Brook channel and its floodplain. Black silt is also present under the surrounding lawn, suggesting that stream sediment was taken from the channel and used as topsoil. The third type of soil sequence appears in many areas throughout the property and is represented by fill placed on top of indigenous brown soil.

In addition to the building, the property is presently covered with asphalt parking lots, roadways, and a grass lawn. A 3-ft-high berm exists in the northern section (drivers education area) of the property (along Coordinate N1775 and between Coordinates E1150 and E1350). The fill used on the property is primarily residual soil transported from higher elevations on the property. Areas with thick accumulations of fill include the berm in the drivers education area (6 ft), the original Lodi Brook channel (6 ft), the conduit through which the brook presently flows (5 to 7 ft), and locations of the property's drainage pipes (approximately 5 ft).

North of the NJVIS access road, surface water drains through three evenly spaced grates directly into the Lodi Brook conduit. The

remainder of the site is drained to the south by a series of surface drains and a buried pipeline. Immediately south of the berm in the drivers education area, this drainage system is ineffective; surface soil in this area is nearly saturated. Groundwater levels are shallowest (6 to 8 ft) in the northern and eastern sections of the property with mid-property levels at depths greater than 10 ft, suggesting a northeast to southwest gradient.

Along the eastern property boundary, a linear 10-ft-wide drainage sump is the only nonburied portion of the former Lodi Brook channel between the Saddle River and Interstate 80. Fill has been placed on both sides of this drainage sump, and this lowland now serves as a collection area for runoff from the neighboring property to the east.

3.4 BUILDING SURVEY PROCEDURES

Two indoor radon measurements were taken using the Tedlar bag technique. Using this method, radon measurements are obtained by pumping air into a Tedlar bag at a rate of approximately 2 l/min and transferring the air sample directly into a scintillation cell with an interior coating of zinc sulfide and an end window for viewing the scintillations. Analysis of the sample was simplified by allowing the radon decay products to build up over time. This method allows all the radon decay products to come into secular equilibrium with the radon. The scintillation cell was placed in contact with a photomultiplier tube, and the scintillations were counted using standard nuclear counting instrumentation. Indoor radon measurement results, using this method, ranged from less than 0.2 to 0.8 pCi/l. These concentrations fall within the range typical of those from background indoor radon measurements.

Four indoor air samples were collected to determine working levels (WL) of radon and thoron daughters. Measurement of radon daughters was done by collecting an air sample for exactly 5 min through a 0.45-micron membrane filter at a rate of 11 liters/min for a total sample volume of 55 liters. Alpha-particle activity on the filter paper was counted 40 to 90 min after sampling using an alpha

scintillation detector coupled to a count-rate meter or a digital scaler. Results of measurements for radon daughters ranged from 0.0006 to 0.001 WL and were substantially less than the applicable generic guideline (40 CFR 192) (Ref. 6) of an annual average (or equivalent) radon decay product concentration not to exceed 0.02 WL (Table 3-1). Measurements for thoron daughters were conducted using the same method as for radon daughters with the exception of the time delay between collection of the air sample and counting of the alpha-particle activity. In the case of thoron daughters, the sample is allowed to age for at least 5 hours after sampling before it is counted. This elapsed time allows radon daughters, which may be present with the thoron daughters, to decay sufficiently so as not to interfere with computation of the working levels for thoron daughters. Results of measurements for thoron daughters ranged from less than the lower limit of detection to 0.003 WL. The generic guideline is more restrictive for radon-222 (radon) than for radon-220 (thoron) according to NCRP Report No. 50 (Ref. 7), which was used as the guideline for thoron daughter measurements.

In addition, exposure rate measurements were taken inside the NJVIS building to determine the potential health risk for employees in the event that contamination might be present beneath the building. These measurements are taken 3 ft above the floor using either a SPA-3 or a pressurized ionization chamber (PIC). The latter instrument has a response to gamma radiation that is proportional to exposure in roentgens. A conversion factor for SPA-3 measurements was established through a correlation of measurements taken at four locations in the vicinity of the NJVIS property with these two instruments. The unshielded SPA-3 readings were then used to estimate gamma exposure rates for each location. Locations of these measurements (Figure 3-7) were determined to be representative of the entire building interior. Gamma radiation exposure rate measurements ranged from 4 μ R/h to 5 μ R/h, giving an average of 4 μ R/h, including background. These measurements are considered within the normal variation of background radiation. These results can be found in Table 3-4.




FIGURE 3-7 EXPOSURE RATE MEASUREMENT LOCATIONS AT THE NEW JERSEY VEHICLE INSPECTION STATION PROPERTY

TABLE 3-1

SUMMARY OF RESIDUAL CONTAMINATION GUIDELINES FOR THE MAYWOOD SITE

Page 1 of 2

BASIC DOSE LIMITS

The basic limit for the annual radiation dose received by an individual member of the general public is 100 mrem/yr.

SOIL (LAND) GUIDELINES (MAXIMUM LIMITS FOR UNRESTRICTED USE)

<u>Radionuclide</u>	<u>Soil Concentration (pCi/g) above background^{a,b,c}</u>
Radium-226	5 pCi/g, averaged over the first 15 cm of soil below the surface; 15 pCi/g when averaged over any 15-cm-thick soil layer below the surface layer.
Radium-228	
Thorium-230	
Thorium-232	
Other radionuclides	Soil guidelines will be calculated on a site-specific basis using the DOE manual developed for this use.

STRUCTURE GUIDELINES (MAXIMUM LIMITS FOR UNRESTRICTED USE)

Airborne Radon Decay Products

Generic guidelines for concentrations of airborne radon decay products shall apply to existing occupied or habitable structures on private property that are intended for unrestricted use; structures that will be demolished or buried are excluded. The applicable generic guideline (40 CFR 192) is: In any occupied or habitable building, the objective of remedial action shall be, and reasonable effort shall be made to achieve, an annual average (or equivalent) radon decay product concentration (including background) not to exceed 0.02 WL.^d In any case, the radon decay product concentration (including background) shall not exceed 0.03 WL. Remedial actions are not required in order to comply with this guideline when there is reasonable assurance that residual radioactive materials are not the cause.

External Gamma Radiation

The average level of gamma radiation inside a building or habitable structure on a site to be released for unrestricted use shall not exceed the background level by more than 20 µR/h.

Indoor/Outdoor Structure Surface Contamination

<u>Radionuclide^f</u>	<u>Allowable Residual Surface Contamination^e</u> <u>(dpm/100 cm²)</u>		
	<u>Average^{g,h}</u>	<u>Maximum^{h,i}</u>	<u>Removable^{h,j}</u>
Transuranics, Ra-226, Ra-228, Th-230, Th-228 Pa-231, Ac-227, I-125, I-129	100	300	20
Th-Natural, Th-232, Sr-90, Ra-223, Ra-224 U-232, I-126, I-131, I-133	1,000	3,000	200

TABLE 3-1
(continued)

Page 2 of 2

Indoor/Outdoor Structure Surface Contamination (continued)

<u>Radionuclide</u> ^f	Allowable Residual Surface Contamination ^e (dpm/100 cm ²)		
	<u>Average</u> ^{g,h}	<u>Maximum</u> ^{h,i}	<u>Removable</u> ^{h,j}
U-Natural, U-235, U-238, and associated decay products	5,000 α	15,000 α	1,000 α
Beta-gamma emitters (radionuclides with decay modes other than alpha emission or spontaneous fission) except Sr-90 and others noted above	5,000 β - γ	15,000 β - γ	1,000 β - γ

^aThese guidelines take into account ingrowth of radium-226 from thorium-230 and of radium-228 from thorium-232, and assume secular equilibrium. If either thorium-230 and radium-226 or thorium-232 and radium-228 are both present, not in secular equilibrium, the guidelines apply to the higher concentration. If other mixtures of radionuclides occur, the concentrations of individual radionuclides shall be reduced so that the dose for the mixtures will not exceed the basic dose limit.

^bThese guidelines represent unrestricted-use residual concentrations above background averaged across any 15-cm-thick layer to any depth and over any contiguous 100-m² surface area.

^cLocalized concentrations in excess of these limits are allowable provided that the average concentration over a 100-m² area does not exceed these limits.

^dA working level (WL) is any combination of short-lived radon decay products in 1 liter of air that will result in the ultimate emission of 1.3×10^5 MeV of potential alpha energy.

^eAs used in this table, dpm (disintegrations per minute) means the rate of emission by radioactive material as determined by correcting the counts per minute observed by an appropriate detector for background, efficiency, and geometric factors associated with the instrumentation.

^fWhere surface contamination by both alpha- and beta-gamma-emitting radionuclides exists, the limits established for alpha- and beta-gamma-emitting radionuclides should apply independently.

^gMeasurements of average contamination should not be averaged over more than 1 m². For objects of less surface area, the average shall be derived for each such object.

^hThe average and maximum radiation levels associated with surface contamination resulting from beta-gamma emitters should not exceed 0.2 mrad/h and 1.0 mrad/h, respectively, at 1 cm.

ⁱThe maximum contamination level applies to an area of not more than 100 cm².

^jThe amount of removable radioactive material per 100 cm² of surface area should be determined by wiping that area with dry filter or soft absorbent paper, applying moderate pressure, and measuring the amount of radioactive material on the wipe with an appropriate instrument of known efficiency. When removable contamination on objects of surface area less than 100 cm² is determined, the activity per unit area should be based on the actual area and the entire surface should be wiped. The numbers in this column are maximum amounts.

TABLE 3-2
SURFACE SOIL SAMPLING RESULTS
FOR THE NEW JERSEY VEHICLE INSPECTION STATION PROPERTY

Page 1 of 2

Grid Coordinates		Concentrations (pCi/g +/- 2 sigma)		
E,W	N,S	Uranium-238	Radium-226	Thorium-232
E1020	N1020	<6.0	<0.7	1.7 ± 0.4
E1020	N1120	<5.1	1.0 ± 0.4	1.6 ± 0.5
E1020	N1220	<5.6	<1.2	<2.9
E1020	N1320	<4.9	<1.0	<3.0
E1020	N1420	<5.6	0.8 ± 0.2	<2.3
E1020	N1520	<6.4	0.6 ± 0.4	2.8 ± 0.5
E1020	N1720	<10.2	0.9 ± 0.3	7.1 ± 1.1
E1020	N1820	<9.6	<1.2	9.2 ± 1.7
E1020	N1820	<7.3	0.5 ± 0.1	4.4 ± 0.6
E1040	N1620	<6.9	<1.8	<3.1
E1065	N1670	<6.9	1.0 ± 0.6	2.1 ± 0.2
E1080	N1875	<6.9	0.6 ± 0.4	4.9 ± 0.4
E1125	N1795	<8.0	0.7 ± 0.1	6.2 ± 1.1
E1140	N1560	<8.1	0.9 ± 0.4	4.6 ± 1.2
E1140	N1680	<9.2	1.0 ± 0.2	12.5 ± 2.3
E1140	N1820	<8.2	0.6 ± 0.5	5.4 ± 3.1
E1160	N1910	<8.3	<1.5	7.6 ± 1.3
E1165	N1470	<9.3	<1.2	3.3 ± 0.6
E1170	N1605	<13.8	1.5 ± 0.3	11.5 ± 0.9
E1210	N1340	<5.1	<1.1	<2.4
E1210	N1755	<8.7	1.2 ± 0.1	11.2 ± 2.9
E1220	N0835	<9.4	0.7 ± 0.1	3.5 ± 0.3
E1230	N1470	<7.6	<1.2	4.1 ± 1.1
E1240	N0775	<4.5	0.5 ± 0.1	0.8 ± 0.6
E1265	N1840	<9.3	<1.1	11.4 ± 2.2
E1270	N1830	<10.0	1.0 ± 0.1	9.0 ± 0.8
E1280	N1425	<8.1	<1.1	4.7 ± 0.8
E1315	N1835	<6.3	0.8 ± 0.5	2.5 ± 0.4
E1330	N1430	<5.5	<1.6	<2.9
E1333	N1340	<4.9	1.6 ± 0.4	<2.1
E1333	N1560	<5.9	0.6 ± 0.3	<3.3
E1350	N0710	<7.7	0.7 ± 0.1	5.0 ± 1.3
E1365	N0730	<14.3	1.7 ± 0.5	10.1 ± 2.2
E1370	N0695	<5.6	0.9 ± 0.2	1.2 ± 0.7
E1370	N0825	<4.9	1.0 ± 0.6	1.1 ± 0.4
E1370	N1735	<6.3	0.8 ± 0.1	7.5 ± 1.7
E1375	N0720	<9.9	1.4 ± 0.4	7.5 ± 0.8
E1380	N1470	<6.3	0.8 ± 0.3	1.8 ± 0.1
E1380	N1540	<5.7	0.8 ± 0.4	1.1 ± 0.6
E1380	N1615	<12.3	0.7 ± 0.1	7.0 ± 0.5
E1420	N0960	<7.0	1.0 ± 0.1	1.9 ± 0.7
E1430	N1725	<9.2	<1.4	8.0 ± 1.2
E1480	N0725	<12.1	1.0 ± 0.2	5.9 ± 2.7

TABLE 3-2
(continued)

Page 2 of 2

Grid Coordinates		Concentrations (pCi/g +/- 2 sigma)		
E,W	N,S	Uranium-238	Radium-226	Thorium-232
E1490	N1020	<4.9	0.8 ± 0.1	1.7 ± 0.1
E1490	N1270	<4.6	0.6 ± 0.2	<2.4
E1490	N1470	<5.4	0.7 ± 0.4	2.3 ± 0.5
E1490	N1670	<7.0	0.8 ± 0.3	3.5 ± 0.6
E1490	N1745	<9.4	1.3 ± 0.4	7.8 ± 0.9
E1505	N0900	<6.6	1.1 ± 0.4	3.1 ± 1.4
E1505	N1100	<9.1	<1.8	<4.9
E1505	N1600	<4.3	1.2 ± 0.2	1.4 ± 0.4
E1505	N1700	<7.1	0.7 ± 0.1	4.1 ± 1.7
E1505	N1750	<8.2	1.7 ± 0.3	5.9 ± 0.5

TABLE 3-3
 DOWNHOLE GAMMA LOGGING RESULTS*
 FOR THE NEW JERSEY VEHICLE INSPECTION STATION PROPERTY

Page 1 of 30

<u>Grid Coordinates</u>		<u>Depth</u> (ft)	<u>Counts</u> per Minute
<u>E,W</u>	<u>N,S</u>		
E1000	N0992	0.5	10,000
E1000	N0992	1.0	12,000
E1000	N0992	1.5	12,000
E1000	N0992	2.0	13,000
E1000	N1100	0.5	8,000
E1000	N1100	1.0	10,000
E1000	N1100	1.5	10,000
E1000	N1100	2.0	11,000
E1000	N1100	2.5	10,000
E1000	N1100	3.0	10,000
E1000	N1100	3.5	9,000
E1000	N1100	4.0	9,000
E1000	N1100	4.5	8,000
E1000	N1200	0.5	8,000
E1000	N1200	1.0	10,000
E1000	N1200	1.5	10,000
E1000	N1200	2.0	11,000
E1000	N1200	2.5	11,000
E1000	N1200	3.0	10,000
E1000	N1200	3.5	11,000
E1000	N1200	4.0	9,000
E1000	N1200	4.5	9,000
E1000	N1200	5.0	9,000
E1000	N1300	0.5	10,000
E1000	N1300	1.0	11,000
E1000	N1300	1.5	11,000
E1000	N1300	2.0	10,000
E1000	N1300	2.5	10,000
E1000	N1300	3.0	11,000
E1000	N1300	3.5	10,000
E1000	N1300	4.0	10,000
E1000	N1300	4.5	10,000
E1000	N1300	5.0	8,000
E1000	N1300	5.5	8,000
E1000	N1300	6.0	8,000
E1000	N1300	6.5	8,000
E1000	N1300	7.0	8,000
E1000	N1300	7.5	8,000
E1000	N1300	8.0	8,000
E1000	N1300	8.5	8,000

TABLE 3-3
(continued)

Page 2 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1000	N1300	9.0	8,000
E1000	N1300	9.5	8,000
E1000	N1300	10.0	8,000
E1000	N1300	10.5	8,000
E1000	N1300	11.0	8,000
E1000	N1300	11.5	8,000
E1000	N1300	12.0	9,000
E1000	N1300	12.5	9,000
E1000	N1300	13.0	9,000
E1000	N1300	13.5	9,000
E1000	N1300	14.0	9,000
E1000	N1400	0.5	9,000
E1000	N1400	1.0	9,000
E1000	N1400	1.5	9,000
E1000	N1400	2.0	10,000
E1000	N1400	2.5	9,000
E1000	N1400	3.0	9,000
E1000	N1400	3.5	8,000
E1000	N1400	4.0	8,000
E1000	N1400	4.5	8,000
E1000	N1500	0.5	9,000
E1000	N1500	1.0	10,000
E1000	N1500	1.5	11,000
E1000	N1500	2.0	11,000
E1000	N1500	2.5	11,000
E1000	N1500	3.0	11,000
E1000	N1500	3.5	10,000
E1000	N1500	4.0	9,000
E1000	N1500	4.5	9,000
E1000	N1600	0.5	13,000
E1000	N1600	1.0	12,000
E1000	N1600	1.5	10,000
E1000	N1600	2.0	10,000
E1000	N1600	2.5	9,000
E1000	N1600	3.0	9,000
E1000	N1600	3.5	9,000
E1000	N1600	4.0	8,000
E1000	N1600	4.5	7,000
E1000	N1600	5.0	6,000
E1000	N1600	5.5	7,000

TABLE 3-3
(continued)

Page 3 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
<u>E,W</u>	<u>N,S</u>		
E1000	N1600	6.0	6,000
E1000	N1600	6.5	9,000
E1000	N1650	0.5	15,000
E1000	N1650	1.0	15,000
E1000	N1650	1.5	12,000
E1000	N1650	2.0	12,000
E1000	N1650	2.5	11,000
E1000	N1650	3.0	12,000
E1000	N1650	3.5	11,000
E1000	N1650	4.0	10,000
E1000	N1700	0.5	34,000
E1000	N1700	1.0	41,000
E1000	N1700	1.5	32,000
E1000	N1700	2.0	17,000
E1000	N1700	2.5	11,000
E1000	N1700	3.0	9,000
E1000	N1700	3.5	9,000
E1000	N1700	4.0	9,000
E1000	N1700	4.5	8,000
E1000	N1700	5.0	8,000
E1000	N1700	5.5	7,000
E1000	N1700	6.0	7,000
E1000	N1700	6.5	8,000
E1000	N1700	7.0	12,000
E1000	N1700	7.5	12,000
E1000	N1700	8.0	13,000
E1000	N1700	8.5	13,000
E1000	N1700	9.0	11,000
E1000	N1700	9.5	11,000
E1000	N1750	0.5	50,000
E1000	N1750	1.0	52,000
E1000	N1750	1.5	38,000
E1000	N1750	2.0	60,000
E1000	N1750	2.5	13,000
E1000	N1750	3.0	11,000
E1000	N1750	3.5	10,000
E1000	N1800	0.5	39,000
E1000	N1800	1.0	47,000
E1000	N1800	1.5	36,000

TABLE 3-3
(continued)

Page 4 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1000	N1800	2.0	30,000
E1000	N1800	2.5	38,000
E1000	N1800	3.0	33,000
E1000	N1800	3.5	32,000
E1000	N1800	4.0	61,000
E1000	N1800	4.5	57,000
E1000	N1800	5.0	25,000
E1000	N1800	5.5	12,000
E1000	N1800	6.0	9,000
E1000	N1800	6.5	9,000
E1000	N1800	7.0	9,000
E1000	N1800	7.5	11,000
E1000	N1800	8.0	12,000
E1000	N1800	8.5	10,000
E1000	N1800	9.0	11,000
E1000	N1800	9.5	10,000
E1000	N1800	10.0	11,000
E1004	N1831	0.5	41,000
E1004	N1831	1.0	48,000
E1004	N1831	1.5	52,000
E1004	N1831	2.0	68,000
E1004	N1831	2.5	80,000
E1004	N1831	3.0	63,000
E1004	N1831	3.5	42,000
E1004	N1831	4.0	31,000
E1004	N1831	4.5	40,000
E1004	N1831	5.0	63,000
E1004	N1831	5.5	72,000
E1004	N1831	6.0	90,000
E1004	N1831	6.5	82,000
E1004	N1831	7.0	40,000
E1004	N1831	7.5	19,000
E1004	N1831	8.0	15,000
E1004	N1831	8.5	14,000
E1008	N1875	0.5	43,000
E1008	N1875	1.0	48,000
E1008	N1875	1.5	47,000
E1008	N1875	2.0	25,000
E1008	N1875	2.5	13,000
E1008	N1875	3.0	10,000
E1008	N1875	3.5	11,000

TABLE 3-3
(continued)

Page 5 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1008	N1875	4.0	13,000
E1008	N1875	4.5	13,000
E1008	N1875	5.0	13,000
E1008	N1875	5.5	13,000
E1008	N1875	6.0	12,000
E1008	N1875	6.5	10,000
E1008	N1875	7.0	10,000
E1008	N1875	7.5	9,000
E1008	N1875	8.0	9,000
E1008	N1875	8.5	9,000
E1008	N1875	9.0	9,000
E1020	N1820	0.5	38,000
E1020	N1820	1.0	33,000
E1020	N1820	1.5	23,000
E1020	N1820	2.0	19,000
E1020	N1820	2.5	17,000
E1080	N1875	0.5	27,000
E1080	N1875	1.0	30,000
E1080	N1875	1.5	30,000
E1080	N1875	2.0	31,000
E1080	N1875	2.5	23,000
E1080	N1875	3.0	16,000
E1085	N1747	0.5	28,000
E1085	N1747	1.0	35,000
E1085	N1747	1.5	21,000
E1085	N1747	2.0	15,000
E1085	N1747	2.5	16,000
E1085	N1747	3.0	15,000
E1085	N1747	3.5	16,000
E1085	N1747	4.0	14,000
E1085	N1747	4.5	14,000
E1085	N1747	5.0	11,000
E1085	N1747	5.5	12,000
E1085	N1747	6.0	13,000
E1085	N1747	6.5	12,000
E1085	N1747	7.0	11,000
E1085	N1747	7.5	10,000
E1085	N1747	8.0	10,000
E1100	N0900	0.5	8,000

TABLE 3-3
(continued)

Page 6 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1100	N0900	1.0	12,000
E1100	N0900	1.5	13,000
E1100	N0900	2.0	14,000
E1100	N0900	2.5	13,000
E1100	N0900	3.0	15,000
E1100	N0900	3.5	15,000
E1100	N0900	4.0	15,000
E1100	N0900	4.5	16,000
E1100	N1000	0.5	6,000
E1100	N1000	1.0	7,000
E1100	N1000	1.5	9,000
E1100	N1000	2.0	12,000
E1100	N1000	2.5	14,000
E1100	N1000	3.0	15,000
E1100	N1000	3.5	15,000
E1100	N1000	4.0	14,000
E1100	N1080	0.5	11,000
E1100	N1080	1.0	11,000
E1100	N1080	1.5	11,000
E1100	N1080	2.0	11,000
E1100	N1080	2.5	11,000
E1100	N1080	3.0	11,000
E1100	N1080	3.5	10,000
E1100	N1080	4.0	9,000
E1100	N1080	4.5	10,000
E1100	N1080	5.0	10,000
E1100	N1185	0.5	11,000
E1100	N1185	1.0	12,000
E1100	N1185	1.5	13,000
E1100	N1185	2.0	13,000
E1100	N1185	2.5	12,000
E1100	N1185	3.0	12,000
E1100	N1185	3.5	10,000
E1100	N1185	4.0	9,000
E1100	N1185	4.5	9,000
E1100	N1185	5.0	9,000
E1100	N1185	5.5	10,000
E1100	N1185	6.0	10,000
E1100	N1185	6.5	9,000
E1100	N1185	7.0	9,000

TABLE 3-3
(continued)

Page 7 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1100	N1185	7.5	8,000
E1100	N1185	8.0	8,000
E1100	N1185	8.5	8,000
E1100	N1300	0.5	6,000
E1100	N1300	1.0	6,000
E1100	N1300	1.5	8,000
E1100	N1300	2.0	9,000
E1100	N1300	2.5	9,000
E1100	N1300	3.0	10,000
E1100	N1300	3.5	9,000
E1100	N1300	4.0	9,000
E1100	N1300	4.5	9,000
E1100	N1400	0.5	20,000
E1100	N1400	1.0	19,000
E1100	N1400	1.5	14,000
E1100	N1400	2.0	12,000
E1100	N1400	2.5	9,000
E1100	N1400	3.0	10,000
E1100	N1400	3.5	9,000
E1100	N1400	4.0	8,000
E1100	N1400	4.5	8,000
E1100	N1500	0.5	9,000
E1100	N1500	1.0	9,000
E1100	N1500	1.5	11,000
E1100	N1500	2.0	10,000
E1100	N1500	2.5	9,000
E1100	N1500	3.0	9,000
E1100	N1500	3.5	9,000
E1100	N1500	4.0	8,000
E1100	N1500	4.5	8,000
E1100	N1500	5.0	9,000
E1100	N1700	0.5	23,000
E1100	N1700	1.0	13,000
E1100	N1700	1.5	10,000
E1100	N1700	2.0	12,000
E1100	N1700	2.5	12,000
E1100	N1700	3.0	14,000
E1100	N1700	3.5	10,000
E1100	N1700	4.0	9,000

TABLE 3-3
(continued)

Page 8 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1100	N1700	4.5	8,000
E1100	N1800	0.5	21,000
E1100	N1800	1.0	28,000
E1100	N1800	1.5	18,000
E1100	N1800	2.0	13,000
E1100	N1800	2.5	14,000
E1100	N1800	3.0	19,000
E1100	N1800	3.5	31,000
E1100	N1800	4.0	71,000
E1100	N1800	4.5	20,000
E1100	N1800	5.0	43,000
E1100	N1800	5.5	165,000
E1100	N1800	6.0	162,000
E1100	N1800	6.5	46,000
E1100	N1800	7.0	16,000
E1100	N1800	7.5	11,000
E1100	N1800	8.0	11,000
E1100	N1800	8.5	10,000
E1100	N1800	9.0	9,000
E1100	N1800	9.5	9,000
E1100	N1800	10.0	10,000
E1100	N1855	0.5	35,000
E1100	N1855	1.0	35,000
E1100	N1855	1.5	40,000
E1100	N1855	2.0	44,000
E1100	N1855	2.5	39,000
E1100	N1855	3.0	33,000
E1100	N1855	3.5	54,000
E1100	N1855	4.0	124,000
E1100	N1855	4.5	122,000
E1100	N1855	5.0	45,000
E1100	N1855	5.5	21,000
E1100	N1855	6.0	16,000
E1100	N1855	6.5	15,000
E1100	N1855	7.0	14,000
E1100	N1855	7.5	13,000
E1100	N1855	8.0	13,000
E1100	N1855	8.5	12,000
E1100	N1900	0.5	34,000
E1100	N1900	1.0	54,000

TABLE 3-3
(continued)

Page 9 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1100	N1900	1.5	68,000
E1100	N1900	2.0	35,000
E1100	N1900	2.5	16,000
E1100	N1900	3.0	11,000
E1100	N1900	3.5	9,000
E1100	N1900	4.0	8,000
E1100	N1900	4.5	9,000
E1100	N1900	5.0	10,000
E1100	N1900	5.5	13,000
E1100	N1900	6.0	13,000
E1106	N1818	0.5	11,000
E1106	N1818	1.0	9,000
E1106	N1818	1.5	9,000
E1106	N1818	2.0	9,000
E1106	N1818	2.5	10,000
E1106	N1818	3.0	12,000
E1106	N1818	3.5	14,000
E1106	N1818	4.0	14,000
E1106	N1818	4.5	16,000
E1106	N1818	5.0	19,000
E1106	N1818	5.5	20,000
E1106	N1818	6.0	16,000
E1106	N1818	6.5	15,000
E1110	N1600	0.5	11,000
E1110	N1600	1.0	11,000
E1110	N1600	1.5	12,000
E1110	N1600	2.0	12,000
E1110	N1600	2.5	13,000
E1110	N1600	3.0	11,000
E1110	N1600	3.5	9,000
E1110	N1600	4.0	9,000
E1110	N1600	4.5	9,000
E1125	N1795	0.5	19,000
E1125	N1795	1.0	27,000
E1125	N1795	1.5	23,000
E1125	N1795	2.0	14,000
E1140	N1680	0.5	20,000
E1140	N1680	1.0	19,000
E1140	N1680	1.5	11,000

TABLE 3-3
(continued)

Page 10 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1140	N1680	2.0	11,000
E1140	N1680	2.5	9,000
E1140	N1680	3.0	10,000
E1150	N1660	0.5	34,000
E1150	N1660	1.0	17,000
E1150	N1660	1.5	12,000
E1150	N1660	2.0	11,000
E1150	N1660	2.5	10,000
E1150	N1660	3.0	10,000
E1150	N1700	0.5	38,000
E1150	N1700	1.0	26,000
E1150	N1700	1.5	22,000
E1150	N1700	2.0	18,000
E1150	N1700	2.5	17,000
E1150	N1700	3.0	15,000
E1150	N1700	3.5	10,000
E1165	N1470	0.5	13,000
E1165	N1470	1.0	15,000
E1165	N1470	1.5	15,000
E1165	N1470	2.0	13,000
E1165	N1470	2.5	11,000
E1170	N1605	0.5	38,000
E1170	N1605	1.0	22,000
E1170	N1605	1.5	18,000
E1170	N1605	2.0	11,000
E1170	N1605	2.5	11,000
E1190	N1820	0.5	22,000
E1190	N1820	1.0	14,000
E1190	N1820	1.5	12,000
E1190	N1820	2.0	10,000
E1190	N1820	2.5	11,000
E1190	N1820	3.0	11,000
E1190	N1820	3.5	11,000
E1192	N1749	0.5	43,000
E1192	N1749	1.0	33,000
E1192	N1749	1.5	18,000
E1192	N1749	2.0	16,000

TABLE 3-3
(continued)

Page 11 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1192	N1749	2.5	18,000
E1192	N1749	3.0	17,000
E1192	N1749	3.5	17,000
E1192	N1749	4.0	17,000
E1192	N1749	4.5	12,000
E1192	N1749	5.0	10,000
E1192	N1749	5.5	9,000
E1192	N1749	6.0	9,000
E1192	N1749	6.5	8,000
E1192	N1749	7.0	8,000
E1192	N1749	7.5	8,000
E1192	N1749	8.0	7,000
E1200	N1000	0.5	14,000
E1200	N1000	1.0	11,000
E1200	N1000	1.5	13,000
E1200	N1000	2.0	13,000
E1200	N1000	2.5	13,000
E1200	N1000	3.0	14,000
E1200	N1000	3.5	14,000
E1200	N1000	4.0	13,000
E1200	N1100	0.5	10,000
E1200	N1100	1.0	11,000
E1200	N1100	1.5	11,000
E1200	N1100	2.0	12,000
E1200	N1100	2.5	11,000
E1200	N1100	3.0	12,000
E1200	N1100	3.5	13,000
E1200	N1100	4.0	13,000
E1200	N1100	4.5	14,000
E1200	N1100	5.0	12,000
E1200	N1100	5.5	13,000
E1200	N1100	6.0	14,000
E1200	N1300	0.5	8,000
E1200	N1300	1.0	10,000
E1200	N1300	1.5	10,000
E1200	N1300	2.0	9,000
E1200	N1300	2.5	9,000
E1200	N1300	3.0	9,000
E1200	N1300	3.5	9,000
E1200	N1300	4.0	9,000

TABLE 3-3
(continued)

Page 12 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1200	N1400	0.5	8,000
E1200	N1400	1.0	10,000
E1200	N1400	1.5	11,000
E1200	N1400	2.0	11,000
E1200	N1400	2.5	10,000
E1200	N1400	3.0	9,000
E1200	N1400	3.5	9,000
E1200	N1400	4.0	9,000
E1200	N1400	4.5	9,000
E1200	N1400	5.0	8,000
E1200	N1400	5.5	9,000
E1200	N1400	6.0	10,000
E1200	N1400	6.5	8,000
E1200	N1400	7.0	8,000
E1200	N1400	7.5	7,000
E1200	N1400	8.0	7,000
E1200	N1400	8.5	9,000
E1200	N1400	9.0	9,000
E1200	N1500	0.5	17,000
E1200	N1500	1.0	14,000
E1200	N1500	1.5	11,000
E1200	N1500	2.0	10,000
E1200	N1500	2.5	10,000
E1200	N1500	3.0	10,000
E1200	N1500	3.5	9,000
E1200	N1500	4.0	9,000
E1200	N1500	4.5	10,000
E1200	N1600	0.5	15,000
E1200	N1600	1.0	14,000
E1200	N1600	1.5	9,000
E1200	N1600	2.0	8,000
E1200	N1600	2.5	8,000
E1200	N1600	3.0	7,000
E1200	N1600	3.5	6,000
E1200	N1600	4.0	6,000
E1200	N1600	4.5	6,000
E1200	N1700	0.5	9,000
E1200	N1700	1.0	10,000
E1200	N1700	1.5	12,000
E1200	N1700	2.0	11,000

TABLE 3-3
(continued)

Page 13 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1200	N1700	2.5	11,000
E1200	N1700	3.0	16,000
E1200	N1700	3.5	17,000
E1200	N1700	4.0	16,000
E1200	N1700	4.5	17,000
E1200	N1700	5.0	18,000
E1200	N1808	0.5	22,000
E1200	N1808	1.0	14,000
E1200	N1808	1.5	11,000
E1200	N1808	2.0	10,000
E1200	N1808	2.5	12,000
E1200	N1808	3.0	11,000
E1200	N1808	3.5	10,000
E1200	N1808	4.0	11,000
E1200	N1808	4.5	9,000
E1200	N1808	5.0	9,000
E1200	N1808	5.5	11,000
E1200	N1808	6.0	11,000
E1200	N1808	6.5	10,000
E1200	N1808	7.0	9,000
E1203	N1776	0.5	11,000
E1203	N1776	1.0	10,000
E1203	N1776	1.5	12,000
E1203	N1776	2.0	14,000
E1203	N1776	2.5	13,000
E1203	N1776	3.0	13,000
E1203	N1776	3.5	14,000
E1203	N1776	4.0	13,000
E1203	N1776	4.5	12,000
E1203	N1776	5.0	11,000
E1203	N1776	5.5	13,000
E1203	N1776	6.0	14,000
E1203	N1776	6.5	14,000
E1203	N1776	7.0	11,000
E1203	N1776	7.5	11,000
E1203	N1776	8.0	15,000
E1203	N1776	8.5	17,000
E1203	N1776	9.0	15,000
E1203	N1776	9.5	11,000
E1210	N1755	0.5	56,000

TABLE 3-3
(continued)

Page 14 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1210	N1755	1.0	33,000
E1210	N1755	1.5	16,000
E1210	N1755	2.0	12,000
E1210	N1755	2.5	11,000
E1210	N1910	0.5	16,000
E1210	N1910	1.0	19,000
E1210	N1910	1.5	12,000
E1210	N1910	2.0	9,000
E1210	N1910	2.5	9,000
E1210	N1910	3.0	9,000
E1210	N1910	3.5	8,000
E1210	N1910	4.0	7,000
E1210	N1910	4.5	7,000
E1210	N1910	5.0	7,000
E1210	N1910	5.5	6,000
E1210	N1910	6.0	6,000
E1215	N0840	0.5	18,000
E1215	N0840	1.0	18,000
E1215	N0840	1.5	16,000
E1215	N0840	2.0	16,000
E1215	N0840	2.5	16,000
E1215	N0840	3.0	16,000
E1215	N0840	3.5	14,000
E1215	N0840	4.0	14,000
E1215	N0840	4.5	14,000
E1265	N1880	0.5	36,000
E1265	N1880	1.0	27,000
E1265	N1880	1.5	14,000
E1265	N1880	2.0	12,000
E1265	N1880	2.5	11,000
E1265	N1880	3.0	10,000
E1270	N1220	0.5	27,000
E1270	N1220	1.0	28,000
E1270	N1220	1.5	14,000
E1270	N1220	2.0	11,000
E1270	N1220	2.5	10,000
E1270	N1220	3.0	10,000
E1270	N1220	3.5	9,000
E1270	N1220	4.0	10,000

TABLE 3-3
(continued)

Page 15 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
<u>E,W</u>	<u>N,S</u>		
E1270	N1220	4.5	10,000
E1290	N0775	0.5	11,000
E1290	N0775	1.0	11,000
E1290	N0775	1.5	11,000
E1290	N0775	2.0	11,000
E1290	N0775	2.5	9,000
E1300	N0700	0.5	14,000
E1300	N0700	1.0	12,000
E1300	N0700	1.5	10,000
E1300	N0700	2.0	12,000
E1300	N0700	2.5	14,000
E1300	N0700	3.0	12,000
E1300	N0700	3.5	12,000
E1300	N0700	4.0	13,000
E1300	N0700	4.5	13,000
E1300	N0800	0.5	6,000
E1300	N0800	1.0	8,000
E1300	N0800	1.5	11,000
E1300	N0800	2.0	10,000
E1300	N0800	2.5	10,000
E1300	N0800	3.0	9,000
E1300	N0800	3.5	10,000
E1300	N0800	4.0	11,000
E1300	N0800	4.5	12,000
E1300	N0800	5.0	11,000
E1300	N0900	0.5	13,000
E1300	N0900	1.0	11,000
E1300	N0900	1.5	10,000
E1300	N0900	2.0	11,000
E1300	N0900	2.5	11,000
E1300	N0900	3.0	10,000
E1300	N0900	3.5	11,000
E1300	N0900	4.0	11,000
E1300	N0900	4.5	11,000
E1300	N0900	5.0	11,000
E1300	N0900	5.5	10,000
E1300	N0900	6.0	11,000
E1300	N0900	6.5	11,000
E1300	N0900	7.0	11,000

TABLE 3-3
(continued)

Page 16 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1300	N0900	7.5	11,000
E1300	N0900	8.0	12,000
E1300	N0900	8.5	12,000
E1300	N0900	9.0	12,000
E1300	N0900	9.5	12,000
E1300	N1000	0.5	11,000
E1300	N1000	1.0	11,000
E1300	N1000	1.5	11,000
E1300	N1000	2.0	11,000
E1300	N1000	2.5	12,000
E1300	N1000	3.0	13,000
E1300	N1000	3.5	12,000
E1300	N1000	4.0	13,000
E1300	N1100	0.5	15,000
E1300	N1100	1.0	12,000
E1300	N1100	1.5	12,000
E1300	N1100	2.0	13,000
E1300	N1100	2.5	14,000
E1300	N1100	3.0	13,000
E1300	N1100	3.5	14,000
E1300	N1100	4.0	13,000
E1300	N1200	0.5	18,000
E1300	N1200	1.0	17,000
E1300	N1200	1.5	13,000
E1300	N1200	2.0	12,000
E1300	N1200	2.5	12,000
E1300	N1200	3.0	11,000
E1300	N1200	3.5	10,000
E1300	N1200	4.0	11,000
E1300	N1200	4.5	10,000
E1300	N1200	5.0	11,000
E1300	N1200	5.5	9,000
E1300	N1200	6.0	9,000
E1300	N1200	6.5	8,000
E1300	N1200	7.0	8,000
E1300	N1200	7.5	9,000
E1300	N1200	8.0	7,000
E1300	N1300	0.5	6,000
E1300	N1300	1.0	8,000

TABLE 3-3
(continued)

Page 17 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1300	N1300	1.5	8,000
E1300	N1300	2.0	9,000
E1300	N1300	2.5	9,000
E1300	N1300	3.0	8,000
E1300	N1300	3.5	9,000
E1300	N1300	4.0	9,000
E1300	N1300	4.5	10,000
E1300	N1300	5.0	10,000
E1300	N1400	0.5	8,000
E1300	N1400	1.0	10,000
E1300	N1400	1.5	11,000
E1300	N1400	2.0	13,000
E1300	N1400	2.5	11,000
E1300	N1400	3.0	9,000
E1300	N1400	3.5	9,000
E1300	N1400	4.0	9,000
E1300	N1400	4.5	9,000
E1300	N1400	5.0	9,000
E1300	N1400	5.5	9,000
E1300	N1500	0.5	7,000
E1300	N1500	1.0	8,000
E1300	N1500	1.5	8,000
E1300	N1500	2.0	8,000
E1300	N1500	2.5	8,000
E1300	N1500	3.0	8,000
E1300	N1500	3.5	8,000
E1300	N1500	4.0	8,000
E1300	N1500	4.5	7,000
E1300	N1500	5.0	7,000
E1300	N1500	5.5	7,000
E1300	N1600	0.5	15,000
E1300	N1600	1.0	14,000
E1300	N1600	1.5	9,000
E1300	N1600	2.0	8,000
E1300	N1600	2.5	9,000
E1300	N1600	3.0	8,000
E1300	N1600	3.5	7,000
E1300	N1600	4.0	7,000
E1300	N1600	4.5	6,000
E1300	N1700	0.5	9,000

TABLE 3-3
(continued)

Page 18 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1300	N1700	1.0	9,000
E1300	N1700	1.5	10,000
E1300	N1700	2.0	13,000
E1300	N1700	2.5	10,000
E1300	N1700	3.0	10,000
E1300	N1700	3.5	10,000
E1300	N1700	4.0	14,000
E1300	N1700	4.5	16,000
E1300	N1700	5.0	10,000
E1300	N1700	5.5	8,000
E1300	N1700	6.0	8,000
E1300	N1700	6.5	8,000
E1300	N1700	7.0	9,000
E1300	N1700	7.5	9,000
E1300	N1700	8.0	10,000
E1300	N1700	8.5	11,000
E1300	N1750	0.5	10,000
E1300	N1750	1.0	11,000
E1300	N1750	1.5	13,000
E1300	N1750	2.0	14,000
E1300	N1750	2.5	13,000
E1300	N1750	3.0	13,000
E1300	N1750	3.5	13,000
E1300	N1750	4.0	18,000
E1300	N1750	4.5	19,000
E1300	N1750	5.0	15,000
E1300	N1750	5.5	11,000
E1300	N1750	6.0	9,000
E1300	N1750	6.5	8,000
E1300	N1775	0.5	41,000
E1300	N1775	1.0	66,000
E1300	N1775	1.5	64,000
E1300	N1775	2.0	26,000
E1300	N1775	2.5	15,000
E1300	N1775	3.0	11,000
E1300	N1775	3.5	10,000
E1300	N1775	4.0	10,000
E1300	N1775	4.5	10,000
E1300	N1775	5.0	10,000
E1300	N1775	5.5	10,000
E1300	N1790	0.5	17,000

TABLE 3-3
(continued)

Page 19 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1300	N1790	1.0	17,000
E1300	N1790	1.5	18,000
E1300	N1790	2.0	14,000
E1300	N1790	2.5	14,000
E1300	N1790	3.0	21,000
E1300	N1790	3.5	18,000
E1300	N1790	4.0	15,000
E1300	N1790	4.5	11,000
E1300	N1790	5.0	9,000
E1300	N1790	5.5	9,000
E1300	N1790	6.0	9,000
E1300	N1790	6.5	9,000
E1300	N1790	7.0	9,000
E1300	N1790	7.5	7,000
E1300	N1790	8.0	7,000
E1300	N1822	0.5	11,000
E1300	N1822	1.0	9,000
E1300	N1822	1.5	9,000
E1300	N1822	2.0	10,000
E1300	N1822	2.5	9,000
E1300	N1822	3.0	11,000
E1300	N1822	3.5	14,000
E1300	N1822	4.0	14,000
E1300	N1822	4.5	15,000
E1300	N1822	5.0	12,000
E1300	N1822	5.5	10,000
E1300	N1822	6.0	10,000
E1300	N1822	6.5	9,000
E1300	N1822	7.0	9,000
E1300	N1822	7.5	9,000
E1300	N1822	8.0	9,000
E1300	N1915	0.5	33,000
E1300	N1915	1.0	19,000
E1300	N1915	1.5	12,000
E1300	N1915	2.0	11,000
E1300	N1915	2.5	10,000
E1300	N1915	3.0	9,000
E1300	N1915	3.5	9,000
E1300	N1915	4.0	8,000
E1300	N1915	4.5	7,000
E1300	N1915	5.0	8,000

TABLE 3-3
(continued)

Page 20 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1307	N1890	0.5	17,000
E1307	N1890	1.0	11,000
E1307	N1890	1.5	11,000
E1307	N1890	2.0	11,000
E1307	N1890	2.5	10,000
E1307	N1890	3.0	10,000
E1307	N1890	3.5	9,000
E1307	N1890	4.0	8,000
E1307	N1890	4.5	7,000
E1307	N1890	5.0	7,000
E1307	N1890	5.5	7,000
E1307	N1890	6.0	7,000
E1307	N1890	6.5	7,000
E1307	N1890	7.0	8,000
E1307	N1890	7.5	8,000
E1315	N1835	0.5	19,000
E1315	N1835	1.0	18,000
E1315	N1835	1.5	15,000
E1315	N1835	2.0	10,000
E1315	N1835	2.5	10,000
E1315	N1835	3.0	9,000
E1320	N1540	0.5	7,000
E1320	N1540	1.0	8,000
E1320	N1540	1.5	8,000
E1320	N1540	2.0	8,000
E1320	N1540	2.5	9,000
E1350	N0710	0.5	32,000
E1350	N0710	1.0	33,000
E1350	N0710	1.5	31,000
E1350	N0710	2.0	24,000
E1350	N0710	2.5	20,000
E1370	N1735	0.5	16,000
E1370	N1735	1.0	12,000
E1370	N1735	1.5	11,000
E1370	N1735	2.0	11,000
E1370	N1735	2.5	11,000
E1380	N1615	0.5	35,000
E1380	N1615	1.0	30,000

TABLE 3-3
(continued)

Page 21 of 30

<u>Grid Coordinates</u>		<u>Depth</u> (ft)	<u>Counts</u> per Minute
<u>E,W</u>	<u>N,S</u>		
E1380	N1615	1.5	16,000
E1380	N1615	2.0	10,000
E1380	N1615	2.5	8,000
E1390	N1783	0.5	31,000
E1390	N1783	1.0	47,000
E1390	N1783	1.5	24,000
E1390	N1783	2.0	14,000
E1390	N1783	2.5	12,000
E1390	N1783	3.0	11,000
E1390	N1783	3.5	8,000
E1390	N1783	4.0	8,000
E1390	N1783	4.5	7,000
E1395	N1763	0.5	49,000
E1395	N1763	1.0	57,000
E1395	N1763	1.5	33,000
E1395	N1763	2.0	24,000
E1395	N1763	2.5	37,000
E1395	N1763	3.0	77,000
E1395	N1763	3.5	106,000
E1395	N1763	4.0	55,000
E1395	N1763	4.5	24,000
E1395	N1763	5.0	14,000
E1395	N1763	5.5	14,000
E1395	N1763	6.0	12,000
E1395	N1763	6.5	11,000
E1395	N1763	7.0	11,000
E1396	N1892	0.5	8,000
E1396	N1892	1.0	10,000
E1396	N1892	1.5	11,000
E1396	N1892	2.0	11,000
E1396	N1892	2.5	11,000
E1396	N1892	3.0	11,000
E1396	N1892	3.5	10,000
E1396	N1892	4.0	11,000
E1396	N1892	4.5	9,000
E1396	N1892	5.0	9,000
E1396	N1892	5.5	8,000
E1396	N1892	6.0	7,000
E1396	N1892	6.5	7,000
E1396	N1892	7.0	7,000

TABLE 3-3
(continued)

Page 22 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1396	N1892	7.5	7,000
E1396	N1892	8.0	7,000
E1396	N1892	8.5	7,000
E1400	N0700	0.5	19,000
E1400	N0700	1.0	22,000
E1400	N0700	1.5	25,000
E1400	N0700	2.0	18,000
E1400	N0700	2.5	15,000
E1400	N0700	3.0	17,000
E1400	N0700	3.5	16,000
E1400	N0700	4.0	14,000
E1400	N0700	4.5	14,000
E1400	N0700	5.0	14,000
E1400	N0800	0.5	10,000
E1400	N0800	1.0	11,000
E1400	N0800	1.5	12,000
E1400	N0800	2.0	11,000
E1400	N0800	2.5	12,000
E1400	N0800	3.0	11,000
E1400	N0800	3.5	11,000
E1400	N0800	4.0	12,000
E1400	N0800	4.5	11,000
E1400	N0800	5.0	11,000
E1400	N0900	0.5	11,000
E1400	N0900	1.0	10,000
E1400	N0900	1.5	11,000
E1400	N0900	2.0	11,000
E1400	N0900	2.5	11,000
E1400	N0900	3.0	10,000
E1400	N0900	3.5	11,000
E1400	N0900	4.0	11,000
E1400	N0900	4.5	11,000
E1400	N0900	5.0	11,000
E1400	N0900	5.5	12,000
E1400	N0900	6.0	12,000
E1400	N0900	6.5	13,000
E1400	N1000	0.5	13,000
E1400	N1000	1.0	13,000
E1400	N1000	1.5	13,000

TABLE 3-3
(continued)

Page 23 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
<u>E,W</u>	<u>N,S</u>		
E1400	N1000	2.0	13,000
E1400	N1000	2.5	14,000
E1400	N1000	3.0	13,000
E1400	N1000	3.5	13,000
E1400	N1100	0.5	10,000
E1400	N1100	1.0	12,000
E1400	N1200	0.5	10,000
E1400	N1200	1.0	11,000
E1400	N1200	1.5	13,000
E1400	N1200	2.0	13,000
E1400	N1200	2.5	13,000
E1400	N1200	3.0	13,000
E1400	N1200	3.5	13,000
E1400	N1200	4.0	13,000
E1400	N1300	0.5	5,000
E1400	N1300	1.0	7,000
E1400	N1300	1.5	8,000
E1400	N1300	2.0	8,000
E1400	N1300	2.5	9,000
E1400	N1300	3.0	9,000
E1400	N1300	3.5	9,000
E1400	N1300	4.0	8,000
E1400	N1300	4.5	8,000
E1400	N1400	0.5	10,000
E1400	N1400	1.0	12,000
E1400	N1400	1.5	11,000
E1400	N1400	2.0	10,000
E1400	N1400	2.5	9,000
E1400	N1400	3.0	9,000
E1400	N1400	3.5	9,000
E1400	N1400	4.0	8,000
E1400	N1400	4.5	8,000
E1400	N1500	0.5	8,000
E1400	N1500	1.0	11,000
E1400	N1500	1.5	8,000
E1400	N1500	2.0	9,000
E1400	N1500	2.5	9,000
E1400	N1500	3.0	9,000

TABLE 3-3
(continued)

Page 24 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1400	N1500	3.5	8,000
E1400	N1500	4.0	8,000
E1400	N1500	4.5	8,000
E1400	N1500	5.0	9,000
E1400	N1500	5.5	9,000
E1400	N1600	0.5	22,000
E1400	N1600	1.0	20,000
E1400	N1600	1.5	11,000
E1400	N1600	2.0	9,000
E1400	N1600	2.5	9,000
E1400	N1600	3.0	7,000
E1400	N1600	3.5	6,000
E1400	N1600	4.0	6,000
E1400	N1600	4.5	7,000
E1400	N1600	5.0	9,000
E1400	N1600	5.5	9,000
E1400	N1600	6.0	9,000
E1400	N1600	6.5	9,000
E1400	N1600	7.0	9,000
E1400	N1600	7.5	10,000
E1400	N1600	8.0	10,000
E1400	N1600	8.5	10,000
E1400	N1600	9.0	10,000
E1400	N1640	0.5	20,000
E1400	N1640	1.0	20,000
E1400	N1640	1.5	13,000
E1400	N1640	2.0	11,000
E1400	N1640	2.5	10,000
E1400	N1640	3.0	9,000
E1400	N1640	3.5	10,000
E1400	N1640	4.0	10,000
E1400	N1640	4.5	10,000
E1400	N1700	0.5	25,000
E1400	N1700	1.0	26,000
E1400	N1700	1.5	21,000
E1400	N1700	2.0	14,000
E1400	N1700	2.5	13,000
E1400	N1700	3.0	12,000
E1400	N1700	3.5	10,000
E1400	N1700	4.0	8,000

TABLE 3-3
(continued)

Page 25 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1400	N1700	4.5	8,000
E1400	N1730	0.5	17,000
E1400	N1730	1.0	31,000
E1400	N1730	1.5	53,000
E1400	N1730	2.0	70,000
E1400	N1730	2.5	44,000
E1400	N1730	3.0	18,000
E1400	N1730	3.5	13,000
E1400	N1730	4.0	12,000
E1400	N1730	4.5	13,000
E1400	N1730	5.0	12,000
E1400	N1850	0.5	16,000
E1400	N1850	1.0	12,000
E1400	N1850	1.5	10,000
E1400	N1850	2.0	10,000
E1400	N1850	2.5	8,000
E1400	N1850	3.0	8,000
E1400	N1850	3.5	7,000
E1400	N1850	4.0	8,000
E1400	N1900	0.5	11,000
E1400	N1900	1.0	10,000
E1400	N1900	1.5	10,000
E1400	N1900	2.0	9,000
E1400	N1900	2.5	9,000
E1400	N1900	3.0	9,000
E1400	N1900	3.5	9,000
E1400	N1900	4.0	9,000
E1400	N1900	4.5	8,000
E1475	N1935	0.5	11,000
E1475	N1935	1.0	11,000
E1475	N1935	1.5	11,000
E1475	N1935	2.0	12,000
E1475	N1935	2.5	10,000
E1475	N1935	3.0	10,000
E1475	N1935	3.5	9,000
E1475	N1935	4.0	9,000
E1475	N1935	4.5	8,000
E1475	N1935	5.0	7,000
E1475	N1935	5.5	8,000

TABLE 3-3
(continued)

Page 26 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1475	N1935	6.0	8,000
E1475	N1935	6.5	7,000
E1475	N1935	7.0	7,000
E1480	N0725	0.5	26,000
E1480	N0725	1.0	23,000
E1480	N0725	1.5	16,000
E1480	N0725	2.0	15,000
E1480	N0725	2.5	13,000
E1480	N0725	3.0	13,000
E1490	N1700	0.5	25,000
E1490	N1700	1.0	30,000
E1490	N1700	1.5	36,000
E1490	N1700	2.0	34,000
E1490	N1700	2.5	20,000
E1490	N1700	3.0	15,000
E1490	N1700	3.5	13,000
E1490	N1700	4.0	13,000
E1490	N1700	4.5	12,000
E1490	N1700	5.0	11,000
E1490	N1745	0.5	46,000
E1490	N1745	1.0	51,000
E1490	N1745	1.5	82,000
E1490	N1745	2.0	98,000
E1490	N1745	2.5	85,000
E1490	N1745	3.0	53,000
E1490	N1745	3.5	20,000
E1490	N1745	4.0	15,000
E1490	N1745	4.5	9,000
E1490	N1745	5.0	9,000
E1499	N1773	0.5	39,000
E1499	N1773	1.0	57,000
E1499	N1773	1.5	26,000
E1499	N1773	2.0	15,000
E1499	N1773	2.5	12,000
E1499	N1773	3.0	11,000
E1499	N1773	3.5	10,000
E1499	N1773	4.0	10,000
E1500	N0700	0.5	20,000

TABLE 3-3
(continued)

Page 27 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1500	N0700	1.0	14,000
E1500	N0700	1.5	13,000
E1500	N0700	2.0	12,000
E1500	N0700	2.5	13,000
E1500	N0700	3.0	13,000
E1500	N0700	3.5	12,000
E1500	N0700	4.0	11,000
E1500	N0700	4.5	11,000
E1500	N0700	5.0	9,000
E1500	N0700	5.5	8,000
E1500	N0700	6.0	7,000
E1500	N0800	0.5	12,000
E1500	N0800	1.0	12,000
E1500	N0800	1.5	12,000
E1500	N0800	2.0	13,000
E1500	N0800	2.5	17,000
E1500	N0800	3.0	15,000
E1500	N0800	3.5	13,000
E1500	N0800	4.0	13,000
E1500	N0800	4.5	12,000
E1500	N0800	5.0	12,000
E1500	N0800	5.5	11,000
E1500	N0800	6.0	12,000
E1500	N0800	6.5	12,000
E1500	N0900	0.5	12,000
E1500	N0900	1.0	13,000
E1500	N0900	1.5	14,000
E1500	N0900	2.0	14,000
E1500	N0900	2.5	14,000
E1500	N0900	3.0	13,000
E1500	N0900	3.5	14,000
E1500	N0900	4.0	14,000
E1500	N0900	4.5	13,000
E1500	N0900	5.0	13,000
E1500	N1000	0.5	11,000
E1500	N1000	1.0	14,000
E1500	N1000	1.5	13,000
E1500	N1100	0.5	11,000
E1500	N1200	0.5	8,000

TABLE 3-3
(continued)

Page 28 of 30

Grid Coordinates		Depth (ft)	Counts per Minute
E,W	N,S		
E1500	N1200	1.0	9,000
E1500	N1200	1.5	12,000
E1500	N1300	0.5	10,000
E1500	N1300	1.0	11,000
E1500	N1300	1.5	11,000
E1500	N1300	2.0	9,000
E1500	N1300	2.5	9,000
E1500	N1300	3.0	10,000
E1500	N1300	3.5	10,000
E1500	N1300	4.0	9,000
E1500	N1300	4.5	9,000
E1500	N1300	5.0	8,000
E1500	N1300	5.5	8,000
E1500	N1300	6.0	8,000
E1500	N1300	6.5	8,000
E1500	N1300	7.0	8,000
E1500	N1300	7.5	9,000
E1500	N1300	8.0	11,000
E1500	N1300	8.5	12,000
E1500	N1300	9.0	11,000
E1500	N1400	0.5	10,000
E1500	N1400	1.0	12,000
E1500	N1400	1.5	11,000
E1500	N1400	2.0	10,000
E1500	N1400	2.5	9,000
E1500	N1400	3.0	9,000
E1500	N1400	3.5	9,000
E1500	N1400	4.0	8,000
E1500	N1400	4.5	8,000
E1500	N1400	5.0	9,000
E1500	N1400	5.5	8,000
E1500	N1500	0.5	9,000
E1500	N1500	1.0	10,000
E1500	N1500	1.5	10,000
E1500	N1500	2.0	10,000
E1500	N1500	2.5	10,000
E1500	N1500	3.0	8,000
E1500	N1500	3.5	8,000
E1500	N1500	4.0	7,000
E1500	N1500	4.5	8,000

TABLE 3-3
(continued)

Page 29 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1500	N1500	5.0	8,000
E1500	N1600	0.5	13,000
E1500	N1600	1.0	11,000
E1500	N1600	1.5	10,000
E1500	N1600	2.0	9,000
E1500	N1600	2.5	8,000
E1500	N1600	3.0	8,000
E1500	N1600	3.5	7,000
E1500	N1600	4.0	8,000
E1500	N1600	4.5	8,000
E1500	N1650	0.5	36,000
E1500	N1650	1.0	37,000
E1500	N1650	1.5	49,000
E1500	N1650	2.0	31,000
E1500	N1650	2.5	19,000
E1500	N1650	3.0	18,000
E1500	N1650	3.5	14,000
E1500	N1650	4.0	15,000
E1500	N1800	0.5	22,000
E1500	N1800	1.0	15,000
E1500	N1800	1.5	11,000
E1500	N1800	2.0	10,000
E1500	N1800	2.5	9,000
E1500	N1800	3.0	9,000
E1500	N1800	3.5	8,000
E1500	N1800	4.0	8,000
E1500	N1800	4.5	8,000
E1500	N1850	0.5	25,000
E1500	N1850	1.0	18,000
E1500	N1850	1.5	15,000
E1500	N1850	2.0	13,000
E1500	N1850	2.5	13,000
E1500	N1850	3.0	12,000
E1500	N1850	3.5	12,000
E1500	N1850	4.0	10,000
E1500	N1850	4.5	10,000
E1500	N1850	5.0	9,000
E1500	N1875	0.5	13,000

TABLE 3-3
(continued)

Page 30 of 30

<u>Grid Coordinates</u>		Depth (ft)	Counts per Minute
E,W	N,S		
E1500	N1875	1.0	12,000
E1500	N1875	1.5	13,000
E1500	N1875	2.0	13,000
E1500	N1875	2.5	12,000
E1500	N1875	3.0	13,000
E1500	N1875	3.5	12,000
E1500	N1875	4.0	11,000
E1500	N1900	0.5	9,000
E1500	N1900	1.0	11,000
E1500	N1900	1.5	11,000
E1500	N1900	2.0	11,000
E1500	N1900	2.5	9,000
E1500	N1900	3.0	10,000
E1500	N1900	3.5	10,000
E1500	N1900	4.0	9,000
E1500	N1900	4.5	10,000
E1507	N1735	0.5	18,000
E1507	N1735	1.0	16,000
E1507	N1735	1.5	14,000
E1507	N1735	2.0	10,000
E1507	N1735	2.5	9,000
E1507	N1735	3.0	9,000
E1507	N1735	3.5	9,000
E1507	N1735	4.0	10,000

^aThe results given in this table are based on penetrating the contamination or the drill reaching refusal. Any other circumstances are noted for the hole to which they apply.

TABLE 3-4
 GAMMA RADIATION EXPOSURE RATE MEASUREMENTS
 FOR THE NEW JERSEY VEHICLE INSPECTION STATION PROPERTY

Location Number	<u>Grid Coordinates</u>		Exposure Rate (μ R/h)
	E,W	N,S	
1	E1275	N1190	5
2	E1280	N1180	4
3	E1160	N1175	4
4	E1250	N1150	4
5	E1200	N1150	4
6	E1275	N1110	4
7	E1280	N1125	4
8	E1160	N1130	4

REFERENCES

1. U.S. Department of Energy. Description of the Formerly Utilized Sites Remedial Action Program, ORO-777, Oak Ridge, TN, September 1980 (as modified by DOE in October 1983).
2. Oak Ridge National Laboratory. Results of the Radiological Survey at 8 Mill Street, Lodi, New Jersey, Oak Ridge, TN, August 1984.
3. Morton, Henry W., Natural Thorium in Maywood, New Jersey, Nuclear Safety Associates, Inc., Potomac, MD, September 29, 1982.
4. U.S. Department of Energy. "U.S. Department of Energy Guidelines for Residual Radioactivity at Formerly Utilized Sites Remedial Action Program and Remote Surplus Facilities Management Program Sites," Rev. 1, July 1985.
5. Trip Report, C. P. Leichtweis, Bechtel National, Inc., to File. "Calibration and Functional Checks of Eberline Instrumentation," CCN 35677, March 25, 1986.
6. U.S. Code of Federal Regulations. 40 CFR 192, "Health and Environmental Protection Standards for Uranium and Thorium Mill Tailings," Washington, DC, July 1986.
7. National Council on Radiation Protection and Measurements. Environmental Radiation Measurements, NCRP Report No. 50, Washington, DC, December 27, 1986.

APPENDIX A
GEOLOGIC DRILL LOGS FOR THE
MAYWOOD INTERIM STORAGE SITE
- NEW JERSEY VEHICLE INSPECTION STATION



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
				FUSRAP			14501-130		1 OF 1		MISS-213R		
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES					ANGLE FROM HORIZ.		BEARINGS		
				N1875,E1000					90°		N/A		
BEGIN		COMPLETED		DRILLER			DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH
7/21/86		7/21/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33		6"		10.0'	0.0'	10.0'
CORE RECOVERY (FT./%)			CORE BOXES		SAMPLES	EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK	
N/A			N/A		N/A	N/A		96.25'		8.5' / 87.75'		N/A	
SAMPLE NUMBER BEHIND/ALL				CASING LEFT IN HOLE; DIA./LENGTH				LOGGED BY:					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH CORE DIA.	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS %	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOSS IN FT. P.S.P.A.	PRESSURE P.S.I.	TIME IN MINUTES						
AUGER, 6" THROUGHOUT.								96.25	0			0.0-1.5': SANDY SILT (G1); DARK YELLOWISH BROWN (GYR4/2); FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. ▽ 7/21/86
							92.75	5			1.5-10.0': SILTY SAND (SM-SC) FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; MOSTLY DRY (SEE DRILL NOTES). 3.5-4.5': MODERATE BROWN (SYR3/4); FINE GRAINED; CLAY BINDER; FEW ORGANICS. 4.5-10.0': DARK YELLOWISH ORANGE (GYR6/6); FINE TO COARSE GRAINED; SATURATED (GLS-10.0 FT).		
								86.25	10				
									15			BOTTOM OF HOLE AT 10.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	-DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. SATURATED DRILL SPOILS FROM 8.5-10.0 FT.
									20				
									25				
									30				
									35				ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.



GEOLOGIC DRILL LOG				PROJECT				JOB NO.		SHEET NO.		HOLE NO.	
				FUSRAP				14501-130		1 OF 1		NISS-214R	
SITE				COORDINATES				ANGLE FROM HORIZ.		BEARDS			
MAYWOOD INTERIM STORAGE SITE - NJVIS				N1900, E1100				90°				N/A	
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		TOTAL DEPTH	
7/21/86		7/21/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		7.5'		7.5'	
CORE RECOVERY (FT./%)		CORE BOXES		SAMPLES		EL. TOP OF CASING		GRIND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK	
N/A		N/A		N/A		N/A		96.25'		NONE OBSERVED		N/A	
SAMPLE NUMBER WEIGHT/FILL				CASING LEFT IN HOLE, DIA./LENGTH				LOGGED BY:					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH CORE RUN	SAMPLE WEIGHT CORE RECOVERY	SAMPLE DIA. PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
				LONG IN P.S.I.	PRESSURE P.S.I.	TIME IN MINUTES							
AUGER, 6" THROUGHOUT.							96.25	0					
							93.75			0.0-2.5: SANDY SILT (SL); DARK YELLOWISH BROWN (OYR4/2); FINE GRAINED; SOFT; POORLY SORTED; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); POORLY CONSOLIDATED; DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.		
								5		2.5-7.5: SILTY SAND (SM-SC); FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; DRY TO SLIGHTLY MOIST.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.		
							88.75	7.5			3.5-4.5: MODERATE BROWN (GYR3/4); FINE GRAINED; CLAY BINDERS; FEW ORGANICS.		
								10			4.5-7.5: DARK YELLOWISH ORANGE (OYR6/6); FINE TO COARSE GRAINED. BOTTOM OF HOLE AT 7.5 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.	
								15					
								20					
								25					
								30					
								35					
SS-SPLIT SPONS; ST-SHEDDY TAIL; D-DUMPS; P-PICKED; O-OTHER				SITE				MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO. NISS-214R	



GEOLOGIC DRILL LOG				PROJECT				JOB NO.		SHEET NO.		HOLE NO.			
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP				14501-130		1 OF 1		NISS-215R			
SITE				COORDINATES				ANGLE FROM HORIZ.		BEARINGS					
				N1910, E1210				90°		N/A					
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)		TOTAL DEPTH	
7/21/86		7/21/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		7.5'		0.0'		7.5'	
CORE RECOVERY (L./3)		CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK			
N/A		N/A		N/A		N/A		96.3'		NONE OBSERVED		N/A			
SAMPLE NUMBER BEGIN/END				CASING LEFT IN HOLE DIA./LENGTH				LOGGED BY							
N/A				N/A				D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH - LENGTH OF CORE TUB	SAMPLE INTERVAL - CORE NUMBER	SAMPLE BEARS - PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.			
				LOGS IN P.S.P.A.	PRELIM. P.S.P.A.	TIME IN MINUTES									
AUGER, 6" THROUGHOUT.							96.3	0				SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.			
							94.8	5		0.0-1.5: SANDY SILT (S); DARK YELLOWISH BROWN (DTR4/2); FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; DRY TO SLIGHTLY MOIST. 1.5-7.5: SILTY SAND (S); DARK YELLOWISH ORANGE (DTR6/6); FINE TO COARSE GRAINED; SOFT; POORLY CONSOLIDATED; DRY TO SLIGHTLY MOIST. 1.5-5.0: FINE GRAINED. 5.0-7.5: FINE TO COARSE GRAINED; POORLY SORTED.					
							88.8	7.5							
								10			BOTTOM OF HOLE AT 7.5 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.			
								15				ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM			
								20							
								25							
								30							
								35							



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				MOBILE FROM HORIZ.		BEARING	
										N1915, E1300				90°		N/A	
BEGIN		COMPLETED		DRILLER			DRILL MAKE AND MODEL			HOLE DIA.		OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH	
7/21/86		7/21/86		MOORE TRENCH ENVIRONMENTAL SERVICES			MOBILE B-33			6"		5.0'		0.0'		5.0'	
CORE RECOVERY (FT./30)			CORE BOXES		SAMPLES		DL. TOP OF CASING		GROUND DL.		DEPTH/CL. GROUND WATER			DEPTH/CL. TOP OF ROCK			
N/A			N/A		N/A		N/A		96.89		NONE OBSERVED			N/A			
SAMPLE NUMBER: NONE/ALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER TYPE/MAKE/LENGTH/DEPTH	SAMPLE RECOVERY/DEPTH	SAMPLE LOSS	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
				LOGS	PRESSURE	TIME											
AUGER, 6" THROUGHOUT							96.89	0									
							94.89			0.0-2.0': SANDY SILT (CL); MODERATE BROWN (5YR5/0) FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.						
							91.89	5		2.0-5.0': SILTY SAND (SM); DARK YELLOWISH ORANGE (4YR6/6) FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; SLIGHTLY MOIST.							
										BOTTOM OF HOLE AT 5.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.						
								10									
								15									
								20									
								25									
								30									
								35									

30-SPLIT 3000L 57-DIA BY T&E
D-RENDER P-PATCH 0-0788

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. MISS-216R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.	SHEET NO.	HOLE NO.	
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS										FUSRAP		14501-138	1 OF 1	NISS-217R	
COORDINATES					N1900,E1400					ANGLE FROM HORIZ.	BEARINGS				
DRILLER	COMPLETED	DRILLER			DRILL MAKE AND MODEL		HOLE SIZE	OVERLAP (FT.)	RICK (FT.)	TOTAL DEPTH					
7/21/86	7/21/86	MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33		6"	5.0'	0.0'	5.0'					
CORE RECOVERY (FT./%)		CORE DIAM.	SAMPLES	EL. TOP OF CASING	GROUND EL.	REPT./EL. GROUND WATER		DEPTH/EL. TOP OF RICK							
N/A		N/A	N/A	N/A	97.25'	NONE OBSERVED		N/A							
SAMPLE NUMBER (DEPTH/VAL)			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:									
N/A			N/A			D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH (CORE RECOVERY)	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS %	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.		
					LOG IN FT. P.S.P.A.	PRESSURE P.S.I.	TIME IN MINUTES								
AUGER 6" THROUGHOUT.								97.25	0						
								95.75				0.0-1.5'; SANDY SILT (CL); DARK YELLOWISH BROWN (10YR4/2) FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.		
								92.25	5			1.5-3.0'; SILTY SAND (SM FINE TO COARSE GRAINED); SOFT; POORLY SORTED; POORLY CONSOLIDATED; DRY TO SLIGHTLY MOIST.			
												3.0-5.0'; MODERATE BROWN (5YR3/4); 3.5-5.0'; DARK YELLOWISH ORANGE (10YR6/6) SLIGHTLY MOIST. BOTTOM OF HOLE AT 50 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.			
									10				EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.		
									15						
									20						
									25						
									30						
									35						
80-8PLT SPDS ST-80BY TUBE, 8-80808 8-80808 8-80808										SITE		MAYWOOD INTERIM STORAGE SITE - NJVIS		HOLE NO.	NISS-217R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
SITE MAYWOOD INTERIM STORAGE SITE-NJVIS				FUSRAP		14501-130	1 OF 1	MISS-210R					
COORDINATES				N1900,E1500		ANGLE FROM HORIZ.		BEARING					
						90°		N/A					
DRILLER	COMPLETED	DRILLER	DRILL MAKE AND MODEL	HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH						
7/21/06	7/21/06	MOORE TRENCH ENVIRONMENTAL SERVICES	MOBILE B-33	6"	5.0'	0.0'	5.0'						
CORE RECOVERY(%)		CORE BOXES	SAMPLES	REL. TOP OF CASING	GROUND EL.	DEPTH/REL. GROUND WATER		DEPTH/REL. TOP OF ROCK					
N/A		N/A	N/A	N/A	97.4'	NONE OBSERVED		N/A					
SAMPLE NUMBER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./DEPTH			LOGGED BY:							
N/A			N/A			D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLE ADVANCE LIGHTLY CORE RUN	SAMPLE INTERRUPT CORE RECOVERY	SAMPLE IN CORE	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG IN FT. IN	P.S.F.	TIME IN MINUTES						
AUGER, 6" THROUGHOUT.								97.4	0				
								96.4				0.0-1.0': SANDY SILT (OL); DARK YELLOWISH BROWN (OYR4/2); FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.
								92.4	5			1.0-4.0': SILTY SAND (SM-SL); FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; DRY; SLIGHTLY MOIST. 4.0-5.0': MODERATE BROWN (SYR3/4); FINE GRAINED; SLIGHTLY MOIST. BOTTOM OF HOLE AT 5.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	
									10			EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.	
									15				ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
									20				
									25				
									30				
									35				

30-SPLT SPONG ST-BELBY TUBE;
P-CORING; P-FITCHER; Q-OTHER

BYE

MAYWOOD INTERIM STORAGE SITE-NJVIS

HOLE NO.

MISS-210R



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
				FUSRAP			14501-138		1 OF 1		MISS-219R		
SITE				COORDINATES				ANGLE FROM NORTH		BEARING			
MAYWOOD INTERIM STORAGE SITE - NJVIS				N1900,E1500				90°		N/A			
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)	TOTAL DEPTH
7/21/86		7/21/86		MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		0.0'	5.0'
CORE RECOVERY (FT./%)			CORE BOXES		SAMPLES	EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK	
N/A			N/A		N/A	N/A		99		NONE OBSERVED		N/A	
SAMPLE NUMBER				CASING LEFT IN HOLE DIA./LENGTH				LOGGED BY:					
N/A				N/A				D. MCGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLED APPROX. LENGTH CORE IN IN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE NO. OR IDENTIFY CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION**	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
				LOSS IN FT. G.P.A.	PRESSURE IN P.S.I.	TIME IN MINUTES							
Auger, 6", THROUGHOUT.								0			0.0-2.5'; SANDY SILT (DL); DARK YELLOWISH BROWN (DYR4/2); WITH A MODERATE BROWN (SYR3/4) ZONE FROM 2.0-2.5 FT.; FINE GRAINED WITH OCCASIONAL PEBBLES; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS)	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.	
								5			2.5-5.0'; SILTY SAND (SH); DARK YELLOWISH BROWN (DYR4/2); WITH A PALE YELLOWISH BROWN (DYR6/2) ZONE FROM 4.5-5.0 FT.; FINE TO MEDIUM GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; SLIGHTLY MOIST. BOTTOM OF HOLE AT 5.0 FT.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION SOLELY BY VISUAL EXAMINATION OF CUTTINGS. ** GROUND ELEVATION NOT KNOWN	
								10					
								15					
								20					
								25					
								30					
								35					

SS-SPLIT SPOON; ST-SHELBY TUBE; P-PITCHER; O-OTHER

SITE

MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO.

MISS-219R



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP			14501-138		1 OF 1		MISS-220R		
SITE				COORDINATES				ANGLE FROM HORIZ.		BEARING			
				N1783, E1390				90°		N/A			
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)	TOTAL DEPTH
7/21/86		7/21/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		0.0'	5.0'
CORE RECOVERY (%)			CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK
N/A			N/A		N/A		N/A		94.96'		4.0' / 90.96'		N/A
SAMPLE NUMBER BEING P/ALL				CASING LEFT IN HOLE DIA./LENGTH				LOGGED BY					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLES	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
				LOSS IN P.S.P.A.	PRESSURE P.S.I.	TIME IN P. MINUTES							
AUGER, 6" THROUGHOUT.							94.96	0					
							92.46				0.0-2.5'; SANDY SILT (CL); MODERATE BROWN (GYR) 3/4 FINE GRAINED SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); OCCASIONAL PEBBLES AND SMALL COBBLES; DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION 7/21/86	
							89.96	5			2.5-5.0'; SILTY SAND (SM-SCH) DARK YELLOWISH BROWN (GYR) 4/2; FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; SLIGHTLY MOIST; SATURATED 4.0-5.0 FT. BOTTOM OF HOLE AT 5.0 FT.		EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
								10					
								15					
								20					
								25					
								30					
								35					




GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				MOBILE FROM HOLE		BEARING	
										N1790, E1300				90°		N/A	
DATE		COMPLETED		DRILLER				DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH	
7/22/86		7/22/86		MORE TRENCH ENVIRONMENTAL SERVICES				MOBILE 8-33		6"		10.0'		0.0'		10.0'	
CORE RECOVERY (FT./TD)			CORE BOXES		SAMPLES		DL. TOP OF CASING		GROUND DL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
N/A			N/A		N/A		N/A		97.0'		8.5'/89.5'		N/A				
SAMPLE NUMBER HEIGHT/FALL				CASING LEFT IN HOLE; DIA./LENGTH				LOGGED BY:									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH/DEPTH CORRECTION	SAMPLE RECOVERY CORRECTION	SAMPLE LOSS %	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.				
					LOG IN P.S.I.	IN P.S.I.	TIME IN MINUTES										
AUGER, 6"; THROUGHOUT.							97.0	0					SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. 7/22/86				
							91.0	5			0.0-6.0': SANDY SILT (CL); FINE GRAINED; SOFT; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); SLIGHTLY MOIST. 0.0-4.5': MODERATE BROWN (SYR3/4); POORLY SORTED; POORLY CONSOLIDATED. 4.5-6.0': DARK REDDISH BROWN (ORS/4); DENSE IN PLACE; FEW ORGANICS; CLAY BINDER.						
							87.0	10			6.0-10.0': SILTY SAND (SH-SC); DARK YELLOWISH BROWN (OYR4/2); FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; MOIST TO SATURATED (8.5-10.0 FT.).						
								15					ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM. * DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.				
								20									
								25									
								30									
								35									
30-SPLIT SPIN; ST-DRILLY TOOL; P-DRILLING; P-DRILLING; P-DRILLING										SITE		MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO.	
																MISS-221R	



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				14501-130		1 OF 1		NISS-222R	
										N1800,E1200				MILE FROM HORIZ.		90°		BEARING	
										N1800,E1200				90°		N/A			
BEGIN		COMPLETED		DRILLER				DRILL NAME AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)		TOTAL DEPTH			
7/22/06		7/22/06		MORETRENCH ENVIRONMENTAL SERVICES				MOBILE B-33		6"		7.5'		0.0'		7.5'			
CORE RECOVERY(FT./%)		CORE DIAM.		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK							
N/A		N/A		N/A		N/A		99.0'		NONE OBSERVED		N/A							
SAMPLE NUMBER RECVT./FALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:											
N/A				N/A				D. McGRANE											
SAMPLE TYPE AND DIAMETER	SAMPLED ADVANCE LENGTH CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE BLANK	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAVIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.						
					LOGS IN	IN	IN												
								99.0	0										
AUGER, 6" THROUGHOUT.							98.0					0.0-1.0': SANDY SILT (OL); MODERATE BROWN (5TR3/25 FINE GRAINED) SOFT, POORLY SORTED, POORLY CONSOLIDATED; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.						
								5				1.0-7.5': SILTY SAND (SM-SC); FINE TO COARSE GRAINED; SOFT; SLIGHTLY MOIST.							
								91.5	7.5					1.0-5.0': DARK YELLOWISH BROWN (OYR4/2); FINE GRAINED; POORLY CONSOLIDATED. 5.0-6.0': DARK REDDISH BROWN (OR3/4); CLAY BINDER; DENSE IN PLACE. 6.0-7.5': DARK YELLOWISH BROWN (OYR4/2); WITH 0.5-1.0' PALE GREEN (SG7/2) CLAYEY LENSES; DENSE IN PLACE.					
									10			BOTTOM OF HOLE AT 7.5 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.						
									15										
									20										
									25										
									30										
									35										
28-SPLT SPONGE ST-CHLBY TUBE; 2-DRILLING PATCHES 6-OTHER										SITE		MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO.			
																NISS-222R			



GEOLOGIC DRILL LOG				PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES		14501-138		1 OF 1		M1SS-223R			
				N1800, E1100		ANGLE FROM HORIZ.		90°		DIP/SLOPE			
				N/A		N/A		N/A		N/A			
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)			
7/22/86		7/22/86		MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		10.0'			
CORE RECOVERY (FT./%)		CORE BONES		SAMPLES		BL. TOP OF CASING		GROUND EL.		DEPT./VEL. GROUND WATER			
N/A		N/A		N/A		N/A		96.25'		7.5' / 88.75'			
DEPT./VEL. TOP OF ROCK		CABLES LEFT IN HOLE; DIA./LENGTH		LOGGED BY:									
N/A		N/A		D. MCGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH (CORE RUN)	SAMPLE RECOVERY (CORE RECOVERY)	SAMPLE LOSS (%)	WATER PRESSURE TESTS				ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOG	IN	PSIA	PSI						
ALUER, 6" THROUGHOUT.							96.25	0					
							95.25	5			0.0-1.0': SANDY SILT (G2) MODERATE BROWN (GYR3/4) BOTTLED WITH GRAY BLACK (G2) CLAYEY ZONES; FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS (GRASS ROOTS); SLIGHTLY MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBENLINE ANALYTICAL CORPORATION. EBENLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.  7/22/86	
							10				1.0-10.0': SILTY SAND (SM-SGS) COLOR STRATIFIED FINE TO COARSE GRAINED; SOFT WITH A DENSE CLAYEY ZONE FROM 4.5-6.0 FT; SLIGHTLY MOIST; SATURATED AT 7.5 FT. 1.0-3.0': DARK REDDISH BROWN (GCR3/4); OCCASIONAL PEBBLES; POORLY SORTED. 3.0-4.5': MODERATE BROWN; OCCASIONAL PEBBLES; POORLY SORTED. 4.5-6.0': GRAYISH BLACK (G2) CLAY BINDER; DENSE IN PLACE; SMALL PIECES OF METAL FILL. 6.0-10.0': DARK YELLOWISH BROWN (GYR4/2); POORLY CONSOLIDATED.		
											6.0-10.0': DARK YELLOWISH BROWN (GYR4/2); POORLY CONSOLIDATED. BOTTOM OF HOLE AT 10.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		
								15					
								20					
								25					
								30					
								35					

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

30-45 FT. SPACING; 57-60 IN. DIA. TUBING; 1/2" DIA. DRILL BIT; 1/2" DIA. DRILL RODS

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. M1SS-223R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
MAYWOOD INTERIM STORAGE SITE - NJVIS										FUSRAP				14501-138		1 OF 1		NISS-224R	
COORDINATES										N1800, E1000				ANGLE FROM HORIZ.		BEARING			
														90°		N/A			
BEGIN		COMPLETED		DRILLER			DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)		TOTAL DEPTH				
7/22/86		7/22/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33		6"		10.0'		0.0'		10.0'				
CORE RECOVERY (FT./%)		CORE BONES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK							
N/A		N/A		N/A		N/A		96.2'		7.5' / 88.7'		N/A							
SAMPLE NUMBER BEHIND / ALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:											
N/A				N/A				D. McGRANE											
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE BLOW BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.							
				LOSS IN FT. IN 15 MIN.	PRESSURE IN PSI	TIME IN MINUTES													
AUGER, 6" THROUGHOUT.							96.2	0											
							94.7	5		0.0-1.5': SANDY SILT (OL); MODERATE BROWN (5YR3/4); FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. 7/22/86 EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.								
							86.2	10		1.5-10.0': SILTY SAND (SM-SC); COLOR STAFFED; FINE TO COARSE GRAINED; SOFT; POORLY CONSOLIDATED FROM 1.5-4.0 FT BUT DENSE FROM 4.0-10.0 FT; FEW ORGANICS TO 4.0 FT; SLIGHTLY MOIST TO SATURATED AT 7.5 FT. 1.4-4.0': DARK YELLOWISH BROWN (8YR4/2); POORLY CONSOLIDATED; FEW ORGANICS. 4.0-7.5': MODERATE BROWN (5YR3/4) WITH GRAYISH BLACK (M2) 0.5-1.0' CLAYEY LENSES; CLAY BINDER; DENSE IN PLACE. 7.5-8.5': GRAY (M3). 8.5-10.0': DARK REDDISH BROWN (8R3/4); CLAY BINDER; DENSE IN PLACE.									
										BOTTOM OF HOLE AT 10.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.									
								15											
								20											
								25											
								30											
								35											

SS-SPLIT SPOON; ST-SHELBY TUBE; D-DIAPHRAGM; P-PISTON; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-224R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.	SHEET NO.	HOLE NO.	
MAYWOOD INTERIM STORAGE SITE - NJVIS										FUSRAP		14501-130	1 OF 1	NISS-225R	
COORDINATES										NIT00,E1000		ANGLE FROM HORIZ.	BEARING		
DATE	COMPLETED	DRILLER			DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH					
7/22/06	7/22/06	MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33		6"	10.0'	0.0'	10.0'					
CORE RECOVERY (FT./30)		CORE BOXES	SAMPLES	REL. TOP OF CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK							
N/A		N/A	N/A	N/A	96.0'	7.5'/88.5'		N/A							
SAMPLE NUMBER (HOLE/FULL)			CASING LEFT IN HOLE (DL/LDN/ST)			LOGGED BY:									
N/A			N/A			D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE ADVANCE LENGTH CORE RUN	SAMPLE SECURITY CORE RECOVERY	SAMPLE LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.		
					LOSS FT.	IN P.S.I.	TIME IN MINUTES								
AUZER 6" THROUGHOUT.							96.0	0				0.0-4.5': SANDY SILT (ML-NC); DARK YELLOWISH BROWN (GYR4/2); WITH A GRAYISH BROWN (GYR3/2) CLAYEY ZONE FROM 3.5-4.0 FT; FINE GRAINED WITH AN OCCASIONAL COBBLE; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS IN UPPERMOST 0.5 FT (GRASS ROOTS); SLIGHTLY MOIST. 4.5-10.0': SILTY SAND (SM-SC); COLOR STRATIFIED; FINE TO MEDIUM GRAINED; POORLY SORTED; MOIST TO SATURATED FROM 7.5-10.0 FT. 4.5-7.5': DARK YELLOWISH ORANGE (OYR6/6); POORLY CONSOLIDATED. 7.5-10.0': DARK YELLOWISH BROWN (OYR4/2); CLAY BINDER; DENSE IN PLACE. BOTTOM OF HOLE AT 10.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION 7/22/06		
							91.5	5							
								86.0	10						
								15							
								20							
								25							
								30							
								35							

36-SPLT SPOILS; ST-SHELBY TUBE; D-DEBRIS; P-PITCHER; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-225R

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.	
MAYWOOD INTERIM STORAGE SITE - NJVIS				FLSRAP			14501-130		1 OF 1		MISS-226R	
SITES				COORDINATES				ANGLE FROM HORIZ.		BEARINGS		
				N1700,E1100				90°		N/A		
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	RICK (FT.)	TOTAL DEPTH	
7/22/86		7/22/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	5.0'	0.0'	5.0'	
CORE RECOVERY(FT./D)			CORE BOXES		SAMPLES	EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF RICK
N/A			N/A		N/A	N/A		95.0'		NONE OBSERVED		N/A
SAMPLE NUMBER HEIGHT/TALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:				
N/A				N/A				D. McGRANE				
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH/ CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE BLOW BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOGS IN FT. G.P.A.	W. PRESSURE IN P.S.I.	TIME IN MINUTES						
AUGER, 6" THROUGHOUT.						95.0	0					
						94.5				0.0-0.5': SANDY SILT ONLY; MODERATE BROWN (GYR3/4); FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.	
						90.0	5			0.5-5.0': SILTY SAND (SILTY COLOR); STRATIFIED; FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; MOIST.		EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.
										0.5-1.5': DARK REDDISH BROWN (GR3/4); FINE GRAINED OCCASIONAL PEBBLES AND SMALL COBBLES.		
										1.5-3.5': DARK YELLOWISH BROWN (GYR4/2); WITH DARK REDDISH BROWN SANDSTONE PEBBLES.		
										3.5-4.0': DARK REDDISH BROWN (GR3/4); FINE TO COARSE GRAINED.	*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.	
										BOTTOM OF HOLE AT 5.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		
							10					
							15					
							20					
							25					
							30					
							35					

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

30-SPLIT SPOON; ST-DRIBBY TUBE; D-DEBRIS; P-PITCHER; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. MISS-226R



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-138
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-227R

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 COORDINATES: N1700, E1400
 ANGLE FROM HORIZ.: 90°
 BEARING: N/A

START: 7/22/06
 COMPLETED: 7/22/06
 DRILLER: MORETRENCH ENVIRONMENTAL SERVICES
 DRILL MAKE AND MODEL: MOBILE B-33
 HOLE SIZE: 6"
 OVERLAP (FT.): 5.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 5.0'

CORE RECOVERY (FT./TD): N/A
 CORE BOXES: N/A
 SAMPLES: N/A
 EL. TOP OF CASING: N/A
 GROUND EL.: 95.6'
 DEPTH/EL. GROUND WATER: 4.5'/91.1'
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE NUMBER HEIGHT/FALL: N/A
 CASING LEFT IN HOLE: DIA./LENGTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLER RECOVERY CORE RECOVERY	SAMPLER LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS	IN	MINUTES						
AUGER, 6", THROUGHOUT.								95.6	0			0.0-0.5': SILTY SAND (SM-SC) MODERATE BROWN (GYR3/4) FINE GRAINED, POORLY SORTED, POORLY CONSOLIDATED; NUMEROUS ORGANICS (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. 7/22/06 EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
							95.1				0.5-5.0': SILTY SAND (SM-SC) COLOR STRATIFIED FINE TO COARSE GRAINED; SOFT; MOSTLY DENSE IN PLACE BUT LOOSE (POORLY CONSOLIDATED) FROM 4.0-5.0 FT; MOST TO SATURATED (4.5-5.0 FT).		
								90.6	5			0.5-3.5': DARK REDDISH BROWN (GR3/4) WITH 1-2" DARK YELLOWISH BROWN (GYR4/2) CLAYEY LENSES AND PIECES OF RED BRICK (FILL). 4.0-5.0': DARK YELLOWISH BROWN (GYR4/2); POORLY SORTED; POORLY CONSOLIDATED. BOTTOM OF HOLE AT 5.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	
									10				
									15				
									20				
									25				
									30				
									35				

SS-SPLT SPDRS ST-SHELTY TUBS; D-CORING P-PISTON Q-OTHER
 SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 HOLE NO.: MISS-227R



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-130
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-220R

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 COORDINATES: N1700, E1200
 ANGLE FROM N090: 90°
 BEARING: N/A

DRILLER: MORE TRENCH ENVIRONMENTAL SERVICES
 DRILL MAKE AND MODEL: MOBILE B-33
 HOLE SIZE: 6"
 OVERLAP (FT.): 5.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 5.0'

CORE RECOVERY (%): N/A
 CORE SERIES: N/A
 SAMPLES: N/A
 REL. TOP OF CORE: N/A
 GROUND EL.: 95.4'
 DEPTH/EL. GROUND WATER: NONE OBSERVED
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE NUMBER HEIGHT/FALL: N/A
 CORE LEFT IN HOLE: DIA./LENGTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLE INTERVAL CORE NUMBER	SAMPLE IN CORE	POSITION CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG IN FT. IN P.S.F.	PRESSURE P.S.F.	TIME IN MINUTES						
AUGER, 6", THROUGHOUT.							95.4	0					
							95.1				0.0-0.3: ASPHALT. 0.3-5.0: SILTY SAND (SM-SC) COLOR STRATIFIED SOIL PROFILE; FINE TO COARSE GRAINED; SOFT; MOIST. 0.3-1.5: DARK REDDISH BROWN (OR3/4); OCCASIONAL GRAVEL; POORLY CONSOLIDATED; POORLY SORTED. 1.5-5.0: DARK YELLOWISH BROWN (OYR4/2) WITH F-Z PALE GREEN (SG7/2) CLAY-RICH LENSES; DENSE IN PLACE.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.	
						90.4	5				BOTTOM OF HOLE AT 5.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS REFILLED WITH ASPHALT.		EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.
								10					
								15					
								20					
								25					
								30					
								35					

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM


* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SPLIT SPINDLE ST-BLBY TUBE; P-RECORDING P-PCORER P-OTHER
 MAYWOOD INTERIM STORAGE SITE - NJVIS
 HOLE NO.: MISS-220R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-138	1 OF 1	MISS-229R				
COORDINATES				N1700, E1300		ANGLE FROM MERID.		BEARING				
N1700, E1300				90°		N/A		N/A				
BEGIN	COMPLETED	DRILLER	DRILL MAKE AND MODEL		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH				
7/23/86	7/23/86	MORETRENCH ENVIRONMENTAL SERVICES	MOBILE B-33		6"	10.0'	0.0'	10.0'				
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	REL. TOP OF CASING	GROUND EL.	DEPTH/VEL. GROUND WATER		DEPTH/VEL. TOP OF ROCK				
N/A		N/A	N/A	N/A	95.6'	8.0'/87.6'		N/A				
SAMPLE NUMBER WEIGHT/FALL		CASING LEFT IN HOLE; DIA./LENGTH			LOGGED BY:							
N/A		N/A			D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOGS IN P.S.P.A.	PRESSURE IN P.S.I.	TIME IN P. MINUTES						
AUGER, 6" THROUGHOUT.							95.6	0	[Symbol]		0.0-0.5': ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. 7/23/86
							90.6	5	[Symbol]	0.5-5.0': SILTY SAND (OL-SM) COLOR STRATIFIED FINE TO COARSE GRAINED; POORLY SORTED; POORLY CONSOLIDATED; MOIST. 1.0-5.0': DARK YELLOWISH BROWN GDR4/2.		
							89.6	8.0	[Symbol]	5.0-8.0': SANDY SILT (ML-CL) PALE GREEN (SG7/2) SOFT; DENSE IN PLACE; MOIST. 8.0-10.0': SILTY SAND (SM) DARK YELLOWISH ORANGE (OYR6/6) FINE TO MEDIUM GRAINED SOFT; DENSE IN PLACE; MOIST TO SATURATED AT 8.0 FT.		
							85.6	10	[Symbol]		BOTTOM OF HOLE AT 10.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CLTTINGS.
								15	[Symbol]			ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM
								20	[Symbol]			
								25	[Symbol]			
								30	[Symbol]			
								35	[Symbol]			



GEOLOGIC DRILL LOG										PROJECT		JOB NO.	SHEET NO.	HOLE NO.
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS										FUSRAP		14501-138	1 OF 1	MISS-230R
COORDINATES										N1600, E1400		ANGLE FROM MERID.	BEARING	
BEGIN	COMPLETED	DRILLER			DRILL NAME AND MODEL			HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH			
7/23/86	7/23/86	MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33			6"	10.0'	0.0'	10.0'			
CORE RECOVERY (FT./30)		CORE BOXES	SAMPLES	EL. TOP OF CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK						
N/A		N/A	N/A	N/A	95.9'	6.0'/89.9'		N/A						
SAMPLE NUMBER WEIGHT/FALL		CASING LEFT IN HOLE/DIAL LENGTH			LOGGED BY:									
N/A		N/A			D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE NO.	SAMPLE RECOVERY CORE RECOVERY	SAMPLE BLEND BY	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
					LOGS IN P.C.P.A.	PRESSURE IN P.S.I.	TIME IN MINUTES							
AUGER, 6", THROUGHOUT.								95.9	0					
								94.9	5			0.0-1.0': SANDY SILT (CL); MODERATE BROWN (5YR3/4); MOSTLY FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS ORGANICS (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION  7/23/86	
								85.9	10			1.0-10.0': SILTY SAND (SM); DARK YELLOWISH ORANGE (10YR6/6); FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); MOIST TO SATURATED AT 6.0 FT.		
									15			BOTTOM OF HOLE AT 10.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.	
									20					
									25					
									30					
									35					

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SPLIT SPOILS ST-BELOW TAIL; 0-DEPOSIT P-PITCHED; 0-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. MISS-230R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				ANGLE FROM HORIZ.		BEARING	
										N1600,E1300				90°		N/A	
BEGIN		COMPLETED		DRILLER			DRILL MAKE AND MODEL			HOLE SIZE	OVERLAP (FT.)		ROCK (FT.)	TOTAL DEPTH			
7/23/86		7/23/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33			6"	5.0'		0.0'	5.0'			
CORE RECOVERY (FT./%)		CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER			DEPTH/EL. TOP OF ROCK				
N/A		N/A		N/A		N/A		96.5'		5.0'/91.5'			N/A				
SAMPLE NUMBER HEIGHT/FALL				CASING LEFT IN HOLE; DIA./LENGTH				LOGGED BY:									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER APPROX. LENGTH CORRECTION	SAMPLER RECOVERY CORRECTION	SAMPLER LOSS %	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
				LOSS IN FT. @ 1/4"	LOSS IN FT. @ 1/2"	LOSS IN FT. @ 1"											
AUGER, 6" THROUGHOUT.							96.5	0									
							95.5				0.0-1.0': SANDY SILT (ML); MODERATE BROWN (5YR3/4); FINE GRAINED; POORLY CONSOLIDATED (LOOSE); NUMEROUS ORGANICS (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.					
							91.5	5			1.0-5.0': SILTY SAND (SM); DARK YELLOWISH BROWN (6YR4/2); FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); MOIST TO SATURATED AT 5.0 FT.						
											BOTTOM OF HOLE AT 5.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.					
								10									
								15									
								20									
								25									
								30									
								35									

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SPLIT SPOON; ST-SHELBY TUBE; D-DEBRIS; P-PITCHER; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-231R



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-138
 SHEET NO.: 1 OF 1
 HOLE NO.: NISS-232R

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 COORDINATES: N1580, E1200
 ANGLE FROM HORIZ.: 90°
 BEARING: N/A

DATE: 7/23/86
 COMPLETED: 7/23/86
 DRILLER: MORETRENCH ENVIRONMENTAL SERVICES
 DRILL MAKE AND MODEL: MOBILE B-33
 HOLE SIZE: 6"
 OVERLAP (FT.): 5.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 5.0'

CORE RECOVERY (FT./TD): N/A
 CORE DIAMETER: N/A
 SAMPLES: N/A
 EL. TOP OF CASING: N/A
 GROUND EL.: 97.0'
 DEPTH/EL. GROUND WATER: NONE OBSERVED
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE NUMBER: N/A
 CASING LEFT IN HOLE: DIA./LENGTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLE ADVANCE LENGTH (CORRECTION)	SAMPLE RECOVERY - CORE RECOVERY	SAMPLE BLEND	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETENTION, CHARACTER OF DRILLING, ETC.
					LOGS	IN	OUT						
ALGER, 6" THROUGHOUT.								97.0	0				
								95.5				0.0-1.5': SANDY SILT (CL); MODERATE BROWN (5YR3/4) SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.
								92.0	5			1.5-3.0': SILTY SAND (SM); COLOR STRATIFIED; FINE TO COARSE GRAINED; POORLY CONSOLIDATED (LOOSE); MOIST. 1.5-3.0': DARK REDDISH BROWN (6YR3/4); FINE TO MEDIUM GRAINED. 3.0-5.0': DARK YELLOWISH BROWN (6YR4/2).	
													BOTTOM OF HOLE AT 5.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.

SS-SPLIT SPOILS; ST-SHED BY TUBE; P-PITCHED; O-OTHER
 SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 HOLE NO.: NISS-232R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
MAYWOOD INTERIM STORAGE SITE - NJVIS										FUSRAP		14501-130		1 OF 1		NISS-233R			
COORDINATES										N1600, E1200		ANGLE FROM HORIZ.		90°		DIP/SLUR		N/A	
DATE		COMPLETED		DRILLER			DRILL MAKE AND MODEL			HOLE SIZE		OVERLAP (FT.)		RICK (FT.)		TOTAL DEPTH			
7/23/86		7/23/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE 8-33			6"		5.0'		0.0'		5.0'			
CORE RECOVERY (FT./%)				CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/VEL. GROUND WATER			DEPTH/VEL. TOP OF ROCK				
N/A				N/A		N/A		N/A		96.0		NONE OBSERVED			N/A				
SAMPLE BARREL WEIGHT/FULL				CASING LEFT IN HOLE DIA./LENGTH				LOGGED BY:											
N/A				N/A				D. MCGRANE											
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH (CORE BAR)	SAMPLE RECOVERY CORE RECOVERY	SAMPLE BLEND	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	CORING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CONTACT OF DRILLING, ETC.						
					LONG IN	P.S.P.A.	TIME IN MINUTES												
AUGER, 6" THROUGHOUT.							96.0	0											
							94.5				0.0-1.5': SANDY SILT (CL); MODERATE BROWN (5YR/7.5) FINE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.							
							91.0	5			1.5-5.0': SILTY SAND (SM); COLOR STRATIFIED FINE TO COARSE GRAINED; POORLY CONSOLIDATED (LOOSE); MOIST. 1.5-3.0': DARK REDDISH BROWN (6.0R3/4); FINE TO MEDIUM GRAINED. 3.0-5.0': DARK YELLOWISH BROWN (6YR4/2). BOTTOM OF HOLE AT 5.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. -DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.							
								10											
								15											
								20											
								25											
								30											
								35											
30-SPLIT SPINDLE ST-BUILDUP TUBE; 10-CENTIMETER P-PITCHED 0-DYER										SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO. NISS-233R					



GEOLOGIC DRILL LOG

PROJECT: FUSRAP JOB NO.: 14501-130 SHEET NO.: 1 OF 1 HOLE NO.: NISS-234R

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS COORDINATES: N1600,E1110 ANGLE FROM HORIZ.: 90° BEARING: N/A

START: 7/23/86 COMPLETED: 7/23/86 DRILLER: MORETRENCH ENVIRONMENTAL SERVICES DRILL NAME AND MODEL: MOBILE B-33 HOLE SIZE: 6" OVERLAP (FT.): 5.0' ROCK (FT.): 0.0' TOTAL DEPTH: 5.0'

CORE RECOVERY (%): N/A CORE BOXES: N/A SAMPLES: N/A EL. TOP OF CASING: N/A GROUND EL.: 96.0' DEPTH/EL. GROUND WATER: NONE OBSERVED DEPTH/EL. TOP OF ROCK: N/A

SAMPLE NUMBER WEIGHT/FALL: N/A CASING LEFT IN HOLE/DIA./LENGTH: N/A LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLER RECOVERY CORE RECOVERY	SAMPLER BLEND	PERCENT CORE RECOVERY	WATER PRESSURE TESTS		ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG IN P.S.F.	TIME IN MINUTES						
AUGER, 6" THROUGHOUT.							96.0	0				
							95.7				0.0-0.3': ASPHALT. 0.3-5.0': SILTY SAND (SHE COLOR STRATIFIED FINE TO COARSE GRAINED; POORLY CONSOLIDATED (LOOSE); MOIST. 0.3-3.0': DARK REDDISH BROWN GOR3/4; FINE TO MEDIUM GRAINED. 3.0-5.0': DARK YELLOWISH BROWN GOR4/2.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.
							91.0	5			BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH 0.3 FT OF ASPHALT.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
												ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

LOG-SPILL SPOILS ST-ORBY THIS; DECONTAMINATION P-PITCHER 0-OTHER SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS HOLE NO.: NISS-234R



GEOLOGIC DRILL LOG

PROJECT

FLSRAP

JOB NO.

14501-130

SHEET NO.

1 OF 1

HOLE NO.

NISS-235R

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

COORDINATES

N1600, E1000

ANGLE FROM HORIZ.

90°

BEARDS

N/A

START

7/23/06

COMPLETED

7/23/06

DRILLER

MORETRENCH ENVIRONMENTAL SERVICES

DRILL MAKE AND MODEL

MOBILE B-33

HOLE SIZE

6"

OVERBURDEN (FT.)

10.0'

ROCK (FT.)

0.0'

TOTAL DEPTH

10.0'

CORE RECOVERY (FT./TD)

N/A

CORE BOXES

N/A

SAMPLES

N/A

REL. TOP OF CASING

N/A

GROUND EL.

96.1'

DEPTH/REL. GROUND WATER

0.0'/00.1'

DEPTH/REL. TOP OF ROCK

N/A

SAMPLE NUMBER WEIGHT/TALL

N/A

CASING LEFT IN HOLE; DIA./LENGTH

N/A

LOGGED BY:

D. McGRATH

SAMPLE TYPE AND DIAMETER	SAMPLE NUMBER - LOGGING CORE FOOT	SAMPLE DEPTH - CORE RECOVERY	SAMPLE DIAMETER	PERCENT CORE RECOVERY	WATER PRESSURE TESTS				ELEVATION	DEPTH	GAMMA LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG IN FT.	P.S.F.	IN P.S.F.	TIME IN MINUTES						
AUGER, 6", THROUGHOUT.								96.1	0					
								94.6	5			0.0-1.5: SANDY SILT CL; DARK YELLOWISH BROWN 00YR4/2; FINE GRAINED; POORLY CONSOLIDATED (LOOSE); NUMEROUS ROOTS AND ORGANICS; DRY. 1.5-10.0: SILTY SAND (SILTY COLOR) STRATIFIED FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); MOIST TO SATURATED AT 8.0 FT. 1.5-5.0: DARK YELLOWISH ORANGE 00YR6/6; FINE TO MEDIUM GRAINED. 5.0-10.0: DARK YELLOWISH BROWN 00YR4/2; FINE TO COARSE GRAINED WITH A FEW ROUNDED PEBBLES.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. 7/23/06	
								86.1	10				BOTTOM OF HOLE AT 10.0 FT. DRILL SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
									15					
									20					
									25					
									30					
									35					

35-0114 SPOILS ST-BELBY TAIL; 3-020000 P-PROCESOR OTHER

SITE

MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO.

NISS-235R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-130	1 OF 1	MISS-236R				
SITE COORDINATES				N1500, E1000		ANGLE FROM HORIZ.		BEARINGS				
						90°		N/A				
START	COMPLETED	DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)				
7/23/86	7/23/86	MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	5.0'	0.0'				
CORE RECOVERY (FT./%)		CORE DIAMETER	SAMPLES	EL. TOP OF CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
N/A		N/A	N/A	N/A	96.6'	NONE OBSERVED		N/A				
SAMPLE NUMBER BEING/FALL		CASING LEFT IN HOLE (IN./LENGTH)			LOGGED BY:							
N/A		N/A			D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLER TYPE AND LENGTH (CORE RUN)	SAMPLER IDENTITY (CORE NUMBER)	SAMPLE DEPTH TO PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPE LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOGS IN P. (P.A.)	IN PRESSURE P. (P.)	TIME IN MINUTES						
ALGER, 6", THROUGHOUT.							96.6	0				SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
							95.6			0.0-1.0': SANDY SILT; MODERATE BROWN (5YR3/4) FINE GRAINED, POORLY SORTED, POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; DRY.		
							91.6	5		1.0-5.0': SILTY SAND (SM) COLOR STRATIFIED SOIL PROFILE; FINE TO COARSE GRAINED, SOFT, POORLY SORTED, POORLY CONSOLIDATED (LOOSE); SLIGHTLY MOIST. 1.0-3.5': DARK YELLOWISH ORANGE (10YR6/5) FINE TO MEDIUM GRAINED. 3.5-5.0': DARK YELLOWISH BROWN (10YR4/2); FEW ORGANICS. BOTTOM OF HOLE AT 5.0 FT. ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		
								10				
								15				
								20				
								25				
								30				
								35				

30-SPLIT SPIN; ST-DRILL; TUB; P-CORING; P-PITCHED; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. MISS-236R



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.	
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP			14501-130		1 OF 1		NISS-237R	
COORDINATES				N1400,E1000				ANGLE FROM HORIZ.		DIPS		
N/A				N/A				90°		N/A		
BEGIN		COMPLETED		DRILLER			DRILL MAKE AND MODEL		HOLE SIZE		OVERLASH (FT.)	
7/23/06		7/23/06		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33		6"		5.0'	
CORE RECOVERY (FT./%)			CORE DIAMETER		SAMPLES		BL. TOP OF CASING		GROUND W.		DEPTH/BL. TOP OF ROCK	
N/A			N/A		N/A		N/A		97.0		NONE OBSERVED	
SAMPLE BANDS REMOVED/FALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:				
N/A				N/A				D. McGRANE				
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH (COR. TO)	SAMPLE RECOVERY COR. (COR. TO)	SAMPLE LOSS BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRANIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOG IN FT. S.P.A.L.	W. PRESSURE P.S.I.	TIME IN MIN. PLUGGED						
ALGER, 6"; THROUGHOUT.							97.0	0				
							96.0				0.0-1.0'; SANDY SILT (S); MODERATE BROWN (5YR 5/4) FINE GRAINED CLAY BINDER; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND OTHER ORGANICS; DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.
						92.0	5			1.0-5.0'; SILTY SAND (SM); COLOR STRATIFIED SOIL PROFILE; FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); SLIGHTLY MOIST. 1.0-3.0'; DARK YELLOWISH ORANGE (10YR 6/6) FEW ROUNDED SMALL PEBBLES. 3.0-5.0'; DARK YELLOWISH BROWN (10YR 4/2).		
											BOTTOM OF HOLE AT 5.0 FT. ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
												ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

36-SPLT. SPOON; ST-SHIELD TUBE;
D-CORRECTOR; P-PROBE; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-237R



GEOLOGIC DRILL LOG

PROJECT: **FUSRAP** JOB NO.: **14501-130** SHEET NO.: **1 OF 1** HOLE NO.: **MISS-230R**

SITE: **MAYWOOD INTERIM STORAGE SITE - NJVIS** COORDINATES: **N1300, E1000** ANGLE FROM HORIZ.: **90°** BEARINGS: **N/A**

DRILLER: **MORETRENCH ENVIRONMENTAL SERVICES** DRILL MAKE AND MODEL: **MOBILE B-33** HOLE SIZE: **6"** OVERLAP (FT.): **20.0'** ROCK (FT.): **0.0'** TOTAL DEPTH: **20.0'**

CORE RECOVERY (FT./20): **N/A** CORE DIAMETER: **N/A** SAMPLES: **N/A** EL. TOP OF CASING: **N/A** ORIGINAL EL.: **97.0'** DEPTH/EL. GROUND WATER: **NONE OBSERVED** DEPTH/EL. TOP OF ROCK: **N/A**

SAMPLE NUMBER WEIGHT/FALL: **N/A** CASING LEFT IN HOLE (IN./LENGTH): **N/A** LOGGED BY: **D. McGRANE**

SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH (CORE LOSS)	SAMPLER RECOVERY (CORE RECOVERY)	SAMPLER LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAB LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS	IN	OUT						
ALIGER, 6" THROUGHOUT.								97.0	0				
								96.0				0.0-1.0': SANDY SILT (LM-MODERATE BROWN); SYR 3/4; FINE GRAINED; CLAY BINDER; SOFT; POORLY CONSOLIDATED; LOOSE; NUMEROUS GRASS ROOTS AND OTHER ORGANICS; DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. 7/23/06
									5			1.0-20.0': SILTY SAND (SM-SC); COLOR STRATIFIED SOIL PROFILE; SEQUENCE GRADES FROM FINE TO COARSE GRAINED (0.0-14.0 FT) TO A CLEAN FINE GRAINED SAND (14.0-20.0 FT); SOFT; POORLY CONSOLIDATED (LOOSE); SLIGHTLY MOIST TO SATURATED AT 13.0 FT.	
									10			1.0-6.0': DARK YELLOWISH ORANGE (OYR6/16); WITH OCCASIONAL P. DARK REDDISH BROWN CLAYEY ZONES; FINE TO MEDIUM GRAINED; OCCASIONAL ROUNDED PEBBLES.	
								20			6.0-14.0': DARK YELLOWISH BROWN (OYR4/2); FINE TO COARSE GRAINED. 14.0-20.0': DARK YELLOWISH BROWN (OYR4/2); MOSTLY FINE GRAINED; CLEAN (SM).		
								77.0	20			BOTTOM OF HOLE AT 20.0 FT. ALIGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
									25				
									30				
									35				

30-SPLIT SPEED ST-EMLEY TUBE; 3-DRUMS; 4-PISTON; 0-OTHER: **MAYWOOD INTERIM STORAGE SITE - NJVIS** HOLE NO.: **MISS-230R**



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-138	1 OF 1	NISS-239R				
SITE			COORDINATES			ANGLE FROM HORIZ.		BEARINGS				
MAYWOOD INTERIM STORAGE SITE - NJVIS			N1500, E1100			90°		N/A				
BEGAN	COMPLETED	DRILLER	MORE TRENCH ENVIRONMENTAL SERVICES	DRILL MAKE AND MODEL	MOBILE B-33	HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH			
7/25/86	7/25/86					6"	5.0'	0.0'	5.0'			
CORE RECOVERY (FT./TD)		CORE BOXES	SAMPLES	REL. TOP OF CORE	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
N/A		N/A	N/A	N/A	96.8'	NONE OBSERVED		N/A				
SAMPLE NUMBER BEGIN/END		CARDS LEFT IN HOLE; DIA./LENGTH		LOGGED BY								
N/A		N/A		D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLER APPROX. LENGTH (CORE RUN)	SAMPLER RECOVERY - CORE RECOVERY	SAMPLER LOSS BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOGS IN P.S.J.	PRESSURE IN P.S.J.	TIME IN MINUTES						
ALGER, 6" THROUGHOUT.							96.8	0				
							96.5			0.0-0.3: ASPHALT 0.3-3.0: SANDY SILT (ML-CL) COLOR STRATIFIED SOIL HORIZON; FINE GRAINED; SOFT; POORLY SORTED; CLAY BINDER; DENSE IN PLACE; MOIST. 0.3-1.5: DARK YELLOWISH BROWN (DYR4/2).	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.	
						93.8			1.5-3.0: MODERATE BROWN (SYR3/4). 3.0-5.0: SILTY SAND (SM) COLOR STRATIFIED FINE TO MEDIUM GRAINED; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); MOIST. 3.0-3.5: DARK YELLOWISH ORANGE (DYR6/6). 3.5-5.0: DARK YELLOWISH BROWN (DYR4/2). BOTTOM OF HOLE AT 5.0 FT. ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.		
						91.8	5					
								10				
								15				
								20				
								25				
								30				
								35				



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				HOLE FROM HORIZ.		BEARING			
										N1200, E1000				90°		N/A			
DATE		COMPLETED		DRILLER			MORE TRENCH			DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)		TOTAL DEPTH	
7/25/86		7/25/86		ENVIRONMENTAL SERVICES			MOBILE B-33			6"		5.0'		0.0'		5.0'			
CORE RECOVERY (FT./20)			CORE BITES		SAMPLES		BL. TOP OF CASING		GROUND EL.		DEPTH/VEL. GROUND WATER			DEPTH/VEL. TOP OF ROCK					
N/A			N/A		N/A		N/A		97.6'		NONE OBSERVED			N/A					
SAMPLE NUMBER				HEIGHT/FALL				CASING LEFT IN HOLE/DIA./LENGTH				LOGGED BY:							
N/A				N/A				N/A				D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLED APPROX. LENGTH CORRECTION	SAMPLE DEPTH/VELOCITY CORRECTION	SAMPLE ELONG. BY PERCENT CORRECTION	WATER PRESSURE TESTS			ELEVATION	DEPTH	CORRECTION LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CONTACT OF DRILLING, ETC.							
				LOSS IN FT. G.P.A.L.	PRESSURE IN P.S.I.	TIME IN MINUTES													
AUGER, 6", THROUGHOUT.							97.6	0											
							96.6				0.0-1.0': SANDY SILT (CL); DARK YELLOWISH BROWN (OYR4/2); FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.							
							92.6	5			1.0-3.0': SILTY SAND (SM); COLOR STRATIFIED SOIL HORIZONS; FINE TO COARSE GRAINED; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); MOIST. 1.0-3.0': DARK YELLOWISH ORANGE (OYR6/6); FINE TO MEDIUM GRAINED. 3.0-5.0': DARK YELLOWISH BROWN (OYR4/2).								
											BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.								
								10											
								15											
								20											
								25											
								30											
								35											

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

10-UP/LY SP-000, ST-000/LY TAB, D-00000, P-00000, O-0000

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-240R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
				FLSRAP		14501-138	1 OF 1	MISS-241R					
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS			COORDINATES				ANGLE FROM HORIZ.	BEARING					
			N1100, E1000				90°	N/A					
BEIGN	COMPLETED	DRIILLER	MORETRENCH	DRIILL MAKE AND MODEL	HOLE SIZE	OVERCULMIN (FT.)	ROCK (FT.)	TOTAL DEPTH					
7/25/86	7/25/86	ENVIRONMENTAL SERVICES	ENVIRONMENTAL SERVICES	MOBILE B-33	6"	5.0'	0.0'	5.0'					
CORE RECOVERY (VT./%)		CORE BOXES	SAMPLES	EL. TOP OF CORES	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK					
N/A		N/A	N/A	N/A	98.2'	NONE OBSERVED		N/A					
SAMPLE NUMBER WEIGHT/FULL			CORES LEFT IN HOLE: DIA./LENGTH		LOGGED BY:								
N/A			N/A		D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE FEET	SAMPLE RECOVERY CORE RECOVERY	SAMPLE WGT. PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
				LOG	TIME	MINUTES							
AUGER, 6" THROUGHOUT.							98.2	0					
							97.2				0.0-1.0': SANDY SILT (CL); DARK YELLOWISH BROWN (OYR4/2); FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.	
							93.2	5			1.0-5.0': SILTY SAND (SM); COLOR STRATIFIED SOIL HORIZONS; FINE TO COARSE GRAINED; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); MOIST. 1.0-3.0': DARK YELLOWISH ORANGE (OYR6/6); FINE TO MEDIUM GRAINED. 3.0-5.0': DARK YELLOWISH BROWN (OYR4/2); CONTAINS ROUNDED PEBBLES OF VARIOUS LITHOLOGIES. BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. -DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
												ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.	
SE-SPLIT SPOIL; ST-SHED BY TAG; P-POSSIBLE; P-PITCHER; O-OTHER				SITE					MAYWOOD INTERIM STORAGE SITE - NJVIS		HOLE NO.		MISS-241R



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.				
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP			14501-130		1 OF 1		MISS-242R				
COORDINATES				N992,E1000				ANGLE FROM HORIZ.		BEARINGS					
N/A				N/A				90°		N/A					
DATE		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH	
7/25/86		7/25/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		2.0'		1.0'		3.0'	
CORE RECOVERY (FT./3)				CORE BOXES		SAMPLES		BL. TOP OF CASING		GROUND EL.		DEPTH/BL. GROUND WATER		DEPTH/BL. TOP OF ROCK	
N/A				N/A		N/A		N/A		99.5'		NONE OBSERVED		2.0' / 97.5'	
SAMPLE BARREL HEIGHT/FULL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:							
N/A				N/A				D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH (CORRECTION)	SAMPLE RECOVERY (CORRECTION)	SAMPLE BLEND	PERCENT CORE RECOVERY	WATER PRESSURE TESTS				ELEVATION	DEPTH	DRAWING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
					LOGS	P. S.P.A.	IN PRESSURE	P. S.I.							TIME
ALGER 6" THROUGHOUT.									99.5	0			0.0-1.0: SANDY SILT (CL); DARK YELLOWISH BROWN (OYR)/2; FINE GRAINED; SOFT-POORLY SORTED; POORLY CONSOLIDATED (LOOSE); DRY.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.	
								96.5	3.0			1.0-2.0: SILTY SAND (SM); DARK YELLOWISH ORANGE (OYR)/6; FINE TO MEDIUM GRAINED; POORLY SORTED; POORLY CONSOLIDATED; SOFT; SLIGHTLY MOIST. 2.0-3.0: DECOMPOSED SANDSTONE; DARK REDDISH BROWN (OYR)/4; FINE TO MEDIUM GRAINED; SOME SILT; TOTALLY DECOMPOSED TO HIGHLY WEATHERED; SOFT WITH NUMEROUS MODERATELY HARD PIECES OF CONSOLIDATED SANDSTONE; MOIST. BOTTOM OF HOLE AT 3.0 FT. ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. -DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. ALGER REFUSAL AT 3.0 FT.		
										5					
										10					
										15					
										20					
										25					
										30					
										35					
36-SP/LT SPOOLS ST-BELLY TUBES; 3-SECTION 4-PIECE 6-OTHER				SITE				MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO. MISS-242R			



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.			
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-138	1 OF 1	NISS-243R			
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES			ANGLE FROM HORIZ.	BEARDS			
				N800, E1300			90°	N/A			
BEARER	COMPLETED	DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)			
7/25/86	7/25/86	MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	2.0'	2.0'			
CORE RECOVERY (FT./TD)		CORE RONES	SAMPLES	TEL. TOP OF CASING	GROUND EL.	DEPTH/VEL. GROUND WATER		DEPTH/VEL. TOP OF ROCK			
N/A		N/A	N/A	N/A	98.1'	NONE OBSERVED		2.0' / 96.2'			
SAMPLE NUMBER IDENT./ALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:					
N/A			N/A			D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLE INTERVAL - LENGTH OF CORE RUN	SAMPLE INTERVAL - CORE RECOVERY	SAMPLE SLUGS BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS		ELEVATION	DEPTH	GRAPIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
ALGER, 6" THROUGHOUT.				LOGS IN P.S./A.	PRESSURE IN P.S.I.	TIME IN MINUTES	98.1	0			
							97.1				
							96.1				
							94.1	4.0		0.0-1.0'; SANDY SILT (S); DARK YELLOWISH BROWN (OYR)/2; FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY ENEERLINE ANALYTICAL CORPORATION.
								5		1.0-2.0'; SILTY SAND (SM); DARK YELLOWISH ORANGE (OYR)/6; WITH OCCASIONAL 0.5-2.0" PIECES OF DARK REDDISH BROWN (OR)/3/4 SANDSTONE; MOSTLY FINE TO MEDIUM GRAINED; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); SOFT; MOIST.	ENEERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.
								10		2.0-4.0'; DECOMPOSED SANDSTONE; DARK REDDISH BROWN (OR)/7; OF FINE TO MEDIUM GRAINED; SOME SILT; SOFT TO MODERATELY HARD (REFUSAL AT 4.0 FT); TOTALLY DECOMPOSED TO HIGHLY WEATHERED; POORLY CONSOLIDATED WITH NUMEROUS	
								15		PIECES OF WELL CONSOLIDATED SANDSTONE; MOIST.	
								20		BOTTOM OF HOLE AT 4.0 FT.	ALGER REFUSAL AT 4.0 FT.
								25		ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	
								30			
								35			
											ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
											* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.



GEOLOGIC DRILL LOG						PROJECT		JOB NO.	SHEET NO.	HOLE NO.			
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS						COORDINATES			14501-130	1 OF 1	MISS-244R		
						MO00,E1400			ANGLE FROM NODAL	90°	BEARING		
BEGIN	COMPLETED	DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH				
7/25/06	7/25/06	MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	5.0'	0.0'	5.0'				
CORE RECOVERY (%)		CORE BOXES	SAMPLES	REL. TOP OF CASING	GROUND EL.	DEPTH/VEL. GROUND WATER		DEPTH/VEL. TOP OF ROCK					
N/A		N/A	N/A	N/A	97.6'	NONE OBSERVED		N/A					
SAMPLE NUMBER DEPTH/FALL			CASING LEFT IN HOLE DIA./LENGTH			LOGGED BY							
N/A			N/A			D. MCGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLE APPROXIMATE LENGTH (CORE ONLY)	SAMPLE DEPTH (CORE ONLY)	SAMPLE DIAMETER	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOSS IN FT. SPAL	PERCENTAGE IN P.S.I.	TIME IN MINUTES						
ALGER, 6" THROUGHOUT.								97.6	0				
								96.1				0.0-1.5'; SANDY SILT (CL-MI); DARK YELLOWISH BROWN (OYR4/2); FINE GRAINED; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT (GRASS ROOTS); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.
								94.1				1.5-3.5'; SILTY SAND (ML); DARK REDDISH BROWN (OYR3/4); FINE TO COARSE GRAINED WITH A FEW 0.5-2.0' PIECES OF WELL CONSOLIDATED SANDSTONE; SOFT; POORLY SORTED; POORLY CONSOLIDATED; MOIST.	
								93.6				3.5-4.0'; SANDY SILT (ML-CL); MODERATE BROWN (OYR3/4); FINE GRAINED; SOFT; CLAYEY; STICKY; DENSE IN PLACE; MOIST.	*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
							92.6	5			4.0-5.0'; SILTY SAND (ML); AS IN 1.5-3.5' ABOVE.	ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.	
													BOTTOM OF HOLE AT 5.0 FT. ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.
									10				
									15				
									20				
									25				
									30				
									35				

36-INCH SPOON, ST-BELLY TUBE, 3-PIECE PITCHER POTTER

SITE

MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO.

MISS-244R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-130	1 OF 1	MISS-245R					
COORDINATES				N700, E1400		ANGLE FROM N090		BEARINGS					
						90°		N/A					
BEGAN	COMPLETED	BILLER	DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	RICK (FT.)	TOTAL DEPTH					
7/25/86	7/25/86	MORETRENCH ENVIRONMENTAL SERVICES	MOBILE B-33		6"	5.0'	0.0'	5.0'					
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP OF CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF RICK					
N/A		N/A	N/A	N/A	97.3'	NONE OBSERVED		N/A					
SAMPLE NUMBER WEIGHT/FALL			CASING LEFT IN HOLE DIA./LENGTH		LOGGED BY:								
N/A			N/A		D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE RECOVERY - LENGTH CORE (FT.)	SAMPLE RECOVERY - WEIGHT (%)	SAMPLE IN CORE	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS IN FT. G.P.A.	IN PRESSURE P.S.I.	TIME IN MINUTES						
AUGER, 6", THROUGHOUT.								97.3	0				
								95.3					
								92.3	5				
									10				
									15				
									20				
									25				
									30				
									35				

0.0-2.0': SANDY SILT (M-L); DARK YELLOWISH BROWN (M/YR/2); FINE GRAINED; SOFT; POORLY CONSOLIDATED; NUMEROUS ORGANICS, ESPECIALLY IN UPPER 0.5 FT. (GRASS ROOTS).

2.0-5.0': SILTY SAND (SM); COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT WITH PIECES OF MODERATELY HARD SANDSTONE; POORLY SORTED; POORLY CONSOLIDATED; MOIST.

2.0-4.0': MODERATE BROWN (5YR3/4) SPECKLED WITH A LIGHT GRAY (N7) SILTY MATERIAL (FILL?).

4.0-5.0': DARK REDDISH BROWN (6R3/4).

BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.

SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.

EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.

*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

RE-PRINT SPECIALTY-QUALITY TAPES
 P-000000 P-000000 P-000000

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. MISS-245R




GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				HOLE FROM HORIZ.		BEARINGS	
										N700,E1300				90°		N/A	
BEGIN		COMPLETED		DRILLER			DRILL MAKE AND MODEL			HOLE SIZE		OVERBURDEN FT.		ROCK FT.		TOTAL DEPTH	
7/25/86		7/25/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33			6"		5.0'		0.0'		5.0'	
CORE RECOVERY %/SD			CORE BOXES		SAMPLES		REL. TOP OF CASING		GROUND EL.		DEPTH/REL. GROUND WATER			DEPTH/REL. TOP OF ROCK			
N/A			N/A		N/A		N/A		97.7'		NONE OBSERVED			N/A			
SAMPLE NUMBER HEIGHT/FALL				CASING LEFT IN HOLE, DR. ALTHRN				LOGGED BY:									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER APPROX. LENGTH CORRECTION	SAMPLER RECOVERY CORRECTION	SAMPLER LOSS	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF MUDS, ETC.					
				LOSS IN FT. OR IN. P.S.F.	PERCENTAGE P.S.F.	TIME IN MINUTES											
ALGER, 6" THROUGHOUT.							97.7	0									
							97.2			0.0-0.5': SANDY SILT (S); DARK YELLOWISH BROWN (SYR4/2); FINE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED; NUMEROUS GRASS ROOTS AND OTHER ORGANICS; DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.						
						92.7	5		0.5-5.0': SILTY SAND (SM); COLOR STRATIFIED SOIL HORIZONS; MOSTLY FINE TO MEDIUM GRAINED WITH 20% ROUNDED GRAVEL OF VARIOUS LITHOLOGIES.								
										0.5-2.0': SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); DRY. 0.5-1.0': DARK YELLOWISH ORANGE (OYR4/6). 1.0-2.0': DARK YELLOWISH BROWN. 2.0-5.0': DARK REDDISH BROWN (OR3/4); VERY SILTY. BOTTOM OF HOLE AT 5.0 FT. ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.						
								10				ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.					
								15									
								20									
								25									
								30									
								35									

SP-SPLIT SPONS; ST-SPLIT TUBE;
D-DRILLER; P-PITCHER; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NJSS-246R



GEOLOGIC DRILL LOG				PROJECT			JOB NO.	SHEET NO.	HOLE NO.			
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES			14501-130	1 OF 1	NISS-247R			
				N700,E1500			ANGLE FROM HORIZ.	BEARING				
DATE	COMPLETED	DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH			
7/25/06	7/25/06	MORTRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	10.0'	0.0'	10.0'			
CORE RECOVERY(FT./%)		CORE BOXES	SAMPLES	EL. TOP OF CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
N/A		N/A	N/A	N/A	97.1'	6.5'/98.6'		N/A				
SAMPLE NUMBER HEIGHT/FALL			CASING LEFT IN HOLE, DIA./LENGTH		LOGGED BY:							
N/A			N/A		D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LEAD IN CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE BELOW PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAIN LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOGS IN FT. & IN.	PRESSURE P.S.I.	TIME IN MINUTES						
AUGER, 6", THROUGHOUT.							97.1	0				
							95.6					SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION  7/25/06 EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. *DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CLITTINGS. ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
							93.6					
							91.6	5				
							87.1	10				
								15				
								20				
								25				
								30				
								35				



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS										FUSRAP		14501-130		1 OF 1		NISS-240R			
COORDINATES										N000, E1500		AZIMUTH FROM HORIZ.		90°		SLANT		N/A	
DATE		COMPLETED		DRILLER				DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)		TOTAL DEPTH			
7/25/06		7/25/06		MOORE TRENCH ENVIRONMENTAL SERVICES				MOBILE B-33		6"		8.5'		0.0'		8.5'			
CORE RECOVERY (%)				CORE BOXES		SAMPLES		BL. TOP OF CORE		GROUND EL.		DEPTH/VEL. GROUND WATER		DEPTH/VEL. TOP OF ROCK					
N/A				N/A		N/A		N/A		97.1'		8.0' / 09.1'		N/A					
SAMPLE NUMBER IDENT./ALL				CORES LEFT IN HOLE: DIA./LENGTH				LOGGED BY:											
N/A				N/A				D. McGRANE											
SAMPLE TYPE AND DIAMETER	SAMPLE NUMBER	SAMPLE DEPTH	SAMPLE LENGTH	SAMPLE WEIGHT	SAMPLE COLOR	SAMPLE TEXTURE	SAMPLE COMMENTS	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPE LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.			
								LOGS	IN	OUT									
AUGER, 6", THROUGHOUT.											97.1	0							
											93.6	5							
											88.6	8.5							
												10							
												15							
											20								
											25								
											30								
											35								

0.0-3.0': SANDY SILT (SL) - BLK/DK YELLOISH BROWN (10YR 4/2) WITH OCCASIONAL PIECES OF DARK REDDISH BROWN (10R3/4) SANDSTONE; MOSTLY FINE GRAINED WITH OCCASIONAL PEBBLES AND COBBLES; POORLY SORTED; HUMIC ROOTS (0.0-0.5 FT) AND ORGANICS; DRY; PIECES OF RED BRICK AND GLASS (FILL)

3.5-4.5': SILTY SAND (SM) WITH TWO CLAYEY (SC) LENSES; COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT; LOOSE TO DENSE IN PLACE; MOST TO SATURATED AT 8.0 FT.

4.5-5.5': MODERATE BROWN (5YR3/4) WITH A FEW LO-2.0" GRAYISH BLACK (N2) CLAYEY LENSES; DENSE IN PLACE; OCCASIONAL PIECES OF BRICK, GLASS, AND SANDSTONE (FILL)

5.5-6.0': CLAYEY LENSE (SC) PALE BLUE (5PB7/2) DENSE; STICKY.

6.0-8.5': DARK REDDISH BROWN (10R3/4) WITH A FEW LO-3.0" DENSE GRAYISH BLACK LENSES; CLAY BINDER; OCCASIONAL PIECES OF POORLY TO WELL CEMENTED SANDSTONE.

BOTTOM OF HOLE AT 8.5 FT.
AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.

SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.

EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.

7/25/06

AUGER REFUSAL AT 8.5 FT.

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

SB-3PL/ SP-2; ST-2; TB-1; T-1; P-1; F-1; O-1

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-240R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.		SHEET NO.		HOLE NO.				
				FUSRAP		14501-138		1 OF 1		NISS-249R				
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES				AZIMUTH FROM HORIZ.		BEARINGS				
				N900, E1500				90°		N/A				
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)				
7/28/86		7/28/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'				
CORE RECOVERY (FT./30)		CORE DIAMETER		SAMPLES		REL. TOP OF CASING		GROUND EL.		DEPTH/REL. GROUND WATER				
N/A		N/A		N/A		N/A		97.9'		NONE OBSERVED				
DEPTH/REL. TOP OF ROCK		SAMPLE NUMBER		CASING LEFT IN HOLE (O.D./L.D./W)		LOGGED BY:								
N/A		N/A		N/A		D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH (FEET)	SAMPLE DEPTH (FEET)	SAMPLE DEPTH (FEET)	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPE LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
					LOGS IN FT. P.S.F.	PRESSURE IN P.S.I.	TIME IN MINUTES							
AUGER, 6" THROUGHOUT.								97.9	0			0.0-5.0': SILTY SAND (S&G) DARK REDDISH BROWN (B&G) FINE TO MEDIUM GRAINED WITH NUMEROUS SANDSTONE PEBBLES AND GRAVEL; POORLY SORTED; POORLY CONSOLIDATED NUMEROUS GRASS ROOTS AND ORGANICS IN UPPERMOST 0.5 FT; DECOMPOSED SANDSTONE; DRY TO SLIGHTLY	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.	
								92.9	5			BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING. •DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CLTTINGS.	
										10				ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
									15					
									20					
									25					
									30					
									35					

30-SAMPLE SPOOLS ST-DRILLBY TUBE,
D-CORRECTION P-P-CORRECTION Q-OTHER

DATE

MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO.

NISS-249R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	WELL NO.					
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-130	1 OF 1	NISS-250R					
COORDINATES				N1000,E1500		ANGLE FROM HORIZ.		BEARINGS					
						90°		N/A					
BEGAN	COMPLETED	DRILLER	MORETRENCH ENVIRONMENTAL SERVICES	DRILL MAKE AND MODEL	MOBILE B-33	HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)					
7/28/86	7/28/86					8"	0.0'	2.5'					
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP OF CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK					
N/A		N/A	N/A	N/A	99.7'	NONE OBSERVED		0.0' / 99.7'					
SAMPLE NUMBER HEIGHT / FALL		CASING LEFT IN HOLE (IN./LBS/IN)		LOGGED BY:									
N/A		N/A		D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE SPACING LENGTH (FEET)	SAMPLE RECOVERY CORE RECOVERY	SAMPLE IN CORE	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION *	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG	IN	IN						
AUGER, 6" THROUGHOUT.								99.7	0				
								97.2	2.5			0.0-2.5' DECOMPOSED SANDSTONE; DARK REDDISH BROWN (OR) / AN ARGILLACEOUS (SAND FINE TO MEDIUM GRAINED; TOTALLY DECOMPOSED TO HIGHLY WEATHERED; AUGER SPOILS CONSIST OF UNCONSOLIDATED (LOOSE) SOFT, SILTY SAND AND MODERATELY HARD, WELL CEMENTED SANDSTONE GRAVEL; FEW GRASS ROOTS AND ORGANICS IN UPPERMOST 0.5 FT. DRY.	
									5			EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.	
									10			*DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.	
									15			AUGER REFUSAL AT 2.5 FT.	
									20			SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.	
									25				
									30				
									35				
	16-SPLIT SPOON ST-BLBY TUBE				SITE				MAYWOOD INTERIM STORAGE SITE - NJVIS				WELL NO. NISS-250R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES				MOBILE FROM HORIZ.		BEARING			
				N1100,E1500				90°		N/A			
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)			
7/28/86		7/28/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		0.0'			
ROCK (FT.)		TOTAL DEPTH		CORE RECOVERY (FT./%)		CORE BONES		SAMPLES		REL. TOP OF CASING			
1.0'		1.0'		N/A		N/A		N/A		N/A			
GROUND BL.		DEPTH/REL. GROUND WATER		DEPTH/REL. TOP OF ROCK									
100.7'		NONE OBSERVED		1.0'/99.7'									
SAMPLE NUMBER WEIGHT/FALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH - LOGGING CORE RUN	SAMPLE DEPTH - CORE RECOVERY	SAMPLE DIAMETER	PERCENT CORE RECOVERY	WATER PRESSURE TESTS		ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
					LOG IN FT. G.P.A.L.	TIME IN MINUTES							
AUGER 6", THROUGHOUT.							100.7	0					
							99.7	LO			<p>0.0-LO: DECOMPOSED SANDSTONE; DARK REDDISH BROWN 0.03/4% ARGILLACEOUS, FINE TO MEDIUM GRAINED, TOTALLY DECOMPOSED TO HIGHLY WEATHERED; AUGER SPOILS CONSIST OF UNCONSOLIDATED (LOOSE), SOFT, SILTY SAND (SAND) AND MODERATELY HARD, WELL CEMENTED SANDSTONE GRAVEL; FEW GRASS ROOTS AND ORGANICS IN UPPERMOST 0.5 FT. DRY.</p> <p>BOTTOM OF HOLE AT LO FT.</p> <p>AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.</p>	<p>SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.</p> <p>EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.</p>	
								5					
								10					
								15					
								20					
								25					
								30					
								35					
SE-SPLIT SPOILS; ST-SHED BY TUBE; D-DEBRIS; P-PITCHES; O-OTHER				SITE				MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO. MISS-251R	

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
SITE MAYWOOD INTERIM STORAGE SITE - NJV15				COORDINATES		14501-138	1 OF 1	NISS-252R					
				N1200,E1500		ANGLE FROM HORIZ.		BEARING					
						90°		N/A					
START	COMPLETED	DRILLER		DRILL MAKE AND MODEL	HOLE SIZE	OVERLASH (FT.)	ROCK (FT.)	TOTAL DEPTH					
7/28/06	7/28/06	MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33	6"	2.0'	1.5'	3.5'					
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	REL. TOP OF CORES	GROUND CL.	DEPTH/REL. GROUND WATER		DEPTH/REL. TOP OF ROCK					
N/A		N/A	N/A	N/A	100.6'	NONE OBSERVED		2.0'/98.6'					
SAMPLE NUMBER WEIGHT/FALL		CORES LEFT IN HOLE: DIA./DEPTH			LOGGED BY:								
N/A		N/A			D. MCGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH	SAMPLE IDENTITY	SAMPLE WEIGHT	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CONTACTS OF BEDDING, ETC.
					LOSS IN P.S.P.	P.S.P.	TIME IN MINUTES						
AUGER, 6" THROUGHOUT.								100.6	0				SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION. EBERLINE ANALYTICAL CORPORATION PERFORMED GAMMA LOGGING.
							98.6						
							97.1	3.5					
									5			0.0-2.0': SILTY SAND (S&G) COLOR STRATIFIED SOIL HORIZONS; FINE TO COARSE GRAINED; SOFT; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); DRY. 0.0-0.5': DARK REDDISH BROWN (GORS/4); FEW ORGANICS; NUMEROUS PIECES OF SANDSTONE GRAVEL. 0.5-2.0': DARK YELLOWISH BROWN (GYM/2).	
									10			2.0-3.5': DECOMPOSED SANDSTONE; DARK REDDISH BROWN ARGILLACEOUS; FINE TO MEDIUM GRAINED; TOTALLY DECOMPOSED; HIGHLY WEATHERED. AUGER SPOILS CONSIST OF UNCONSOLIDATED (LOOSE), SOFT, SILTY SAND (S&G) AND MODERATELY HARD, WELL CEMENTED SANDSTONE GRAVEL; DRY. BOTTOM OF HOLE AT 3.5 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	
									15				
									20				
									25				
									30				
									35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

SS-SILT; SP-SAND; ST-SILT-CLAY; SCL-SAND-CLAY; P-PITCHER; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJV15

HOLE NO. NISS-252R



GEOLOGIC DRILL LOG				PROJECT				JOB NO.		SHEET NO.		HOLE NO.					
				FUSRAP				14501-130		1 OF 1		NJSS-253R					
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES				AZIMUTH FROM HORIZ.				BEARING					
				N1300,E1500				90°				N/A					
BEGIN		COMPLETED		DRILLER			DRILL MOUNT AND MODEL			HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH	
7/28/86		7/28/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33			6"		10.0'		N/A		10.0'	
CORE RECOVERY (FT./%)			CORE DIAMETER		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER			DEPTH/EL. TOP OF ROCK			
N/A			N/A		N/A		N/A		99.0'		NONE OBSERVED			N/A			
SAMPLE NUMBER (DEPTH/FALL)				CASING LEFT IN HOLE (IN./LENGTH)				LOGGED BY:									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH (INCHES)	SAMPLE RECOVERY (PERCENT)	SAMPLE LOSS (PERCENT)	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRANIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
				LOG IN FT. S.P.A.L.	PRESSURE IN P.S.I.	TIME IN MINUTES											
AUGER, 6", THROUGHOUT.							99.0	0									
							98.0										
								5									
								10									
							95.0										
								15									
								20									
								25									
								30									
								35									

0.0-1.0': SANDY SILT (S); DARK YELLOWISH BROWN (10YR/2); FINE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; DRY.

1.0-4.0': SILTY SAND (S); COLOR STRATIFIED SOIL HORIZONS; FINE TO COARSE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE) WITH ONE DENSE CLAYEY (SC) ZONE (7.0-7.5 FT); DRY TO VERY MOIST.

4.0-7.0': DARK YELLOWISH ORANGE (10YR/6); FINE TO MEDIUM GRAINED; DRY.

7.0-7.5': CLAYEY SILTY SEAM WITH NUMEROUS ROUNDED PEBBLES OF VARIOUS LITHOLOGIES; DARK REDDISH BROWN (6.5YR/4); MOIST.

7.5-10.0': DARK REDDISH BROWN; OCCASIONAL ROUNDED PEBBLES; VERY MOIST NEAR GROUND WATER LEVEL.

BOTTOM OF HOLE AT 10.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.

SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBELINE ANALYTICAL CORPORATION.

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

SE-SPLIT SPONS; ST-SHELBY TANK; D-DEBRIS; P-PITCHER; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NJSS-253R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.		SHEET NO.		HOLE NO.		
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-130		1 OF 1		NISS-254R		
COORDINATES				N1400,E1500				ANGLE FROM HORIZ.		BEARING		
N/A				N/A				90°		N/A		
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		
7/28/86		7/28/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		
CORE RECOVERY (%)		CORE BOXES		SAMPLES		REL. TOP OF CASING		GROUND EL.		DEPTH/REL. GROUND WATER		
N/A		N/A		N/A		N/A		98.9'		NONE OBSERVED		
SAMPLE NUMBER BEGIN/END				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY				
N/A				N/A				D. McGRANE				
SAMPLE TYPE AND DIAMETER	SAMPLE ORIENTATION (LIGHT SIDE WEST)	SAMPLE RECOVERY (CORE RECOVERY)	SAMPLE BLOCK BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOG IN FT. S.P.A.L.	PRESSURE IN P.S.I.	TIME IN MINUTES						
AUGER, 6" THROUGHOUT.							98.9	0				
							97.9					
							93.9	5				
								10				
								15				
								20				
								25				
								30				
								35				

0.0-1.0': SANDY SILT (CL); DARK REDDISH BROWN (W3/4); SOFT, FINE TO MEDIUM GRAINED; POORLY SORTED; POORLY CONSOLIDATED (LOOSE); NUMEROUS ROUND PEBBLES; NUMEROUS ROOTS AND ORGANICS; DRY.

1.0-5.0': SILTY SAND (SM-SC); COLOR STRATIFIED SOIL HORIZONS; SOFT, FINE TO MEDIUM GRAINED; MOSTLY POORLY CONSOLIDATED (LOOSE); SLIGHTLY MOST TO MOST.

1.0-3.0': DARK YELLOWISH BROWN (OYR4/2) WITH A LOT DENSE, CLAYEY, GRAYISH BLACK (O2) ORGANIC LAYER (2.5-2.6 FT).

3.0-4.0': DARK YELLOWISH ORANGE (OYR6/6).

4.0-5.0': DARK REDDISH BROWN.

BOTTOM OF HOLE AT 5.0 FT.

AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.

SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				MOBILE FROM HOLE		RELATIONS	
										N1500, E1500				90°		N/A	
BEGIN		COMPLETED		DRILLER			DRILL NAME AND MODEL			HOLE SIZE		OVERBURDEN FT./J		ROCK FT./J		TOTAL DEPTH	
7/28/86		7/28/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33			6"		5.0'		0.0'		5.0'	
CORE RECOVERY %/L/30				CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK			
N/A				N/A		N/A		N/A		97.0'		4.5'/92.5'		N/A			
SAMPLE NUMBER WEIGHT/FULL				CASING LEFT IN HOLE/DIAPHRAGM				LOGGED BY									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RECOVERY	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.				
					LOG	P.S.P.A.	PRELIMINARY P.S.I.										
AUGER, 6" THROUGHOUT.								97.0	0				SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION 7/28/86				
							96.5				0.0-0.5': SANDY SILT (CL); MODERATE BROWN (5YR5/2) FINE GRAINED, SOFT, POORLY SORTED, POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOIST. 0.5-3.0': SILTY SAND (SM) COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED, SOFT, POORLY SORTED, POORLY CONSOLIDATED (LOOSE); MOIST TO SATURATED AT 4.0 FT. 0.5-3.0': DARK YELLOWISH ORANGE G0YR6/6A. 3.0-5.0': DARK YELLOWISH BROWN G0YR4/2.	ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM. * DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.					
							92.0	5									
									10								
									15								
									20								
									25								
									30								
									35								



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
MAYWOOD INTERIM STORAGE SITE - NJVIS										FUSRAP				14501-130		1 OF 1		MISS-256R	
COORDINATES										N1600,E1500				ANGLE FROM HORIZ.		BEARINGS			
N/A										N/A				90°		N/A			
BEGIN		COMPLETED		DRILLER			DRILL MAKE AND MODEL			HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH			
7/28/86		7/28/86		MORTRECH ENVIRONMENTAL SERVICES			MOBILE B-33			6"		5.0'		0.0'		5.0'			
CORE RECOVERY (FT./%)			CORE DIAM.		SAMPLES		REL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER			DEPTH/EL. TOP OF ROCK					
N/A			N/A		N/A		N/A		96.0'		NONE OBSERVED			N/A					
SAMPLE NUMBER WEIGHT/FALL				CASING LEFT IN HOLE/DIA./LENGTH				LOGGED BY:											
N/A				N/A				D. McGRANE											
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LEADING CORE FEET	SAMPLER RECOVERY CORE RECOVERY	SAMPLER BLANK	PRIORITY CORE RECOVERY	WATER PRESSURE TESTS				ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
					LOGS IN P.S.P.A.	PRESSURE IN P.S.P.	TIME IN MINUTES	IN MINUTES											
AUGER, 6" THROUGHOUT.									96.0	0			0.0-3.0': SANDY SILT (G1); MODERATE BROWN (5YR5/4) FINE GRAINED; SOFT; POORLY CONSOLIDATED BUT DENSE IN PLACE; CLAY BINDER; NUMEROUS GRASS ROOTS (0.0-0.5 FT) AND ORGANICS; MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.					
								93.0				3.0-5.0': SILTY SAND (SM); MOTTLED DARK YELLOWISH BROWN (5YR4/2) AND DARK YELLOWISH ORANGE (5YR6/6) WITH A FEW PALE GREEN (5G7/2) SILTY LENSES 3.0-4.0 FT; FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); MOIST.							
									91.0	5			5.0-5.0': BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.						
										10									
										15									
										20									
										25									
										30									
										35									

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SP/LP SPOOLS ST-DRILBY TAIL; D-DRILLER P-PITCHER; O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. MISS-256R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.		SHEET NO.		HOLE NO.					
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-130		1 OF 1		NISS-257R					
COORDINATES				NIT00,E1490				ANGLE FROM HORIZ.		BEARING					
7/28/86				7/28/86				DRILLER		DRILL MAKE AND MODEL		HOLE SIZE			
7/28/86				7/28/86				NORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"			
OVERLAP (FT.)				ROCK (FT.)				TOTAL DEPTH							
5.0'				0.0'				5.0'							
CORE RECOVERY (L/B)				CORE SERIES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER			
N/A				N/A		N/A		N/A		96.1'		4.5'/91.6'			
DEPTH/EL. TOP OF ROCK				SAMPLE NUMBER				CASING LEFT IN HOLE				LOGGED BY			
N/A				N/A				N/A				D. McGRANE			
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH	SAMPLE DEPTH	SAMPLE ID	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.			
				LOGS	IN	OUT									
AUGER, 6", THROUGHOUT.							96.1	0							
							95.6								
							91.1	5							
								10							
								15							
								20							
								25							
								30							
								35							

0.0-0.5'; SANDY SILT (M) MODERATE BROWN (5YR3/4) FINE GRAINED, SOFT, POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOST.

0.5-5.0'; SILTY SAND (SM-SM) COLOR STRATIFIED WITH NUMEROUS CLAYEY LENSES OF VARIOUS COLORS; FINE TO MEDIUM GRAINED, SOFT; UNCONSOLIDATED (LOOSE) OCCASIONALLY DENSE (TIGHTLY PACKED CLAYEY LENSES) MOST TO SATURATED AT 4.5 FT.

0.5-2.0'; DARK REDDISH BROWN (6R3/4) WITH DENSE GRAYISH BLACK (2) CLAYEY LENSES.

2.0-5.0'; DARK YELLOWISH BROWN (6YR4/2) WITH DENSE DARK YELLOWISH ORANGE (6YR6/6) AND PALE GREEN (5G7/2) CLAYEY LENSES.

BOTTOM OF HOLE AT 5.0 FT.

AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.

7/28/86

SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.			
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES			14501-130		1 OF 1		NISS-250R			
				N1500,E1400			ANGLE FROM VERT.		90°		SLANTS			
DATE		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		TOTAL DEPTH		
7/28/86		7/28/86		MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		5.0'		
CORE RECOVERY (FT./%)			CORE DIAM.		SAMPLES		EL. TOP OF CORE		GROUND EL.		DEPTH/VEL. GROUND WATER		DEPTH/VEL. TOP OF ROCK	
N/A			N/A		N/A		N/A		97.0'		NONE OBSERVED		N/A	
SAMPLE NUMBER (HOLE/FULL)				CORES LEFT IN HOLE (NO./LENGTH)				LOGGED BY:						
N/A				N/A				D. McGRANE						
SAMPLE TYPE AND DIAMETER	SAMPLE INTERVAL LENGTH (CORE RUN)	SAMPLE INTERVAL (CORE RECOVERY)	SAMPLE LENGTH	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAIN LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
					LOGS	IN	PSI/AL							
AUGER, 6"; THROUGHOUT.								97.0	0					
								96.0				0.0-1.0': SANDY SILT (M); MODERATE BROWN (5YR 3/4) FINE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBELINE ANALYTICAL CORPORATION.	
								92.0	5			1.0-5.0': SILTY SAND (SM-SC) MOTTLED DARK YELLOWISH BROWN (5YR 4/2) AND DARK YELLOWISH ORANGE (5YR 6/4) WITH OCCASIONAL LOOSE, PALE GREEN (5G 7/2) SILT LENSES AND DARK REDDISH BROWN (5R 3/4) SANDSTONE GRAVEL; SOFT; POORLY CONSOLIDATED (LOOSE); BOTTOM OF HOLE AT 5.0 FT.		
												AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		
									10					
									15					
									20					
									25					
									30					
									35					
30-SPLE SPOILS STORED BY THIS ENVIRONMENTAL SERVICES OFFICE				SITE				MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO. NISS-250R		

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				HOLE FROM HORIZ.		BEARING	
										N1400, E1400				90°		N/A	
DRILLER		COMPLETED		DRILLER			DRILL HOLE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)		ROCK (FT.)	TOTAL DEPTH				
7/30/86		7/30/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33		6"	5.0'		0.0'	5.0'				
CORE RECOVERY (L/T)			CORE BOXES		SAMPLES	EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK					
N/A			N/A		N/A	N/A		98.9'		NONE OBSERVED		N/A					
SAMPLE NUMBER IDENT./FALL				CASING LEFT IN HOLE (DIA./LENGTH)				LOGGED BY									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LEAD IN CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
				LOGS FT. IN P. C/A.	PRESSURE P.S.I.	TIME IN MIN. PER SAMPLES											
AUGER, 6" THROUGHOUT.							98.9	0				SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION. * DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CLIPPINGS.					
							97.9			0.0-1.0': SANDY SILT (CL); BLACK; FINE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOIST.							
							93.9	5		1.0-5.0': SILTY SAND (SM-SC); COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE) BUT CLAYEY AND DENSE (1.0-3.3 FT); MOIST. 1.0-3.0': DARK REDDISH BROWN (OR3/4). 3.0-3.3': ORGANIC LAYER, BLACK. 3.3-4.0': DARK YELLOWISH BROWN (OYR4/2). 4.0-5.0': DARK YELLOWISH ORANGE (OYR6/6). BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.							
								10									
								15									
								20									
								25									
								30									
								35									
SE-SPUT SPOON ST-ORBY TUBE; P-CORING P-PITCH; O-OTHER										SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO. NISS-261R			



GEOLOGIC DRILL LOG				PROJECT		JOB NO.		SHEET NO.		HOLE NO.		
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES				ANGLE FROM NAD83		READING		
				N1400, E1300				90°		N/A		
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		
7/30/06		7/30/06		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		
CORE RECOVERY (FT./%)		CORE LINES		SAMPLES		BL. TOP OF CASING		GROUND BL.		DEPTH/VEL. GROUND WATER		
N/A		N/A		N/A		N/A		90.8'		NONE OBSERVED		
SAMPLE NUMBER BEGIN/END				CASING LEFT IN HOLE: IN/ALERT IN				LABBED BY:				
N/A				N/A				D. MCGRANE				
SAMPLE TYPE AND DIAMETER	SAMPLED APPROX. LEGTH CORE RUN	SAMPLE INTERVAL CORE THROUGHOUT	SAMPLE BEING PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LONG IN FT. IN	PRESSURE P.S.I.	TIME IN MIN. IN						
AUGER, 6", THROUGHOUT.							98.8	0				SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
							97.8				0.0-1.0': SANDY SILT (CL); BLACK; FINE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOIST.	
							93.8	5			1.0-5.0': SILTY SAND (SM-SC); COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE) BUT CLAYEY AND DENSE (0.0-3.3 FT); MOIST. 1.0-3.0': DARK REDDISH BROWN (OOR3/4). 3.0-3.3': ORGANIC LAYER, BLACK. 3.3-4.0': DARK YELLOWISH BROWN (OYR4/2). BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	
								10				ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
								15				
								20				
								25				
								30				* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
								35				



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.		
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES			14501-130	1 OF 1	NISS-263R	
				N1500, E1300			ANGLE FROM HORIZ.	BEARINGS		
DATE	COMPLETED	DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH	
7/30/06	7/30/06	MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	5.0'	0.0'	5.0'	
CORE RECOVERY (FT./30)		CORE BOXES	SAMPLES	BL. TOP OF CORE	GRIND BL.	DEPT/VEL. GROUND WATER		DEPT/VEL. TOP OF ROCK		
N/A		N/A	N/A	N/A	96.8'	NONE OBSERVED		N/A		
SAMPLE NUMBER WEIGHT/FALL		CORES LEFT IN HOLE; DR. LENGTH			LOGGED BY:					
N/A		N/A			D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH (CORE LOSS)	SAMPLER RECOVERY CORE RECOVERY	SAMPLER BLIND	WATER PRESSURE TESTS	ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
AUGER, 6", THROUGHOUT.					96.8	0			0.0-2.0': SANDY SILT (OL-M); MODERATE BROWN (STR/0) FINE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS ROOTS (0.0-0.5 FT) AND ORGANICS; MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
					94.8			2.0-5.0': SILTY SAND (SM); COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); MOIST.		
					91.8	5		2.0-4.0': DARK YELLOWISH ORANGE (OYR6/6L); 4.0-5.0': DARK YELLOWISH BROWN (OYR4/2); MOSTLY MEDIUM GRAINED.		
								BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		
						10				
						15				
						20				
						25				
						30				
						35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SP/LT SPOILS; ST-EMPTY TUBS; S-DRILLING P-PISTON; P-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-263R



GEOLOGIC DRILL LOG				PROJECT				JOB NO.		SHEET NO.		HOLE NO.	
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES				14501-130		1 OF 1		M15S-264R	
DRILLER				DRILL MAKE AND MODEL				HOLE SIZE		OVERBURDEN (FT.)		DIP	
COMPLETED				MOBILE B-33				6"		10.0'		90°	
CORE RECOVERY (FT./30)				CORE DIAMETER		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER	
N/A				N/A		N/A		N/A		90.5'		8.0'/90.5'	
SAMPLE NUMBER				CASING LEFT IN HOLE (IN./LBS/IN)				LOGGED BY:					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLE APPROXIMATE LENGTH (CORE ONLY)	SAMPLING METHOD	SAMPLING DEPTH	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
				LOGS IN FT. G.P.A.L.	PRELIMINARY P.S.I.	TIME IN MINUTES							
AUGER, 6" THROUGHOUT.							90.5	0					
							90.0	5		0.0-0.5': SANDY SILT (M); MODERATE BROWN (5YR 3/4) FINE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION. 7/30/86		
										0.5-10.0': SILTY SAND (SM) COLOR STRATIFIED SOIL HORIZONS; FINE-COARSE GRAINED; POORLY SORTED; POORLY CONSOLIDATED (LOOSE) WITH A DENSE CLAYEY ZONE.			
										0.5-2.0': DARK REDDISH BROWN (6YR 3/4); CLAY BINDER; FINE TO MEDIUM GRAINED; FEW ORGANICS. 0.5-2.0': MOIST-SATURATED AT 8.0 FT. 2.0-6.0': DARK YELLOWISH ORANGE (10YR 6/6); FINE TO MEDIUM GRAINED. 6.0-10.0': DARK YELLOWISH BROWN (8YR 4/2); FINE TO COARSE GRAINED.			
							88.5	10			BOTTOM OF HOLE AT 10.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		
								15					
								20					
								25					
								30					
								35					

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-PLY 10000 ST-001BY TUBS
10-000000 P-01000 0-0100

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. M15S-264R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES		14501-130	1 OF 1	NISS-265R				
DATE		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE				
7/30/06		7/30/06		MOORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"				
OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH								
5.0'		0.0'		5.0'								
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	REL. TOP OF CASING	GROUND EL.	DEPTH/VEL. GROUND WATER		DEPTH/VEL. TOP OF ROCK				
N/A		N/A	N/A	N/A	99.1'	NONE OBSERVED		N/A				
SAMPLE BARRED (YES/NO/FALL)		CASING LEFT IN HOLE (Y/N)/DEPTH		LOGGED BY:								
N/A		N/A		D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLER APPLIED LENGTH CORRECTION	SAMPLE DEPTH CORRECTION	SAMPLE BEING RECOVERED CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	DRIVING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOAD IN FT. C/P.A.	PRESSURE IN P.S.I.	TIME IN MINUTES						
AUGER, 6", THROUGHOUT.							99.1	0			0.0-0.3: ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
							98.8				0.3-5.0: SILTY SAND (SILTY COLOR) STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); MOIST.	
							94.1	5			0.3-1.0: MODERATE BROWN (SILTY) WITH PIECES OF DARK REDDISH BROWN (SANDSTONE) GRAVEL.	ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
											1.0-5.0: DARK YELLOWISH BROWN (SANDSTONE) GRAVEL WITH OCCASIONAL ROUNDED QUARTZ PEBBLES.	
											BOTTOM OF HOLE AT 5.0 FT.	* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
											AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.	



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP			14501-130		1 OF 1		NISS-266R		
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES				AZIMUTH FROM HORIZ.		SLANTS			
				N1300, 1300				90°		N/A			
START		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)	TOTAL DEPTH
7/30/86		7/30/86		MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		0.0'	5.0'
CORE RECOVERY (FT./D)			CORE DIAMETER		SAMPLES		EL. TOP OF CASING		GRINDING EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK
N/A			N/A		N/A		N/A		98.3'		NONE OBSERVED		N/A
SAMPLE BAGGING WEIGHT/FALL				CASING LEFT IN HOLE DIA./LENGTH				LOGGED BY					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH - LOGGING CORE AUTH.	SAMPLE RECOVERY - CORE RECOVERY	SAMPLE IN CORE	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	DRILLING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS	IN	IN						
AUGER, 6" THROUGHOUT.								98.3	0				
								98.0				0.0-0.3: ASPHALT. 0.3-5.0: SILTY SAND (S&S) COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT, POORLY CONSOLIDATED (LOOSE, MOIST). 0.3-2.5: DARK YELLOWISH BROWN (0YR4/2). 2.5-3.5: DARK YELLOWISH ORANGE (0YR6/6). 3.5-5.0: DARK YELLOWISH BROWN. BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
								93.3	5				
									10				
									15				
									20				
									25				
									30				
									35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

20-FOOT SPONGE STOP-CHUCK TUBE; 10-FOOT SPONGE STOP-CHUCK TUBE

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-266R



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-130
 SHEET NO.: 1 OF 1
 HOLE NO.: NISS-267R

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 COORDINATES: N1105, E1100
 AZIMUTH FROM HORIZ.: 90°
 BEARING: N/A

DRILLER: MORETRENCH ENVIRONMENTAL SERVICES
 DRILL MAKE AND MODEL: MOBILE B-33
 HOLE SIZE: 6"
 OVERLAP (FT.): 10.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 10.0'

DATE: 7/30/86
 COMPLETED: 7/30/86
 CORE RECOVERY (FT./3): N/A
 CORE DIAMETER: N/A
 SAMPLES: N/A
 EL. TOP OF CASING: N/A
 BOREHOLE: 99.5'
 DEPTH/EL. BOREHOLE WATER: 9.8'/89.7'
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE NUMBER IDENT./TOTAL: N/A
 CASING LEFT IN HOLE: DIA./LENGTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLE ADVANCE LOGGING CODE	SAMPLE RECOVERY CODE	SAMPLE BLANK	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS IN P. G.P./AL	W. PRESSURE P.S.I.	TIME IN MINUTES						
AUGER, 6", THROUGHOUT.							99.5	0					SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION. 7/30/86 ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM. * DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
							97.5	5			0.0-2.0': SANDY SILT (CL-MI) MODERATE BROWN (5YR 5/2) FINE GRAINED SOFT POORLY CONSOLIDATED (LOOSE) NUMEROUS GRASS ROOTS (0.0-0.5 FT) AND ORGANICS; SLIGHTLY MOIST. OCCASIONAL ROUNDED PEBBLES AND LO-2.0' GRAVEL; SLIGHTLY MOIST TO SATURATED AT 9.8 FT.		
											2.0-10.0': SILTY SAND (SM), COLOR STRATIFIED SOIL HORIZONS; FINE-MEDIUM GRAINED; SOFT POORLY CONSOLIDATED (LOOSE) WITH ONE DENSE PALE GREEN (5G 7/2) CLAYEY ZONE (6.0-6.5') OCCASIONAL ROUNDED PEBBLES AND 1-2 IN. GRAVEL. SLIGHTLY MOIST-SATURATED AT 9.8 FT.		
							89.5	10			2.0-4.0': DARK REDDISH BROWN (6R3/4) 4.0-10.0': MOTTLED DARK YELLOWISH BROWN (6YR4/2) AND DARK YELLOWISH ORANGE (6YR6/6) BOTTOM OF HOLE AT 10.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		
								15					
								20					
								25					
								30					
								35					

30-SPLIT SPINDLE ST-DRILL TUBE; 0-DRILLING P-DRILLING 0-DRILL

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO.: NISS-267R



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-130
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-260R

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 COORDINATES: N1000, E1100
 ANGLE FROM HORIZ.: 90°
 BEARING: N/A

DRILLER: MORE TRENCH ENVIRONMENTAL SERVICES
 DRILL MAKE AND MODEL: MOBILE B-33
 HOLE SIZE: 6"
 OVERBURDEN (FT.): 5.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 5.0'

CORE RECOVERY 1/30: N/A
 CORE BOXES: N/A
 SAMPLES: N/A
 REL. TOP OF CASING: N/A
 GROUND EL.: 99.5'
 DEPTH/EL. GROUND WATER: NONE OBSERVED
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE NUMBER HEIGHT/FALL: N/A
 CASING LEFT IN HOLE: DIA./LENGTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE - LOGGING CORE RUN	SAMPLER INTERVAL - CORE RECOVERY	SAMPLER LOSS - PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN FT. IN	PERCENT	TIME IN MINUTES						
AUGER, 6" THROUGHOUT.							99.5	0				
							90.5			0.0-1.0' SILTY SILY (CL) MODERATE BROWN (SILTY) FINE GRAINED, SOFT, POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.	
							94.5	5		1.0-5.0' SILTY SAND (SM) DARK REDDISH BROWN (O/S) FINE TO MEDIUM GRAINED WITH NUMEROUS PIECES OF SANDSTONE; SOFT, POORLY SORTED, POORLY CONSOLIDATED; MOIST.		
										BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		

NO-SPLE SPOILS ST-BELLY TUB; P-RECORD; P-PTCHER; O-OTHER
 SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 HOLE NO.: MISS-260R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES		14501-130	1 OF 1	MISS-269R					
				N1400,E1100		ANGLE FROM NORIZ.		BEARING					
						90°		N/A					
BEGIN	COMPLETED	DRIILLER	DRILL NAME AND MODEL	HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH						
7/30/86	7/30/86	MOORETRENCH ENVIRONMENTAL SERVICES	MOBILE B-33	6"	5.0'	0.0'	5.0'						
CORE RECOVERY % L/D		CORE BOXES	SAMPLES	REL. TOP OF CASING	GRINDED CL.	DEPTH/REL. GRINDED WATER		DEPTH/REL. TOP OF ROCK					
N/A		N/A	N/A	N/A	98.5'	NONE OBSERVED		N/A					
SAMPLE NUMBER USED/FALL		CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:								
N/A		N/A			D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH	SAMPLE RECOVERY	SAMPLE RECOVERY	SAMPLE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG	PRESSURE	TIME						
					FT IN	PSI	MIN	98.5	0				
AUGER, 6" THROUGHOUT.								97.5				0.0-1.0'; SANDY SILT (M); MODERATE BROWN (5YR3/4) FINE GRAINED SOFT; POORLY CONSOLIDATED (LOOSE); DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION BY EBERLINE ANALYTICAL CORPORATION.
												1.0-5.0'; SILTY SAND (SM-SC) COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE) WITH OCCASIONAL DENSE CLAYEY LENSES 1.0-2.5 FT AND 4.0-4.3 FT; SLIGHTLY MOIST.	
								93.5	5			1.0-2.5'; MODERATE BROWN (5YR3/4) OCCASIONAL PIECES OF RED BRICK AND GRAVEL, AND A FEW 1.0-2.0' CLAYEY LENSES. 2.5-5.0'; DARK REDDISH BROWN (0R3/4) WITH A GRAYISH BLACK (10Z) ORGANIC LAYER (4.0-4.3 FT); NUMEROUS PIECES OF SANDSTONE GRAVEL. BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	
									10				
									15				
									20				
									25				
									30				
									35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

80-SPLIT SPOILS ST-SHELFY TUBE; 80-DEBRIS; P-PTCHES; 0-OTHER

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. MISS-269R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
SITE MAYWOOD INTERIM STORAGE SITE NJVIS				FUSRAP			14501-130	1 OF 1	NISS-270R				
COORDINATES				N1300,E1100			ANGLE FROM HORIZ.	BEARING	N/A				
DATE	COMPLETED	DRILLER		DRILL NAME AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH				
7/30/86	7/30/86	MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	5.0'	0.0'	5.0'				
CORE RECOVERY(FT./%)		CORE BOXES	SAMPLES	EL. TOP OF CORE	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK					
N/A		N/A	N/A	N/A	98.5'	NONE OBSERVED		N/A					
SAMPLE NUMBER WEIGHT/FALL			CORES LEFT IN HOLE: HULL/LENGTH			LOGGED BY:							
N/A			N/A			D. MCGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLE LOCATION (EASTING, NORTHING, ELEVATION)	SAMPLE DEPTH (FT.)	SAMPLE WEIGHT (LBS.)	SAMPLE WEIGHT (GMS.)	SAMPLE WEIGHT (MGMS.)	WATER PRESSURE TESTS		ELEVATION	DEPTH	GRAPHIC LOG	SAMPLES	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
						LOGS IN FT. @ 24 HRS.	LOGS IN FT. @ 48 HRS.						
AUGER, 6"; THROUGHOUT.								98.5	0				
								98.2				0.0-0.3: ASPHALT. 0.3-5.0: SILTY SAND (S&S) COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); MOIST. 0.3-1.0: MODERATE BROWN (5YR3/4). 1.0-3.0: DARK YELLOWISH ORANGE (6YR6/6). 3.0-5.0: DARK YELLOWISH BROWN (6YR4/2); LESS FINES. BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EVERLINE ANALYTICAL CORPORATION.
								93.5	5				
									10				
									15				
									20				
									25				
									30				
									35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SPLE SPONGE ST-ORLEY TUBE,
D-ORLEY P-PITCHER 0-OTHER

SITE MAYWOOD INTERIM STORAGE SITE
NJVIS

HOLE NO. NISS-270R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES				HOLE FROM HORIZ.		BEARING	
										N900, E1400				90°		N/A	
BEGUN		COMPLETED		DRILLER			DRILL MAKE AND MODEL			HOLE SIZE		OVERLAP (FT.)		RICK (FT.)		TOTAL DEPTH	
8/4/86		8/4/86		MOORE TRENCH ENVIRONMENTAL SERVICES			MOBILE B-33			6"		5.5'		1.5'		7.0'	
CORE RECOVERY (FT./2)			CORE DIAM.		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER			DEPTH/EL. TOP OF ROCK			
N/A			N/A		N/A		N/A		97.9'		3.5'/94.4'			5.5'/92.4'			
SAMPLE NUMBER WEIGHT/FALL				CASING LEFT IN HOLE; DIA./LENGTH				LOGGED BY:									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE INTERVAL LENGTH (CORE RUN)	SAMPLE INTERVAL CORE INTERVAL	SAMPLE WEIGHT	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETAIN. CHARACTER OF DRILLING, ETC.				
					LOGS	IN	PSI										
AUGER, 6", THROUGHOUT.								97.9	0								
								97.6									
								94.4									
								92.4	5								
							90.9	7.0									
									10								
									15								
									20								
									25								
									30								
									35								



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES		14501-138	1 OF 1	NISS-272R					
				N1000,E1400		ANGLE FROM HORIZ.		DIRECTION					
BEGIN	COMPLETED	DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERLAP (FT.)	RICK (FT.)	TOTAL DEPTH				
8/4/86	8/4/86	MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	0.3'	3.2'	3.5'				
CORE RECOVERY (FT./TD)		CORE BONES	SAMPLES	BL. TOP OF CASING	GROUND BL.	DEPTH/VL. GROUND WATER		DEPTH/VL. TOP OF ROCK					
N/A		N/A	N/A	N/A	99.5'	NONE OBSERVED		0.3'/99.2'					
SAMPLE NUMBER IDENT/FALL			CASING LEFT IN HOLE, DIA./LENGTH			LOGGED BY:							
N/A			N/A			D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLE INTERVAL (START/END)	SAMPLE INTERVAL (START/END)	SAMPLE INTERVAL (START/END)	SAMPLE INTERVAL (START/END)	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLER, ETC.
					LOSS IN PRESSURE (PSI)	TIME TO PERFORM (MIN)	TIME TO PERFORM (MIN)						
AUGER 6" THROUGHOUT.								99.5	0				
								99.2					
								96.0	3.5			0.0-0.3: ASPHALT. 0.3-3.5: DECOMPOSED SANDSTONE; DARK REDDISH BROWN (OR) 3/4" FINE TO MEDIUM GRAINED (ARGILLACEOUS); SOFT TO MODERATELY HARD; DRILL SPOILS CONSIST OF SILTY SAND (SM) WITH NUMEROUS PIECES OF POORLY TO WELL CEMENTED SANDSTONE GRAVEL; TOTALLY DECOMPOSED HIGHLY WEATHERED, DRY.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY ECHERLINE ANALYTICAL CORPORATION.
									5			BOTTOM OF HOLE AT 3.5 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.	
									10				
									15				
									20				
									25				
									30				
									35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SPL. SPOILS 57-DRILL. TAIL
D-DRILLER P-PISTON O-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-272R



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-130
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-273R

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 COORDINATES: N1100, E1400
 ANGLE FROM HORIZ.: 90°
 BEARINGS: N/A

DRILLER: MORETRENCH ENVIRONMENTAL SERVICES
 DRILL MAKE AND MODEL: MOBILE B-33
 HOLE SIZE: 6"
 OVERLAP (FT.): 0.3'
 RICK (FT.): 0.7'
 TOTAL DEPTH: 1.0'

DATE: 8/4/86
 COMPLETED: 8/4/86
 CORE RECOVERY (%): N/A
 CORE BOXES: N/A
 SAMPLES: N/A
 EL. TOP OF CASING: N/A
 GROUND EL.: 100.7'
 DEPTH/EL. GROUND WATER: NONE OBSERVED
 DEPTH/EL. TOP OF ROCK: 0.3' / 100.4'

SAMPLE NUMBER BEGIN/END: N/A
 CASING LEFT IN HOLE: DA/AL/STN: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH (FEET)	SAMPLE NUMBER	SAMPLE BEING PRESERVED FOR	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOG IN P.S.P.A.	PRESSURE P.S.I.	TIME IN MINUTES						
AUGER, 6", THROUGHOUT							100.7	0				
							99.7	LO				

0.0-0.3: ASPHALT.
 0.3-LO: DENSED SANDSTONE; DARK REDDISH BROWN GROSSLY TO FINE TO MEDIUM GRAINED (ARGILLACEOUS); SOFT TO MODERATELY HARD DRILL. SPOILS CONSIST OF SILTY SAND (SM) WITH NUMEROUS PIECES OF POORLY TO WELL CEMENTED SANDSTONE GRAVEL; TOTALLY DECOMPOSED TO HIGHLY WEATHERED; DRY.
 BOTTOM OF HOLE AT LO FT.
 AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.

AUGER REFUSAL AT LO FT.
 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES				14501-130		1 OF 1		NISS-274R	
MAYWOOD INTERIM STORAGE SITE - NJVIS				N1200, E1400				ANGLE FROM MERID.		90°		REARMS	
START		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		RICK (FT.)	
8/4/86		8/4/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		0.0'	
CORE RECOVERY (FT./%)		CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF RICK	
N/A		N/A		N/A		N/A		100.0'		NONE OBSERVED		N/A	
SAMPLE BARRED DOWN/FALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLER APPLIED LENGTH CORRECTION	SAMPLE RECOVERY CORRECTION	SAMPLE LENGTH BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
				LOSS IN P.S.I.	PRESSURE P.S.I.	TIME IN MINUTES							
AUGER 6" THROUGHOUT.							100.0	0					
							99.7			0.0-0.3: ASPHALT. 0.3-5.0: SILTY SAND (S&G) DARK REDDISH BROWN (G&G); FINE TO MEDIUM GRAINED; SOFT; WITH NUMEROUS PIECES OF MODERATELY HARD, POORLY TO WELL CEMENTED SANDSTONE GRAVEL; POORLY CONSOLIDATED (LOOSE); DRY; DECOMPOSED SANDSTONE.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION, AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.		
							95.0	5			BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.		
								10					
								15					
								20					
								25					
								30					
								35					

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
SIT MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP		14501-130	1 OF 1	NISS-275R				
COORDINATES				N1300.E1400		ANGLE FROM N090		BEARING				
						90°		N/A				
DRILLER	COMPLETED	DRILLER		DRILL NAME AND SERIAL		HOLE SIZE	OVERLAP (FT.)	ROCK FT.				
B/4/86	B/4/86	MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"	5.0'	TOTAL DEPTH				
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	REL. TOP OF CASING	GROUND EL.	DEPTH/REL. GROUND WATER		DEPTH/REL. TOP OF ROCK				
N/A		N/A	N/A	N/A	99.1'	NONE OBSERVED		N/A				
SAMPLE NUMBER DEPTH/FALL		CASING LEFT IN HOLE DIA./DEPTH			LOGGED BY							
N/A		N/A			D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH CORE RUN	SAMPLE INTERVAL CORE RECOVERY	SAMPLE NO. OR PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN P. S.P.A.	PRESSURE P.S.J.	TIME IN MINUTES						
AUGER, 6" THROUGHOUT.							99.1	0			0.0-0.2: ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
							98.9				0.3-5.0: SILTY SAND (SM-SC) COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED (FEW FINES); SOFT; POORLY CONSOLIDATED (LOOSE) MOIST.	
							94.1	5			0.3-2.0: MODERATE BROWN (SYR3/4). 2.0-5.0: DARK YELLOWISH ORANGE (OY16/6).	
											BOTTOM OF HOLE AT 5.0 FT.	
											AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.	
								10				
								15				
								20				
								25				
								30				
								35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.


* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SPLIT SPOILS ST-ORLEY TUBE, P-ORLEANS P-PTCHER 0-0718

OFFICE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-275R



GEOLOGIC DRILL LOG					PROJECT		JOB NO.	SHEET NO.	HOLE NO.			
MAYWOOD INTERIM STORAGE SITE - NJVIS					FUSRAP		14501-130	1 OF 1	NISS-270R			
SITE COORDINATES			N1200, E1300			ANGLE FROM MERID.		BEARING				
						90°		N/A				
START	COMPLETED	BILLER	BILL MAKE AND MODEL	HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH					
8/4/86	8/4/86	MORETRENCH ENVIRONMENTAL SERVICES	MOBILE B-33	6"	10.0'	0.0'	10.0'					
CORE RECOVERED (FT./%)	CORE DIAMETER	SAMPLES	REL. TOP OF CORES	GROUND EL.	DEPTH/EL. GROUND WATER	DEPTH/REL. TOP OF ROCK						
N/A	N/A	N/A	N/A	99.5'	7.0'/92.5'	N/A						
SAMPLE BARREL WEIGHT/FALL		CORES LEFT IN HOLE; DIA./LENGTH			LOGGED BY:							
N/A		N/A			D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLE ADVANCE LENGTH CORRECTION	SAMPLE RECOVERY CORRECTION	SAMPLE LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS		ELEVATION	DEPTH	GRAB LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS IN P.S./A.	PRESSURE P.S./J.						
AUGER, 6", THROUGHOUT.							99.5	0			0.0-10.0': SILTY SAND (S&S) COLOR STRATIFIED SOIL HORIZONS; FINE TO COARSE GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; SLIGHTLY MOIST TO SATURATED AT 7.0 FT. 0.0-3.0': MODERATE BROWN (5YR3/4) VERY SILTY; FINE GRAINED. 3.0-6.0': DARK YELLOWISH ORANGE (6YR6/6) FINE TO MEDIUM GRAINED. 6.0-10.0': DARK YELLOWISH BROWN (6YR4/2) FINE TO COARSE GRAINED.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION, AND HOLE GAMMA LOGGED, BY EBERLINE ANALYTICAL CORPORATION.  8/4/86
							89.5	10				
								15			BOTTOM OF HOLE AT 10.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.	ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.
								20				
								25				
								30				
								35				
<small>30-3/4" SPIRAL ST-DRIFT TUB; P-DRIFT; P-PTCH; 0-OTHER</small>					<small>NOTE</small> MAYWOOD INTERIM STORAGE SITE - NJVIS					<small>HOLE NO.</small> NISS-270R		



GEOLOGIC DRILL LOG										PROJECT		JOB NO.	SHEET NO.	HOLE NO.
SITE MAYWOOD INTERIM STORAGE SITE - NJVIS										COORDINATES			MOBILE FROM HORIZ.	BEARING
										N1100, E1300			90°	N/A
BEGIN		COMPLETED		DRILLER			DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH		
8/4/86		8/4/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33		6"	5.0'	0.0'	5.0'		
CORE RECOVERY(FT./%)		CORE DIAM.		SAMPLES	REL. TOP OF CASING		GROUND EL.	DEPTH/REL. GROUND WATER			DEPTH/REL. TOP OF ROCK			
N/A		N/A		N/A	N/A		99.5'	NONE OBSERVED			N/A			
SAMPLE NUMBER HEIGHT/FALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:						
N/A				N/A				D. McGRANE						
SAMPLE TYPE AND DIAMETER	SAMPLES OBTAINED - LOGGING CODE LIST	SAMPLES RECOVERED - LOGGING CODE	SAMPLE DIAM.	PERCENT CORE RECOVERY	WATER PRESSURE TESTS		ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.		
					LOG IN P.S.I.	TIME IN MINUTES								
ALGER, 6" THROUGHOUT.							99.5	0						
							99.2				0.0-0.3' ASPHALT. 0.3-5.0' SILTY SAND (SAND DARK REDDISH BROWN) 3/4" FINE TO MEDIUM GRAINED, SOFT WITH NUMEROUS PIECES OF MODERATELY HARD, POORLY TO WELL CEMENTED SANDSTONE GRAVEL POORLY CONSOLIDATED (LOOSE), DRY, DECOMPOSED SANDSTONE?	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.		
							94.5	5			BOTTOM OF HOLE AT 5.0 FT. ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.			
								10						
								15						
								20						
								25						
								30						
								35						

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SP.LT. SPONS. ST-DRILL. TAGS, 0-DRILLING P-PIECES, 0-OTHER

SITE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-277R



GEOLOGIC DRILL LOG

PROJECT: **FUSRAP** JOB NO.: **14501-130** SHEET NO.: **1 OF 1** HOLE NO.: **NISS-270R**

SITE: **MAYWOOD INTERIM STORAGE SITE - NJVIS** COORDINATES: **N1000, E1300** ANGLE FROM HORIZ.: **90°** BEARING: **N/A**

DATE: **8/4/86** COMPLETED: **8/4/86** DRILLER: **MORETRENCH ENVIRONMENTAL SERVICES** DRILL MAKE AND MODEL: **MOBILE B-33** HOLE SIZE: **6"** OVERLAP (FT.): **5.0'** RICK (FT.): **0.0'** TOTAL DEPTH: **5.0'**

CORE RECOVERY (%): **N/A** CORE BOXES: **N/A** SAMPLES: **N/A** EL. TOP OF CASING: **N/A** GROUND EL.: **99.4'** DEPTH/EL. GROUND WATER: **NONE OBSERVED** DEPTH/EL. TOP OF RICK: **N/A**

SAMPLE NUMBER DEPTH/FT. ALL: **N/A** CASING LEFT IN HOLE: DIA./LENGTH: **N/A** LOGGED BY: **D. McGRANE**

SAMPLE TYPE AND DIAMETER	SAMPLER APPLIED LEAST CORRECTION	SAMPLER RECOVERY CORRECTION	SAMPLER BLEND	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPE LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS	IN	IN						
FT.	IN	IN	IN	IN	IN	IN	IN	IN	IN	IN	IN	IN	IN
ALGER, 6" THROUGHOUT.							99.4	0			0.0-0.3' ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.	
							94.4	5			0.3-5.0' SILTY SAND (SAND DARK REDDISH BROWN 0.03/0.4 FINE TO MEDIUM GRAINED, SOFT WITH NUMEROUS PIECES OF MODERATELY HARD, POORLY TO WELL CEMENTED SANDSTONE GRAVEL; POORLY CONSOLIDATED (LOOSE); DRY; DECOMPOSED SANDSTONE?).		
											BOTTOM OF HOLE AT 5.0 FT.	ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.	
											ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		

NO-SPLIT SPINDLE STABILIZER TUBES; 1" DIAMETER; 10' LENGTH; 0.5" OFFSET. HOLE NO.: **NISS-270R**



GEOLOGIC DRILL LOG


PROJECT: FUSRAP
 JOB NO.: 14501-130
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-279R

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 COORDINATES: N900, E1300
 AZIMUTH FROM HOLE: 90°
 BEARING: N/A

DATE: 8/4/86
 COMPLETED: 8/4/86
 DRILLER: MORETRENCH ENVIRONMENTAL SERVICES
 DRILL MAKE AND MODEL: MOBILE B-33
 HOLE SIZE: 6"
 OVERBURDEN (FT.): 10.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 10.0'

CORE RECOVERY (FT./%)
 N/A
 CORE DIAMETER: N/A
 SAMPLES: N/A
 EL. TOP OF CASING: N/A
 GROUND EL.: 98.2'
 DEPTH/EL. GROUND WATER: 7.0'/91.2'
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE BARREL HEIGHT/FULL: N/A
 CASING LEFT IN HOLE: DIA./DEPTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH	SAMPLE RECOVERY	SAMPLE LOSS	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRANIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOW	IN	PERCENTAGE						
AUGER, 6" THROUGHOUT							98.2	0			0.0-0.3: ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.  8/4/86
							97.9	5			0.3-10.0: SILTY SAND (SH-SCH) COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT WITH OCCASIONAL PIECES OF MODERATELY HARD SANDSTONE GRAVEL (2.5-10.0 FT); POORLY CONSOLIDATED (LOOSE); FEW ORGANICS; MOST TO SATURATED AT 7.0 FT. 2.5-6.0: DARK YELLOWISH BROWN (MTR4/2); CLAY BINDER (SL). 6.0-6.5: GRAYISH BLACK (MTR); ORGANIC LAYER. 6.5-10.0: DARK REDDISH BROWN (MTR3/4); VERY SILTY; DECOMPOSED SANDSTONE.	
							88.2	10			BOTTOM OF HOLE AT 10.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.	
								15				ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM. * DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
								20				
								25				
								30				
								35				

LEGEND: S-SPLIT SPOILS; ST-STRENGTH TESTS; D-DRILLING; P-PITCHER; O-OTHER
 SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS
 HOLE NO.: MISS-279R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.		SHEET NO.		HOLE NO.					
MAYWOOD INTERIM STORAGE SITE - NJVIS				FLURAP				14501-130		1 OF 1		NJSS-200R			
COORDINATES				N1220, E1270				ANGLE FROM HORIZ.		BEARING					
N1220, E1270				90°				N/A							
DATE		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)		TOTAL DEPTH	
8/5/86		8/5/86		MORE TRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		0.0'		5.0'	
CORE RECOVERY (%)		CORE BOXES		SAMPLES		REL. TOP OF CORE		CORING DL.		DEPT./REL. OPENED WATER		DEPTH/REL. TOP OF ROCK			
N/A		N/A		N/A		N/A		99.5'		NONE OBSERVED		N/A			
SAMPLE NUMBER		WEIGHT/FALL		CORES LEFT IN HOLE		DRILLER		LABORER							
N/A		N/A		N/A		D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH (CORE LOG)	SAMPLE INTERVAL	SAMPLE NO.	SAMPLE NO. BY	WATER PRESSURE TESTS			ELEVATION	DEPTH	CORING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.		
					LOSS IN P.S.I.	PRESSURE IN P.S.I.	TIME IN MINUTES								
AUGER, 6" THROUGHOUT								99.5	0				SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.		
								94.5	5		0.0-5.0': SILTY SAND (S&S) CLAY STRATIFIED SOIL HORIZONS FINE TO MEDIUM GRAINED WITH OCCASIONAL PIECES OF REDDISH BROWN (GYR4/2) SANDSTONE GRAVEL AND PEBBLES AT VARIOUS LITHOLOGES; SOFT; POORLY CONSOLIDATED (LOOSE); MOIST. 0.0-1.0': MODERATE BROWN (GYR3/4) NUMEROUS GRASS ROOTS AND ORGANICS. 1.0-4.0': DARK YELLOWISH ORANGE (GYR6/6). BOTTOM OF HOLE AT 5.0 FT.				
									10				ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.		
									15						
									20						
									25						
									30				* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CLIPPINGS.		
									35						



GEOLOGIC DRILL LOG				PROJECT	JOB NO.	SHEET NO.	HOLE NO.								
				FUSRAP	14501-138	1 OF 1	NISS-201R								
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS			COORDINATES: N1100, E1200			ANGLE FROM HORIZ: 90°		SEASONS: N/A							
START: 8/5/86	COMPLETED: 8/5/86	DRILLER: MORE TRENCH ENVIRONMENTAL SERVICES		DRILL MAKE AND MODEL: MOBILE B-33	HOLE SIZE: 6"	OVERBURDEN (FT.): 1.0'	DRILL (FT.): 5.0'	TOTAL DEPTH: 6.0'							
CORE RECOVERY (FT./D): N/A		CORE BOXES: N/A	SAMPLES: N/A	EL. TOP OF CASING: N/A	GROUND EL.: 99.5'	DEPTH/EL. GROUND WATER: NONE OBSERVED		DEPTH/EL. TOP OF DRILL: 1.0'/98.5'							
SAMPLE NUMBER (DEPTH/FALL): N/A		CASING LEFT IN HOLE, DIA./LENGTH: N/A			LOGGED BY: D. McGRANE										
SAMPLE TYPE AND DIAMETER	SAMPLE INTERVAL - LEADIN CORE TUB	SAMPLE INTERVAL - CORE TUB	SAMPLE NUMBER	PERCENT CORE RECOVERY	WATER PRESSURE TESTS				ELEVATION	DEPTH	GRAPING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETENTION CHARACTER OF DRILLING, ETC.	
					LOSS IN P. (P.A.)	TEMPERATURE (P.S.I.)	TIME IN MINUTES								
AUGER, 6", THROUGHOUT.									99.5	0					
									98.5				0-6.0' SILTY SAND (S&M) MODERATE BROWN (SILTY) FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION, AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.	
								93.5	5			6.0	6.0-6.1' DECOMPOSED SANDSTONE; DARK REDDISH BROWN (S&M) FINE TO MEDIUM GRAINED; ARGILLACEOUS; SOFT TO MODERATELY HARD; DRILL SPOILS CONSIST OF SILTY SAND (S&M) WITH NUMEROUS PIECES OF POORLY TO WELL CEMENTED SANDSTONE GRAVEL; TOTALLY DECOMPOSED.		AUGER REFUSAL AT 6.0 FT.
										10					
										15					
										20					
										25					
										30					
										35					
60-SPLIT SPOILS ST-SHEDDY TAIL; DISCONTINUED P-PRECORD OTHER				CORE				MAYWOOD INTERIM STORAGE SITE - NJVIS				HOLE NO. NISS-201R			



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.			
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES			14501-130		1 OF 1		NISS-202R			
				N1000, E1200			ANGLE FROM HORIZ.		90°		BEARING			
DATE		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)		
8/5/86		8/5/86		MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33		6"		5.0'		0.0'		
CORE RECOVERY (FT./%)			CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER			
N/A			N/A		N/A		N/A		99.6'		NONE OBSERVED			
SAMPLE NUMBER HEIGHT/FALL				CASING LEFT IN HOLE/DL/LENGTH				LOGGED BY						
N/A				N/A				D. McGRANE						
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH CORE FEET	SAMPLE RECOVERY CORE RECOVERY	SAMPLE ID NOS.	PERCENT CORE RECOVERY	WATER PRESSURE TESTS				ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS	IN	PSI	IN						
AUGER, 6" THROUGHOUT.									99.6	0			0.0-0.5: ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EVERLINE ANALYTICAL CORPORATION.
									94.6	5			0.5-5.0: SILTY SAND (S.M. DARK REDDISH BROWN COBS/0. FINE TO MEDIUM GRAINED, SOFT WITH NUMEROUS PIECES OF MODERATELY HARD, WELL CEMENTED SANDSTONE GRAVEL, POORLY CONSOLIDATED (CLOSELY MOIST; DECOMPOSED SANDSTONE?).	
													BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.	
										10				
										15				
										20				
										25				
										30				
										35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

30-SPLIT SPINDLE STABILIZER TUBE; 0-2000-RPM; 1-1/2" DIA. 0-10" DIA.

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-202R



GEOLOGIC DRILL LOG				PROJECT			JOB NO.	SHEET NO.	HOLE NO.				
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES			MOBILE FROM HOLE	BEARDS					
				NO40,E1215			90°	N/A					
BEGIN	COMPLETED	DRILLER		DRILL NAME AND MODEL		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH				
8/5/86	8/5/86	MORETRENCH ENVIRONMENTAL SERVICES		MOBILE 8-33		6"	5.0'	0.0'	5.0'				
CORE RECOVERY (FT./3)		CORE BOXES	SAMPLES	REL. TOP OF CORE	GROUND EL.	DEPT./REL. OPENED WATER		DEPT./REL. TOP OF ROCK					
N/A		N/A	N/A	N/A	98.7'	NONE OBSERVED		N/A					
SAMPLE NUMBER BEING/FALL			CORES LEFT IN HOLE: DIA./LENGTH			LOGGED BY:							
N/A			N/A			D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLE ADVANCE LENGTH (CORRECTION)	SAMPLE INTERVAL (CORRECTION)	SAMPLE BEARS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER METHOD, CHARACTER OF DRILLING, ETC.
					LOGS	IN	PSI						
AUGER, 6", THROUGHOUT.								98.7	0			0.0-1.5'; SANDY SILT (S); MODERATE BROWN (5YR5/4) FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); NUMEROUS GRASS ROOTS AND ORGANICS; MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
							93.7	5			1.5-5.0'; SILTY SAND (SM); DARK REDDISH BROWN (6R3/4) FINE TO MEDIUM GRAINED; SOFT WITH NUMEROUS PIECES OF MODERATELY HARD, WELL CEMENTED SANDSTONE GRAVEL; POORLY CONSOLIDATED, BUT NEAR REFUSAL; MOIST; DECOMPOSED SANDSTONE? BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE.		
									10				
									15				
									20				
									25				
									30				
									35				

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

35-SAMPLE SPOILS ST-CORRECTION TABLE
35-SAMPLE SPOILS ST-CORRECTION TABLE

SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. MISS-283R



GEOLOGIC DRILL LOG				PROJECT				JOB NO.		SHEET NO.		HOLE NO.				
MAYWOOD INTERIM STORAGE SITE - NJVIS				FUSRAP				14501-130		1 OF 1		NISS-284R				
COORDINATES				N900, E1100				ANGLE FROM HORIZ.		BEARING		N/A				
DATE		COMPLETED		DRILLER			DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH	
8/5/86		8/5/86		MORETRENCH ENVIRONMENTAL SERVICES			MOBILE B-33		6"		5.0'		0.0'		5.0'	
CORE RECOVERY (%)			CORE DIAMETER		SAMPLES		EL. TOP OF CORES		CORRECTED EL.		DEPTH/EL. GROUND WATER			DEPTH/EL. TOP OF ROCK		
N/A			N/A		N/A		N/A		99.0'		NONE OBSERVED			N/A		
SAMPLE NUMBER WEIGHT/FALL				CORES LEFT IN HOLE/DISPOSITION				LOGGED BY:								
N/A				N/A				D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH (FEET)	SAMPLE RECOVERY (%)	SAMPLE WEIGHT (LBS)	WATER PRESSURE TESTS			ELEVATION	DEPTH	CORRECTED LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.				
				LOGS	P.S.P.A.	TIME IN MINUTES										
AUGER, 6" THROUGHOUT.							99.0	0								
							98.7			0.0-0.3' ASPHALT.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.					
							94.0	5		0.3-5.0' SILTY SAND (S&S) COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED WITH NUMEROUS PIECES OF MODERATELY HARD, WELL CEMENTED SANDSTONE GRAVEL; POORLY CONSOLIDATED (LOOSE); DRY TO MOIST. 0.3-2.5' DARK YELLOWISH BROWN (OYR4/2); DRY. 2.5-5.0' DARK REDDISH BROWN (ORF3/4); MOIST; DECOMPOSED SANDSTONE. BOTTOM OF HOLE AT 5.0 FT. AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.						
								10								
								15								
								20								
								25								
								30								
								35								

ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.

DE-SPLE SPIND ST-DRILLY TOOL; 1-DRILLING P-PT-CORR; 0-0718

DATE MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO. NISS-284R



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
SITE: MAYWOOD INTERIM STORAGE SITE - NJVIS				COORDINATES		14501-130	1 OF 1	NISS-205R					
				N1000, E1100		ANGLE FROM HORIZ	90°	REMARKS					
DRILLER	COMPLETED	DRILLER		DRILL NAME AND MODEL	HOLE SIZE	OVERBURDEN (FT.)	BACK (FT.)	TOTAL DEPTH					
8/5/86	8/5/86	MORETRENCH ENVIRONMENTAL SERVICES		MOBILE B-33	8"	5.0'	0.0'	5.0'					
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP OF CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK					
N/A		N/A	N/A	N/A	99.6'	NONE OBSERVED		N/A					
SAMPLE NUMBER BEHIND/PAI		CASING LEFT IN HOLE: DIA./LENGTH		LOGGED BY:									
N/A		N/A		D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE NUMBER BEHIND/PAI	SAMPLE NUMBER CORE RECOVERY	SAMPLE WEIGHT	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS IN P.S.J.A.	PRESSURE P.S.J.	TIME IN MINUTES						
ALGER, 6", THROUGHOUT.								99.6	0				
								99.3				0.0-0.3': ASPHALT. 0.3-5.0': SILTY SAND (SAND COLOR STRATIFIED SOIL HORIZONS; FINE TO MEDIUM GRAINED; SOFT; POORLY CONSOLIDATED (LOOSE); MOIST. 0.3-1.0': MODERATE BROWN (SYRS/4L 1.0-5.0': DARK REDDISH BROWN (BORS/4L) CONTAINS NUMEROUS PIECES OF SANDSTONE GRAVEL.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EVERLINE ANALYTICAL CORPORATION.
								94.6	5			BOTTOM OF HOLE AT 5.0 FT. ALGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE AND THE HOLE WAS RESEALED WITH ASPHALT.	
									10				
									15				
									20				
									25				
									30				
									35				
* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.										ELEVATIONS ESTABLISHED RELATIVE TO AN ARBITRARY DATUM.			

SO-SPILE SPONS; ST-SHED BY TUBS; P-DRILLING; P-PATCHES; O-OTHER

DATE

MAYWOOD INTERIM STORAGE SITE - NJVIS

HOLE NO.

NISS-205R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
MISS - N.J. INSPECTION STATION										FUSRAP		14501-130	1 OF 1	MISS-624R				
COORDINATES										N1892, E1396		ANGLE FROM MERID.		BEARING				
DRILLER										DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH			
2/24/87										2/24/87		MORETRENCH ENV. SERV.		CHE-55	6"	10.0'	0.0'	10.0'
CORE RECOVERY FT./%		CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL. ⁰⁰		DEPTH/VEL. GROUND WATER ⁰⁰		DEPTH/VEL. TOP OF ROCK						
N/A		N/A		N/A		N/A				5.0' /		N/A						
SAMPLE NUMBER HEIGHT/FALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:										
N/A				N/A				D. MCGRANE										
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE FEET	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAIN LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLER, ETC.						
				LOG FT. IN	P. S.P.A.L.	TIME IN MINUTES												
6" AUGER								0			0.0-0.3: ASPHALT.	2/24/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.						
								5			0.3-1.0: GRAVEL; 1.0-2.0: 1.0-10.0: SILTY SAND (SMB. FILL AND INDIGENOUS MATERIAL (2.0-10.0), COLOR STRATIFIED; FINE TO MEDIUM GRAINED WITH FEW TO NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST TO SATURATED AT 5.0'. 1.0-2.0: MODERATE BROWN; FEW ORGANICS; FILL? 2.0-10.0: DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.							
								10			BOTTOM OF HOLE AT 10.0 FT.	⁰⁰ DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. ⁰⁰ NOT AVAILABLE.						
								15			AUGER SPOILS WERE IMMEDIATELY REPLACED IN THE HOLE, 2/24/87.							
								20										
								25										
								30										
								35										

SE-SPLIT SPOILS; ST-STEEL TUBE; P-PITCHER; O-OTHER


SITE

MISS - N.J. INSPECTION STATION

HOLE NO.

MISS-624R



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
MISS - N.J. INSPECTION STATION				FUSRAP			14501-130		1 OF 1		MISS-625R		
SITE				COORDINATES				AZIMUTH FROM HORIZ.		BEARING			
MISS - N.J. INSPECTION STATION				N1890, E1307				90°		N/A			
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)	TOTAL DEPTH
2/24/87		2/24/87		MORETRENCH ENV. SERV.		CME-55		6"		10.0'		0.0'	10.0'
CORE RECOVERY (FT./3)			CORE BOXES		SAMPLES	EL. TOP OF CASING		GROUND EL. ⁰⁰		DEPTH/VEL. GROUND WATER ⁰⁰		DEPTH/VEL. TOP OF ROCK	
N/A			N/A		N/A	N/A		N/A		5.0' /		N/A	
SAMPLE NUMBER BEG/END/FALL				CASING LEFT IN HOLE DIA./LENGTH				LOGGED BY:					
N/A				N/A				D. MCGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLE INTERVAL CORE RECOVERY	SAMPLE LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS IN	P.S.P.A.L.	TIME IN MINUTES						
6" AUGER.									0			0.0-10.0': SILTY SAND (SMB. FILL AND INDIGENOUS MATERIAL (2.0-10.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED AT 5.0'. 0.0-2.0': MODERATE BROWN (SYR3/4); NUMEROUS GRASS ROOTS (0.0-0.5') AND ORGANICS; DISTURBED UPPER SOIL HORIZON? 2.0-10.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.	2/24/87  SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
									5				
									10			BOTTOM OF HOLE AT 10.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS, 2/24/87.	DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS. ⁰⁰ NOT AVAILABLE.
									15				
									20				
									25				
									30				
									35				

SS-SPLIT SPOON ST-STEELY TUBE; D-DIAMETER; P-PISTON; O-OTHER

SITE

MISS - N.J. INSPECTION STATION

HOLE NO.

MISS-625R



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-138
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-626R

SITE: MISS - M.J. INSPECTION STATION
 COORDINATES: N1935, E1475
 ANGLE FROM HORIZ.: 90°
 BEARING: N/A

DRIVEN: 2/24/87
 COMPLETED: 2/24/87
 DRILLER: MORETRENCH ENV. SERV.
 DRILL MAKE AND MODEL: CME-55
 HOLE SIZE: 6"
 OVERLAP (FT.): 9.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 9.0'


CORE RECOVERY (FT./TD): N/A
 CORE BOXES: N/A
 SAMPLES: N/A
 SL. TOP OF CORE: N/A
 GROUND EL.⁰⁰:
 DEPTH/VEL. GROUND WATER⁰⁰: 5.0' /
 DEPTH/VEL. TOP OF ROCK: N/A

SAMPLE BARREL RETURN/FALL: N/A
 CORES LEFT IN HOLE: 0/1/0/0/0/0
 LOGGED BY: D. McGRANE


SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH	SAMPLE DEPTH	SAMPLE BEING RECOVERED	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPE LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG IN P.S.P.A.	PRESSURE P.S.I.	TIME IN MINUTES						
6" AUGER									0			0.0-9.0': SILTY SAND (SIL. FILL AND INDIGENOUS MATERIAL (2.0-9.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-011); MOIST - SATURATED AT 5.0'. 0.0-2.0': MODERATE BROWN (SYR3/4); FEW ORGANICS; FILL OR DISTURBED UPPER SOIL HORIZON? 2.0-9.0': DARK YELLOWISH BROWN (00YR4/2); DECOMPOSED SANDSTONE.	2/24/87
									10			BOTTOM OF HOLE AT 9.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS, 2/24/87.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
									15				
									20				
									25				
									30				
									35				

00-SPLIT SPOILS; ST-SHEDDY TAIL; P-SPILL; P-PEPPER; O-OTHER
 SITE: MISS - M.J. INSPECTION STATION
 HOLE NO.: MISS-626R




GEOLOGIC DRILL LOG				PROJECT			JOB NO.	SHEET NO.	HOLE NO.			
MISS - N.J. INSPECTION STATION				FUSRAP			14501-130	1 OF 1	MISS-627R			
SITE				COORDINATES			ANGLE FROM HORIZ.		BEARING			
MISS - N.J. INSPECTION STATION				N1640, E1400			90°		N/A			
BEGIN	COMPLETED	DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH			
2/25/87	2/25/87	MORETRENCH ENV. SERV.		CME-55		6"	4.5'	N/A	4.5'			
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP OF CASING	GROUND E.L. ⁰	DEPTH/EL. GROUND WATER ⁰		DEPTH/EL. TOP OF ROCK				
N/A		N/A	N/A	N/A	N/A	3.0' /		N/A				
SAMPLE NUMBER BEHIND/FILL			CASING LEFT IN HOLE DIA./DEPTH			LOGGED BY						
N/A			N/A			D. McGRANE						
SAMPLE TYPE AND DIAMETER	SAMPLE INTERVAL - LENGTH CORE TUBE	SAMPLE INTERVAL - CORE NUMBER	SAMPLE NO. OR PRESENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰	DEPTH	GRAPHIC LOG	SAMPLES	DESCRIPTION AND CLASSIFICATION ⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				ELONG IN IN	P.P.A.	PRELIMINARY P.P.L.						
6" AUGER								0			0.0-4.5': SILTY SAND (SIL. FILL AND INDIGENOUS MATERIAL 0.5-4.5%. COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED AT 3.0'. 0.0-0.5': BLACK; NUMEROUS GRASS ROOTS AND ORGANICS. 0.5-1.5': MODERATE BROWN (GYR3/4); FEW ORGANICS; DISTURBED SOIL HORIZON? 1.5-4.5': DARK YELLOWISH BROWN (GYR4/2); DECOMPOSED SANDSTONE.	 2/25/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
								4.5			BOTTOM OF HOLE AT 4.5 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS, 2/25/87.	
								5				
								10				
								15				
								20				
								25				
								30				
								35				



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
MISS - N.J. INSPECTION STATION				FUSRAP			14501-130		1 OF 1		MISS-620R		
SITE				COORDINATES				AZIMUTH FROM HORIZ.		DIP/SLUR			
MISS - N.J. INSPECTION STATION				N1730, E1400				90°		N/A			
BEGUN		COMPLETED		DRILLED BY		DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)	TOTAL DEPTH
2/25/87		2/25/87		MCRETRENCH ENV. SERV.		CME-55		6"		5.0'		0.0'	5.0'
CORE RECOVERY (%)			CORE BOXES		SAMPLES		BL. TOP OF CASING		GROUND ELF ⁰⁰		DEPTH/VEL. GROUND WATER ⁰⁰		DEPTH/VEL. TOP OF ROCK
N/A			N/A		N/A		N/A		4.0' /		N/A		
SAMPLE NUMBER HEIGHT/FALL				CASING LEFT IN HOLE; DIA./LENGTH				LOGGED BY					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH (FEET)	SAMPLE INTERVAL (FEET)	SAMPLE NUMBER	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	BRINE LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG IN FT. IN P. G.P.A.	W. PRESSURE IN P.S.I.	TIME IN P. MINUTES						
6' AUGER									0				
									5			0.0-5.0': SILTY SAND (SM. FILL AND INDIGENOUS MATERIAL 0.5-5.0% COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED.	 2/25/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERTLINE ANALYTICAL CORPORATION.
									10			0.0-1.5': MODERATE BROWN (S1YR3/4); MOTTLED GRAYISH BLACK (R2); NUMEROUS GRASS ROOTS (0.0-0.5') AND ORGANICS; MIXED FILL AND STREAM SEDIMENTS.	
									15			1.5-5.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.	
									20			BOTTOM OF HOLE AT 5.0 FT.	
									25			HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT, 2/25/87.	
									30				
									35				
⁰⁰ SAMPLE SPONSOR: ST-ORNLBY TAIL; D-CORPOR; P-PTCHER; O-OTHER				SITE				MISS - N.J. INSPECTION STATION					HOLE NO.
													MISS-620R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.			
SITE MISS - N.J. INSPECTION STATION										COORDINATES N1763, E1395				14501-138		1 OF 1		MISS-629R	
BEGIN 2/25/87		COMPLETED 2/25/87		DRILLER MCRETRENCH ENV. SERV.			DRILL MAKE AND MODEL CME-55		HOLE SIZE 6"	OVERBURDEN (FT.) 7.0'		ROCK (FT.) 0.0'		TOTAL DEPTH 7.0'					
CORE RECOVERY(FT./%) N/A		CORE BOXES N/A		SAMPLES N/A		REL. TOP OF CASING N/A		GROUND W.L. ⁰⁰		DEPT./REL. GROUND WATER ⁰⁰ 4.0' /		DEPTH/REL. TOP OF ROCK N/A							
SAMPLE NUMBER HEIGHT/FALL N/A				CASING LEFT IN HOLE DIA./LENGTH N/A				LOGGED BY D. McGRANE											
SAMPLE TYPE AND DIAMETER	SAMPLE INTERVAL - LENGTH CORE RUN	SAMPLE INTERVAL - CORE NUMBER	SAMPLE IN CORE	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CONDUCTOR OF DRILLING, ETC.						
					LOG	IN	IN												
					FT. IN	PSI	PSI												
6" AUGER									0			0.0-7.0': SILTY SAND (SN) FILL AND INDIGENOUS MATERIAL (LS-7.0). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0M); MOIST - SATURATED AT 4.0 FT.	 2/25/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.						
									5			0.0-3.5': MODERATE BROWN (SYR3/4); MOTTLED GRAYISH BLACK (M2); NUMEROUS GRASS ROOTS AND ORGANICS; CLAYEY; MIXED FILL AND STREAM SEDIMENTS?							
									7.0			3.5-7.0': DARK YELLOWISH BROWN (OYB4/2); DECOMPOSED SANDSTONE.							
									10			BOTTOM OF HOLE AT 7.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT, 2/25/87.							
									15										
									20										
									25										
									30										
									35										



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE MISS - N.J. INSPECTION STATION										COORDINATES N1850, E1400				DRILL FROM HORIZ. 90°		READING N/A	
BEGIN 2/25/87		COMPLETED 2/25/87		DRIILLED MIDRETRENCH ENV. SERV.			DRILL NAME AND MODEL DCE-55			HOLE SIZE 6"	OVERBURDEN (FT.) 5.0'		ROCK (FT.) 0.0'	TOTAL DEPTH 5.0'			
CORE RECOVERY (FT./D) N/A			CORE DIAMETER N/A	SAMPLES N/A	EL. TOP OF CASING N/A		GROUND EL. ⁰		DEPTH/VEL. GROUND WATER ⁰ 5.0' /			DEPTH/VEL. TOP OF ROCK N/A					
SAMPLE NUMBER HEIGHT/FALL N/A				CASING LEFT BY HOLE DIA./LENGTH N/A				LOGGED BY D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE - LENGTH CORE RUN	SAMPLE INTERVAL - CORE NUMBER	SAMPLE BEING PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰	DEPTH	CASING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
				IN LONG IN P.S.P.A.	PRELIM P.F.J.	TIME IN MINUTES											
6" AUGER								0			0.0-5.0: SILTY SAND (S.M. FILL AND INDIGENOUS MATERIAL 10.5-5.0). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-CH); MOIST - SATURATED AT 5.0'. 0.0-0.5: MODERATE BROWN (SYR3/4); NUMEROUS GRASS ROOTS AND ORGANICS. 0.5-5.0: DARK YELLOWISH BROWN (OYB4/2); DECOMPOSED SANDSTONE. BOTTOM OF HOLE AT 5.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS, 2/25/87.						
								5				▽ 2/25/87					
								10				SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.					
								15									
								20									
								25									
								30									
								35									

⁰ DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
⁰⁰ NOT AVAILABLE

30-SPLOT SPOILS; ST-SHELF TAGS;
D-CORING; P-PICKER; O-OTHER

SITE
MISS - N.J. INSPECTION STATION

HOLE NO.
MISS-630R



GEOLOGIC DRILL LOG				PROJECT			JOB NO.	SHEET NO.	HOLE NO.						
MISS - N.J. INSPECTION STATION				FUSRAP			14501-138	1 OF 1	MISS-631R						
COORDINATES				N1775, E1300			ANGLE FROM MERID.		BEARING						
							90°		N/A						
DATE	COMPLETED	BILLER	DRILL NAME AND MODEL	HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH								
2/25/87	2/25/87	MORETRENCH ENVIRONMENTAL SERVICE	CHE-55	6"	5.0'	0.0'	5.0'								
CORE RECOVERY FT./%		CORE BOXES	SAMPLES	EL. TOP OF CASING	GROUND EL. ⁰⁰	DEPTH/EL. GROUND WATER ⁰⁰	DEPTH/EL. TOP OF ROCK								
N/A		N/A	N/A	N/A		4.0' /	N/A								
SAMPLE NUMBER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:									
N/A			N/A			D. McBRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH CORE (FT.)	SAMPLE INTERVAL CORE NUMBER	SAMPLE LENGTH	PERCENT CORE RECOVERY	WATER PRESSURE TESTS				ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF BILLER, ETC.	
					LOGS	TIME	IN	PER							
6" AUGER									0				0.0-5.0': SILTY SAND (SML. FILL AND INDIGENOUS MATERIAL 0.0-5.0% COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0%); MOIST - SATURATED AT 5.0'.	2/25/87	
									5			0.0-1.0': MODERATE BROWN (SYR 3/4) MOTTLED GRAYSH BLACK (0.2) NUMEROUS GRASS ROOTS AND ORGANICS; FILL AND STREAM SEDIMENT. 1.0-3.0': DARK REDDISH BROWN (00YR 4/2); DECOMPOSED SANDSTONE. 3.0-5.0': DARK YELLOWISH BROWN (00YR 4/2); DECOMPOSED SANDSTONE. BOTTOM OF HOLE AT 5.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/25/87.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.		
									10						
									15						
									20						
									25						
									30						
									35						
<small>SD-SPLIT SPONS; ST-SHIELD TUBE; D-DRILLING; P-PISTON; O-OTHER</small>				DATE					MISS - N.J. INSPECTION STATION			HOLE NO.			
												MISS-631R			



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.		
MISS - N.J. INSPECTION STATION				FUSRAP		14501-130	1 OF 1	MISS-632R		
DATE				COORDINATES			ANGLE FROM HORIZ.			
MISS - N.J. INSPECTION STATION				N1750,E1300			90°			
DESIGN	COMPLETED	DRIILLED	DRILL NAME AND MODEL		HOLE SIZE	OVERLASH (FT.)	ROCK (FT.)	TOTAL DEPTH		
2/25/87	2/25/87	MORETRENCH ENV. SERV.	CME-55		6"	7.0'	0.0'	7.0'		
CORE RECOVERY (FT./%)		CORE DIAM.	SAMPLES	EL. TOP OF CASING	GROUND EL. ⁰⁰	DEPTH/EL. GROUND WATER ⁰⁰	DEPTH/EL. TOP OF ROCK			
N/A		N/A	N/A	N/A		5.0' /	N/A			
SAMPLE NUMBER WEIGHT/FILL			CASING LEFT IN HOLE; DIA./LENGTH		LOGGED BY:					
N/A			N/A		D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE DIA.	SAMPLER RECOVERY CORE RECOVERY	SAMPLE COLOR	WATER PRESSURE TESTS	ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
6" AUGER						0 5 7 10 15 20 25 30 35			<p>0.0-7.0': SILTY SAND (SOIL FILL AND INDIGENOUS MATERIAL 0.0-7.0% COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (S.C. 0%); MOIST - SATURATED AT 5.0'. 0.0-1.0'; MODERATE BROWN (SYR3/4); NUMEROUS GRASS ROOTS AND ORGANICS. FILL?</p> <p>1.0-4.5'; MOTTLED MODERATE BROWN AND DARK REDDISH BROWN (OR3/4); DISTURBED UPPER SOIL HORIZON?</p> <p>4.5-7.0'; DARK YELLOWISH BROWN (OY1/4); DECOMPOSED SANDSTONE.</p> <p>BOTTOM OF HOLE AT 7.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS, 2/25/87.</p>	<p>2/25/87</p> <p>SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY ENERLINE ANALYTICAL CORPORATION.</p>
<p>⁰⁰ DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.</p> <p>⁰⁰ NOT AVAILABLE</p>										
<p>10-SPLIT SPOILS 51-DRILL BY TOOL, PREVIOUS PAPER OR OTHER</p>				<p>DATE</p>				<p>MISS - N.J. INSPECTION STATION</p>		<p>HOLE NO.</p> <p>MISS-632R</p>



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.						
SITE				COORDINATES		14501-130	1 OF 1	MISS-633R						
MISS - N.J. INSPECTION STATION				N1822,E1300		ANGLE FROM HORIZ.	90°	BEARING						
START	COMPLETED	DRILLER		DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN FT./J	ROCK FT./J						
2/25/87	2/25/87	MORETRENCH ENV. SERV.		CME-55		6"	7.0'	0.0'						
CORE RECOVERY % L/TD		CORE DIAMETER	SAMPLES	EL. TOP OF CASING	GROUND ELEV ⁰	DEPTH/EL. GROUND WATER ⁰⁰		DEPTH/EL. TOP OF ROCK						
N/A		N/A	N/A	N/A	N/A	5.0' /		N/A						
SAMPLE NUMBER BEGIN/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:								
N/A			N/A			D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE ORIENTATION	SAMPLE LENGTH	SAMPLE WEIGHT	SAMPLE BLINDS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF BELLW. ETC.
						LOGS	IN	MIN						
6" AUGER.										0			0.0-0.3': ASPHALT. 0.3-0.6': GRAVEL 2.0'. 0.6-7.0': SILTY SAND (SMD. FILL AND INDIGENOUS MATERIAL (3.5-7.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-018); MOIST - SATURATED AT 5.0'. 0.6-3.5': DARK YELLOWISH ORANGE (00YR6/6); FILL? 3.5-7.0': DARK YELLOWISH BROWN (00YR4/2); DECOMPOSED SANDSTONE. BOTTOM OF HOLE AT 7.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS, 2/25/87.	2/25/87
										5				
										7.0				
										10				
										15				
										20				
										25				
										30				
										35				

⁰ DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
⁰⁰ NOT AVAILABLE

30-SP/LT SPEED ST-REELAY TANK; OPERATING P-PITCHED COVER		SITE		MISS - N.J. INSPECTION STATION		HOLE NO.		MISS-633R
--	--	------	--	--------------------------------	--	----------	--	-----------




GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE MISS - N.J. INSPECTION STATION										COORDINATES N1776,E1283				HOLE FROM HORIZ. 90°		BEARING N/A	
STARTED 2/25/87		COMPLETED 2/25/87		DRILLER MIDRETRENCH ENV. SERV.			DRILL MAKE AND MODEL CME-55		HOLE SIZE 6"	OVERBURDEN (FT.) 14.0'		ROCK (FT.) 0.0'	TOTAL DEPTH 14.0'				
CORE RECOVERY (FT./TD) N/A			CORE BOXES N/A		SAMPLES N/A	EL. TOP OF CASING N/A		GROUND EL. 98	DEPTH/VEL. GROUND WATER 8.0' / 00			DEPTH/EL. TOP OF ROCK N/A					
SAMPLE NUMBER (HOLE/FT./ALL) N/A				CASING LEFT IN HOLE; DIA./LENGTH N/A				LOGGED BY: D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH (CORE DIA.)	SAMPLE DEPTH (CORE MIDDLE)	SAMPLE LENGTH PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
				LOSS IN P.S.I.	PERCENTAGE P.S.I.	TIME IN MINUTES											
6" AUGER								0			0.0-0.5': ASPHALT. 0.5-0.6': GRAVEL, 20%.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION. ▽ 2/25/87					
								5			0.6-14.0': SILTY SAND (S.M.) FILL AND INDIGENOUS MATERIAL (S.O-M.D.). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY 0.6-14.0': (S.C-OH); MOIST - SATURATED AT 8.0'. 0.6-5.0': DARK REDDISH BROWN (DR3/4); FILL. 5.0-14.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.						
								14.0									
								15			BOTTOM OF HOLE AT 14.0 FT.						
								20			HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS, 2/25/87.						
								25									
								30									
								35									
								36									

30-SPLIT SPOILS; ST-SHEDDY TAIL; D-BEARING; P-PITCHER; O-OTHER

SITE
MISS - N.J. INSPECTION STATION

HOLE NO.
MISS-634R




GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
SITE				COORDINATES			ANGLE FROM HORIZ.		BEARING				
MISS - N.J. INSPECTION STATION				N1749,E1192			90°		N/A				
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERBURDEN (FT.)		ROCK (FT.)	TOTAL DEPTH
2/25/87		2/25/87		MORRENTRENCH ENV. SERV.		CHE-55		6"		7.0'		0.0'	7.0'
CORE RECOVERY (FT./%)			CORE BOXES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK
N/A			N/A		N/A		N/A		98		4.0' / 98		N/A
SAMPLE NUMBER WEIGHT/FALL				CASING LEFT IN HOLE/DIA./LENGTH				LOGGED BY:					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS %	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
				LOGS	DEPTH	TIME							
6" AUGER.				LOGS	DEPTH	TIME		0					
								5			0.0-7.0': SILTY SAND (S.M. FILL AND INDIGENOUS MATERIAL (4.0-7.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-04); MOST - SATURATED AT 4.0'. 0.0-1.0': MODERATE BROWN (SYR3/4); MOTTLED GRAYISH BLACK (02); NUMEROUS GRASS ROOTS AND ORGANICS. 1.0-4.0': DARK REDDISH BROWN (00R3/4). FILL OR ALLUVIAL SOIL?	 2/25/87	
								7.0			BOTTOM OF HOLE AT 7.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/25/87.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.	
								10					
								15					
								20					
								25					
								30					
								35					
SE-SPLV SPEED ST-BELBY TUBE; D-DRILLING P-PISTON; O-OTHER				SITE				MISS - N.J. INSPECTION STATION				HOLE NO.	
												MISS-635R	




GEOLOGIC DRILL LOG				PROJECT			JOB NO.	SHEET NO.	HOLE NO.	
MISS - N.J. INSPECTION STATION				FUSRAP			14501-130	1 OF 1	MISS-636R	
COORDINATES				N1747,E1005			HOLE FROM HORIZ.		BEARING	
90°				N/A						
DATE	COMPLETED	DRIER	DRILL NAME AND NUMBER		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH		
2/26/87	2/26/87	MORETRENCH ENV. SERV.	CME-55		6"	8.0'	0.0'	8.0'		
CORE RECOVERY %		CORE BOXES	SAMPLES	REL. TOP OF CASING	GROUND EL.	DEPTH/REL. GROUND WATER		DEPTH/REL. TOP OF ROCK		
N/A		N/A	N/A	N/A	90	6.5' / 90		N/A		
SAMPLE NUMBER USED/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:				
N/A			N/A			D. McGRANE				
SAMPLE TYPE AND DIAMETER	SAMPLE LENGTH	SAMPLE WEIGHT	SAMPLE BLANK	WATER PRESSURE TESTS	NO. OF SAMPLES	DEPTH	CORRECTION LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
6" ALGER.						0			0.0-8.0': SILTY SAND (SM. FILL AND INDIGENOUS MATERIAL (4.0-8.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED AT 6.5'. 0.0-6.0': MODERATE BROWN (5YR3/4); MOTTLED GRAYISH BLACK (02); NUMEROUS GRASS ROOTS (0.0-0.5') AND ORGANICS; OCCASIONAL PIECE OF GLASS; NUMEROUS ROUNDED PEBBLES (5.5-6.0'); FILL AND STREAM SEDIMENT? 6.0-7.0': GRAY (08); SOIL? 7.0-8.0': DARK YELLOWISH BROWN (10YR4/2) DECOMPOSED SANDSTONE.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
						10			BOTTOM OF HOLE AT 8.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN ALGER SPOILS AND CEMENT GROUT MIXTURE, 2/26/87.	
						15				
						20				
						25				
						30				
						35				
<p>• DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.</p> <p>** NOT AVAILABLE.</p>										
<p>MISS - N.J. INSPECTION STATION</p>						<p>MISS-636R</p>				




GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
MISS - N.J. INSPECTION STATION				FUSRAP		14501-130	1 OF 1	MISS-637R					
COORDINATES				N1820,E1190		ANGLE FROM HORIZ.		BEARINGS					
						90°		N/A					
DATE	COMPLETED	DRIER	DRILL NAME AND MODEL	HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH						
2/26/87	2/26/87	MOIRE TRENCH ENV. SERV.	CME-55	6"	5.0'	0.0'	5.0'						
CORE RECOVERY (FT./30)		CORE BOXES	SAMPLES	EL. TOP OF CASING	GROUND EL.	DEPTH/EL. GROUND WATER	DEPTH/EL. TOP OF ROCK						
N/A		N/A	N/A	N/A	90	4.0' / 90	N/A						
SAMPLE NUMBER IDENT./ALL			CASING LEFT IN HOLE; DIA./LENGTH		LOGGED BY								
N/A			N/A		D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE GRAIN SIZE LENGTH CORE FEET	SAMPLE LOCATION CORE NUMBER	SAMPLE COLOR	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOG IN FT. IN P.S.I.	PRESSURE IN P.S.I.	TIME IN MINUTES						
6" AUGER.									5			<p>0.0-5.0': SILTY SAND (SML) FILL AND INDIGENOUS MATERIAL 0.5-5.0% COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED AT 4.0'. 0.0-0.5': GRAYISH BLACK (M2) STREAM SEDIMENT USED AS TOPSOIL? 0.5-1.5': DARK REDDISH BROWN (OR3/4); FILL. 1.5-5.0': DARK YELLOWISH BROWN (O0YR 4/2); DECOMPOSED SANDSTONE</p>	 2/26/87
									10			<p>BOTTOM OF HOLE AT 5.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/26/87.</p>	<p>SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.</p>
									15				
									20				
									25				
									30				
									35				
30-SPLIT SPINDLE; 57-DRILLER TYPE; 1-DRILLER; 1-DRILLER 0-0718				SITE				MISS - N.J. INSPECTION STATION		HOLE NO. MISS-637R			




GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
MISS - N.J. INSPECTION STATION				FLSRAP		14501-130	1 OF 1	MISS-630R				
SITE				COORDINATES			ANGLE FROM HORIZ.	BEARINGS				
MISS - N.J. INSPECTION STATION				N1810, E1106			90°	N/A				
BEGIN	COMPLETED	DRILLER		DRILL LOGS AND INSTR.		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH			
2/26/87	2/26/87	MORETRENCH ENV. SERV.		CME-55		6"	18.0'	0.0'	10.0'			
CORE RECOVERY (FT./%)		CORE DIAM.	SAMPLES	REL. TOP OF CASING	GROUND EL.	DEPTH/REL. GROUND WATER		DEPTH/REL. TOP OF ROCK				
N/A		N/A	N/A	N/A	90	5.0' / 90		N/A				
SAMPLE BARREL BEING/TALL			CASING LEFT IN HOLE DIA./LENGTH			LOGGED BY						
N/A			N/A			D. McGRANE						
SAMPLE TYPE AND DIAMETER	SAMPLE RECOVERY (PERCENT CORE)	SAMPLE RECOVERY (PERCENT CORE)	SAMPLE RECOVERY (PERCENT CORE)	WATER PRESSURE TESTS			ELEVATION ⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOGS IN FT. G.P.A.	PRESSURE IN P.S.I.	TIME IN MINUTES						
6" AUGER								0			0.0-10.0': SILTY SAND (SM. FILL AND INDIGENOUS MATERIAL (6.0-10.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED AT 5.0'. 0.0-0.5': MODERATE BROWN (SYR3/4); MOTTLED GRAYISH BLACK (M2); MIXED FILL AND STREAM SEDIMENT USED AS TOPSOIL. 0.5-6.0': DARK REDDISH BROWN (DR3/4); FILL. 6.0-7.0': GRAYISH BLACK; STREAM SEDIMENT. 7.0-10.0': DARK YELLOWISH BROWN; DECOMPOSED SANDSTONE.	 2/26/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
								5			10.0-10.0': DARK YELLOWISH BROWN; DECOMPOSED SANDSTONE. BOTTOM OF HOLE AT 10.0 FT.	
								10			HOLE WAS IMMEDIATELY BACKFILLED WITH CLEAN AUGER SPOILS, 2/26/87.	
								15				
								20				
								25				
								30				
								35				
0.0-10.0': SILTY SAND (SM. FILL AND INDIGENOUS MATERIAL (6.0-10.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED AT 5.0'. 0.0-0.5': MODERATE BROWN (SYR3/4); MOTTLED GRAYISH BLACK (M2); MIXED FILL AND STREAM SEDIMENT USED AS TOPSOIL. 0.5-6.0': DARK REDDISH BROWN (DR3/4); FILL. 6.0-7.0': GRAYISH BLACK; STREAM SEDIMENT. 7.0-10.0': DARK YELLOWISH BROWN; DECOMPOSED SANDSTONE.												
HOLE WAS IMMEDIATELY BACKFILLED WITH CLEAN AUGER SPOILS, 2/26/87.												
DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.												
NOT AVAILABLE												



GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
MISS - N.J. INSPECTION STATION				FUSRAP		14501-130	1 OF 1	MISS-639R				
COORDINATES				N1855,E1100		ANGLE FROM HORIZ.		BEARING				
						90°		N/A				
START	COMPLETED	DRIER	DRILL MAKE AND MODEL		HOLE SIZE	OVERBURDEN (FT.)	ROCK (FT.)	TOTAL DEPTH				
2/26/87	2/26/87	MORETRENCH ENV. SERV.	DIE-55		6"	9.0'	0.0'	9.0'				
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	BL. TOP OF CORES	GROUND EL.	DEPTH/BL. GROUND WATER		DEPTH/BL. TOP OF ROCK				
N/A		N/A	N/A	N/A	00	5.0' / 00		N/A				
SAMPLE NUMBER WEIGHT/FULL			CORES LEFT IN HOLE: DIA./LENGTH			LOGGED BY						
N/A			N/A			D. McGRANE						
SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH (CORE FEET)	SAMPLE RECOVERY CORE RECOVERY	SAMPLE BLEND	PERCENT CORE RECOVERY	WATER PRESSURE TESTS		ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰	DEPTH AND WATER LEVELS, WATER TABLE, CHARACTER OF DRILLING, ETC.
					LOW P. IN P. C.P.A.	HIGH P. PRESSURE P. P.S.I.						
6' AUGER								0			0.0-9.0': SILTY SAND (S.M. FILL AND INDIGENOUS MATERIAL 15.0-9.0% COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-01); MOIST - SATURATED AT 5.0'. 0.0-2.0': MODERATE BROWN (SYR3/4); MOTTLED GRAYISH BLACK (02); MIXED FILL AND STREAM SEDIMENTS? 2.0-5.0': DARK YELLOWISH BROWN (00YR4/2); MOTTLED GRAYISH BLACK; MIXED FILL AND STREAM SEDIMENTS. 5.0-6.0': GRAY (05); RESIDUAL SOIL. 6.0-9.0': DARK YELLOWISH BROWN; DECOMPOSED SANDSTONE.	 2/26/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
								10			BOTTOM OF HOLE AT 10.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/26/87.	
								15				
								20				
								25				
								30				
								35				

⁰ DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
⁰⁰ NOT AVAILABLE



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
MISS - N.J. INSPECTION STATION				FUSRAP			14501-138		1 OF 1		MISS-640R		
DATE				COORDINATES				ANGLE FROM MERID.		BEARING			
2/26/87				N1831,E1004				90°		N/A			
DRILLER		DRILL		DRILL MAKE AND MODEL		HOLE SIZE		OVERLASH (FT.)		ROCK FTJ			
2/26/87		MORETRENCH ENV. SERV.		CME-55		6"		9.0'		0.0'			
CORE RECOVERY FT./%		CORE DIAM.		SAMPLES		REL. TOP OF CASING		GROUND EL.		DEPTH/REL. TOP OF ROCK			
N/A		N/A		N/A		N/A		90		5.0' / 90			
SAMPLE NUMBER IDENT./ALL			CASING LEFT IN HOLE/DIA./LENGTH			LOGGED BY:							
N/A			N/A			D. McGRANE							
SAMPLE TYPE AND DIAMETER	SAMPLER AND MAKE	SAMPLER LENGTH	SAMPLER RECOVERY	SAMPLER NO.	PERCENT CORE RECOVERY	WATER PRESSURE TESTS		ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
						LOGS	TIME						
6" AUGER									0			0.0-9.0': SILTY SAND (SMA) FILL AND INDIGENOUS MATERIAL (4.5-9.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-010); MOIST - SATURATED.	 2/26/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
								5			0.0-1.0': MODERATE BROWN (S)R3/4; MOTTLED GRAYISH BLACK (N2); MIXED FILL AND STREAM SEDIMENT; NUMEROUS GRASS ROOTS AND ORGANICS.		
									9.0			1.0-4.5': DARK REDDISH BROWN (O)R3/4; MOTTLED MODERATE BROWN FILL.	
									10			4.5-6.5': GRAY (N3); NUMEROUS ORGANICS; STREAM SEDIMENTS.	
									15			6.5-9.0': DARK YELLOWISH BROWN (10YR 4/2); DECOMPOSED SANDSTONE.	
									20			BOTTOM OF HOLE AT 9.0 FT.	
									25			HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/26/87.	
									30				
									35				

⁰ DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
⁰⁰ NOT AVAILABLE

NO-SPLIT SPINDLE STABILIZER TOOL;
 DISCONTINUED PAPER LOGGING SYSTEM

DATE MISS - N.J. INSPECTION STATION

HOLE NO. MISS-640R




GEOLOGIC DRILL LOG				PROJECT			JOB NO.	SHEET NO.	HOLE NO.					
SITE				COORDINATES										
MISS - N.J. INSPECTION STATION				N1750,E1000			ANGLE FROM MERID.		BEARINGS					
BEGAN	COMPLETED	DRIER	DRILL MAKE AND MODEL		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH						
2/26/87	2/26/87	MONOTRENCH ENV. SERV.	CME-55		6"	5.0'	0.0'	5.0'						
CORE RECOVERY (FT./%)		CORE DIAM.	SAMPLES	EL. TOP OF CORES	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK						
N/A		N/A	N/A	N/A	00	NONE OBSERVED		N/A						
SAMPLE NUMBER (HOLE/FT./ALL)			CORES LEFT IN HOLE; DRILL LENGTH			LOGGED BY								
N/A			N/A			D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE ADVANCE (DEPTH) CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAVIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
					LOSS FT. IN P. G.P.A.	PRESSURE P. P.S.I.	TIME IN P. MINUTES							
6' AUGER								0				0.0-5.0': SILTY SAND (SML FILL AND INDIGENOUS MATERIAL (3.0-5.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-04); MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION. NO GROUND WATER OBSERVED, 2/26/87.	
								5				0.0-3.0': MODERATE BROWN (SYR3/4); MOTTLED GRAYISH BLACK (42); MIXED SOIL WITH STREAM SEDIMENTS. 3.0-5.0': DARK YELLOWISH BROWN (00YR4/2); DECOMPOSED SANDSTONE.		
								10				BOTTOM OF HOLE AT 5.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/26/87.		
								15						
								20						
								25						
								30						
								35						
<small>SS-01/4 ST-02/2 ST-03/2 ST-04/2 ST-05/2 ST-06/2 ST-07/2 ST-08/2 ST-09/2 ST-10/2 ST-11/2 ST-12/2</small>											SITE MISS - N.J. INSPECTION STATION		HOLE NO. MISS-641R	




GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.							
MISS - N.J. INSPECTION STATION										FUSRAP				14501-130		1 OF 1		MISS-642R					
COORDINATES										N1650, E1000				ANGLE FROM HORIZ.		DIP							
DRILLER										DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH					
2/26/87										2/26/87		MORETRENCH ENV. SERV.		CHE-55		6"		5.0'		0.0'		5.0'	
CORE RECOVERY (FT./30)			CORE BOXES			SAMPLES			REL. TOP OF CASING			GROUND W.			DEPTH/REL. GROUND WATER			DEPTH/REL. TOP OF ROCK					
N/A			N/A			N/A			N/A			NONE OBSERVED			NONE OBSERVED			N/A					
SAMPLE NUMBER					DEPTH/FULL					CASING LEFT IN HOLE: DIA./LENGTH					LOGGED BY:								
N/A					N/A					N/A					D. McGRANE								
SAMPLE TYPE AND DIAMETER	SAMPLE ADVANCE LENGTH (CORE LOSS)	SAMPLE INTERVAL (CORE RECOVERY)	SAMPLE LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.										
					LOSS IN P.S.F.	PRESSURE IN P.S.F.	TIME IN MINUTES																
6" AUGER							0.0	0				0.0-5.0': SILTY SAND (S.M. FILL AND INDIGENOUS MATERIAL 0.0-5.0'. COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST. 0.0-1.0': MODERATE BROWN (SYR3/4) FILL. 1.0-3.0': DARK YELLOWISH ORANGE (OYR6/6); SOIL. 3.0-5.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION. NO GROUND WATER OBSERVED, 2/26/87.										
								5															
								10															
								15															
								20															
								25															
								30															
								35															
50-SPLIT SPOILS, 51-DRIFT TUBS, 52-DRIFT, 53-DRIFT, 54-DRIFT										MISS - N.J. INSPECTION STATION				HOLE NO. MISS-642R									



GEOLOGIC DRILL LOG				PROJECT			JOB NO.		SHEET NO.		HOLE NO.		
MISS - N.J. INSPECTION STATION				FUSRAP			14501-130		1 OF 1		MISS-643R		
SITE				COORDINATES				ANGLE FROM HORIZ.		BEARING			
MISS - N.J. INSPECTION STATION				N1660, E1150				90°		N/A			
BEGIN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)	TOTAL DEPTH
2/26/87		2/26/87		MORETRENCH ENV. SERV.		CNE-55		6"		5.0'		0.0'	5.0'
CORE RECOVERY (FT./%)		CORE DIAMETER		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/VEL. GROUND WATER		DEPTH/EL. TOP OF ROCK	
N/A		N/A		N/A		N/A		90		4.0' / 90		N/A	
SAMPLE NUMBER BEG/END/FALL				CASING LEFT IN HOLE DIA./LNGTH				LOGGED BY					
N/A				N/A				D. McGRANE					
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH (CORE LOSS)	SAMPLER RECOVERY CORE RECOVERY	SAMPLER LOSS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS	PRELIMINARY	TIME						
6" AUGER									0			0.0-5.0': SILTY SAND (SM) FILL AND INDIGENOUS MATERIAL (LO-5.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED AT 4.0'. 0.0-LO': MODERATE BROWN (SYR3/4) FILL MIXED WITH STREAM SEDIMENT AND USED AS FILL? LO-5.0': DARK YELLOWISH ORANGE (OYR6/6) INDIGENOUS RESIDUAL SOIL.	 2/26/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
									5			BOTTOM OF HOLE AT 5.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/26/87.	
									10				
									15				
									20				
									25				
									30				
									35				
									40				
									45				
									50				
									55				
									60				
									65				
									70				
									75				
									80				
									85				
									90				
									95				
									100				



GEOLOGIC DRILL LOG				PROJECT			JOB NO.	SHEET NO.	HOLE NO.							
MISS - N.J. INSPECTION STATION				FUSRAP			14501-130	1 OF 1	MISS-644R							
COORDINATES				NIT00,E1150			ANGLE FROM HORIZ.		BEARING							
DATE				DRILLER			HOLE SIZE		ROCK (FT.)							
2/26/87				MORETRENCH ENV. SERV.			6"		0.0'							
COMPLETED				DRILL NAME AND MODEL			OVERLAP (FT.)		TOTAL DEPTH							
2/26/87				CME-55			5.0'		5.0'							
CORE RECOVERY %		CORE BOXES	SAMPLES	REL. TOP OF CASING	GROUND W.	DEPTH/REL. GROUND WATER		DEPTH/REL. TOP OF ROCK								
N/A		N/A	N/A	N/A	00	3.5' / 00		N/A								
SAMPLE NUMBER			CASING LEFT IN HOLE			LOGGED BY										
N/A			N/A			D. McGRANE										
SAMPLE TYPE AND DIAMETER	SAMPLE ANGLE	SAMPLE DEPTH	SAMPLE LENGTH	SAMPLE WEIGHT	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.		
						LOG IN FT.	IN P.S.F.	IN P.S.F.								
6" AUGER										0			0.0-5.0': SILTY SAND (SM) FILL AND INDIGENOUS MATERIAL (3.0-5.0'). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0M); MOIST - SATURATED AT 3.5'. 0.0-1.5': GRAYISH BLACK (M2); NUMEROUS GRASS ROOTS AND ORGANICS. FILL, PROBABLY FORMER STREAM SEDIMENTS. 1.5-3.0': DARK REDDISH BROWN (O2S/4); FILL. 3.0-5.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.	 2/26/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.		
										5			BOTTOM OF HOLE AT 5.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/26/87.			
										10						
										15						
										20						
										25						
										30						
										35						
SE-SPLE SPOILS ST-CHLBY TUBE											DATE		MISS - N.J. INSPECTION STATION		HOLE NO.	
															MISS-644R	



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-138
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-645R

SITE: MISS - N.J. INSPECTION STATION
 COORDINATES: N1650, E1500
 ANGLE FROM HORIZ.: 90°
 BEARING: N/A

DATE: 2/27/87
 COMPLETED: 2/27/87
 BILLED TO: MORETRENCH ENV. SERV.
 BILL NAME AND NO.: CHE-55
 HOLE SIZE: 6"
 OVERLAP (FT.): 4.5'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 4.5'

CORE RECOVERY (FT./%)
 N/A
 CORE DIAMETER: N/A
 SAMPLES: N/A
 EL. TOP OF CASING: N/A
 GROUND EL.: 00
 DEPTH/EL. GROUND WATER: 0.0' / 00
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE NUMBER WEIGHT/FALL: N/A
 CASING LEFT IN HOLE DIA./LENGTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLE RECOVERY CORE RECOVERY	SAMPLE BLEND	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF BILLING, ETC.
					LONG IN P.S.P.A.	PRESSURE P.S.I.	TIME IN P.MINUTES						
6" AUGER								0				0.0-4.5': SILTY SAND (SIL. CLOR STRATIFIED); FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); SATURATED. 0.0-0.5': BLACK; VERY SILTY; NUMEROUS ORGANICS; STREAM SEDIMENTS. 0.5-1.0': DARK YELLOWISH BROWN (OYR4/2); UPPER SOIL HORIZON? 1.0-3.0': GRAY (O5); LOWER SOIL HORIZON? 3.0-4.5': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE. BOTTOM OF HOLE AT 4.5 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN AUGER SPOILS AND CEMENT GROUT MIXTURE, 2/27/87.	2/27/87
								5					SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
								10					
								15					
								20					
								25					
								30					
								35					

30-SPLE SPONG ST-DRLEY TUBS
 30-SPLE SPONG ST-DRLEY TUBS
 MISS - N.J. INSPECTION STATION
 HOLE NO.: MISS-645R



GEOLOGIC DRILL LOG


PROJECT: FUSRAP
 JOB NO.: 14501-138
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-646R

SITE: MISS - N.J. INSPECTION STATION
 COORDINATES: N1735, E1507
 ANGLE FROM HORIZ.: 90°
 BEARING: N/A

DRILLER: MORETRENCH ENV. SERV.
 DRILL MAKE AND MODEL: CME-55
 HOLE SIZE: 6"
 OVERBURDEN (FT.): 4.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 4.0'

CORE RECOVERY (FT./TD): N/A
 CORE BOXES: N/A
 SAMPLES: N/A
 EL. TOP OF CASING: N/A
 GROUND EL.: 00
 DEPTH/EL. GROUND WATER: 1.5' / 00
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE BARRED WEIGHT/FALL: N/A
 CASING LEFT IN HOLE, DIA./LENGTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLE APPROX. LENGTH (CORE ONLY)	SAMPLE DEPTH (CORE ONLY)	SAMPLE ELONG. BY PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ⁰⁰	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN P. GAL	INCREASE IN P. PSI	TIME IN MINUTES						
6" AUGER								0			0.0-4.0': SILTY SAND (S.M. FILL AND INDIGENOUS MATERIAL. COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES); SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H); MOIST - SATURATED AT 15'. 0.0-1.0': GRAYISH BLACK (GZ); NUMEROUS GRASS ROOTS AND ORGANICS. 1.0-4.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.	 2/27/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
								4.0			BOTTOM OF HOLE AT 4.0 FT. HOLE WAS IMMEDIATELY BACKFILLED WITH CLEAN AUGER SPOILS, 2/27/87.	
								5				
								10				
								15				
								20				
								25				
								30				
								35				

LOG-SPLE SPOILS ST-SHEDLY TRAIL
 DECISION: P-PATCHED O-OTHER
 SITE: MISS - N.J. INSPECTION STATION
 HOLE NO.: MISS-646R



GEOLOGIC DRILL LOG

PROJECT: FUSRAP
 JOB NO.: 14501-130
 SHEET NO.: 1 OF 1
 HOLE NO.: MISS-647R

SITE: MISS - N.J. INSPECTION STATION
 COORDINATES: N1773, E1499
 ANGLE FROM HORIZ.: 90°
 BEARING: N/A

DRILLER: MORETRENCH ENV. SERV.
 COMPLETED: 2/27/87
 DRILL NAME AND MODEL: CHE-55
 HOLE SIZE: 6"
 OVERLAP (FT.): 5.0'
 ROCK (FT.): 0.0'
 TOTAL DEPTH: 5.0'

CORE RECOVERY (FT./20): N/A
 CORE BOXES: N/A
 SAMPLES: N/A
 EL. TOP OF CASING: N/A
 GROUND EL.: 88
 DEPTH/EL. GROUND WATER: 3.0' / 88
 DEPTH/EL. TOP OF ROCK: N/A

SAMPLE NUMBER HEIGHT/FALL: N/A
 CASING LEFT IN HOLE DIA./DEPTH: N/A
 LOGGED BY: D. McGRANE

SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE DIA.	SAMPLER RECOVERY CORE RECOVERY	SAMPLER BLINDS	PERCENT CORE RECOVERY	WATER PRESSURE TESTS			ELEVATION ⁰⁰	DEPTH	GRAPIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ^P	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOGS	TIME	PRESSURE						
FT. IN	IN	IN	IN	IN	PSI	PSI	PSI	FT.	MIN.	MIN.	MIN.		
6" ALGER.									0				
									5			0.0-5.0': SILTY SAND (S.M. FILL AND INDIGENOUS MATERIAL (0.3-5.0% COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-04); MOIST - SATURATED AT 3.0'. 0.0-0.5': MODERATE BROWN (SYR3/4); NUMEROUS GRASS ROOTS AND ORGANICS. 0.5-3.0': DARK YELLOWISH ORANGE (OYR6/6); SOIL HORIZON? 3.0-5.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE. BOTTOM OF HOLE AT 5.0 FT. HOLE BACKFILLED IMMEDIATELY WITH CLEAN ALGER SPOILS AND CEMENT GROUT MIXTURE, 2/27/87.	2/27/87 SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION.
									10				
									15				
									20				
									25				
									30				
									35				

NO-SPLE SPIND ST-BELEY TUBE; P-SCHEMIDT P-PITCHER; O-OTHER
 SITE: MISS - N.J. INSPECTION STATION
 HOLE NO.: MISS-647R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.	SHEET NO.	HOLE NO.	
SITE										FUSRAP		14501-130	1 OF 1	MISS-648R	
MISS - N.J. INSPECTION STATION										COORDINATES		N1050,E1500		ANGLE FROM HORIZ.	BEARING
DATE	COMPLETED	DRILLER			DRILL MAKE AND MODEL		HOLE SIZE	OVERLAP (FT.)	ROCK (FT.)	TOTAL DEPTH					
2/27/87	2/27/87	MORETRENCH ENV. SERV.			CHE-55		6"	5.0'	0.0'	5.0'					
CORE RECOVERY (%)		CORE BOXES	SAMPLES	REL. TOP OF CORE	GROUND BL.	DEPT./REL. GROUND WATER		DEPTH/REL. TOP OF ROCK							
N/A		N/A	N/A	N/A	90	NONE OBSERVED		N/A							
SAMPLE NUMBER HEIGHT/FALL			CORES LEFT IN HOLE: DIA./INCH			LOGGED BY:									
N/A			N/A			D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLE GRAIN LENGTH CORE (IN)	SAMPLE DIAMETER CORE (IN)	SAMPLE LENGTH CORE (IN)	PERCENT CORE RECOVERY	WATER PRESSURE (PSI)			ELEVATION (FT.)	DEPTH	GRAPHIC LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION ^P	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF MUDS, ETC.		
					LOG IN FT.	SP. AL.	TIME IN MINUTES								
6" ALGER.									0			0.0-5.0': SILTY SAND (SML FILL AND INDIGENOUS MATERIAL (0.3-5.0% COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0H) MOIST. 0.0-0.5': GRAYISH BLACK (M2); NUMEROUS GRASS ROOTS AND ORGANICS. 0.5-1.5': DARK YELLOWISH ORANGE (OYR6/6); UPPER SOIL HORIZON. 1.5-5.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION. NO GROUND WATER OBSERVED, 2/27/87.		
									5						
									10						
									15						
									20						
									25						
									30						
									35						
											BOTTOM OF HOLE AT 5.0 FT.				
											HOLE BACKFILLED IMMEDIATELY WITH CLEAN ALGER SPOILS AND CEMENT GROUT MIXTURE, 2/27/87.				
												DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CLTTINGS. ND NOT AVAILABLE			

SD-SPLIT SPONS; ST-STEELY TUBE; D-DRILLING; P-PISTON; O-OTHER

SITE MISS - N.J. INSPECTION STATION

HOLE NO. MISS-648R



GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
MISS - N.J. INSPECTION STATION										FUSRAP		14501-130		1 OF 1		MISS-649R	
COORDINATES										N1075, E1500		ANGLE FROM HORIZ.		BEARING			
STARTED		COMPLETED		DRILLED		DRILL NAME AND MODEL		HOLE SIZE		OVERLAP (FT.)		ROCK (FT.)		TOTAL DEPTH			
2/27/87		2/27/87		MOROTRENCH ENV. SERV.		CME-55		6"		5.0'		0.0'		5.0'			
CORE RECOVERY (FT./%)		CORE BONES		SAMPLES		EL. TOP OF CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK					
N/A		N/A		N/A		N/A		00		NONE OBSERVED		N/A					
SAMPLE NUMBER				CASING LEFT IN HOLE DIA./LENGTH				LOGGED BY									
N/A				N/A				D. McGRANE									
SAMPLE TYPE AND DIAMETER	SAMPLER ADVANCE LENGTH CORE RUN	SAMPLER DEPTH CORE RECOVERY	SAMPLE LOSS	WATER PRESSURE TESTS			ELEVATION**	DEPTH	GRAPING LOG	SAMPLE	DESCRIPTION AND CLASSIFICATION*	NOTES ON WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
				LOSS IN FT. G.P.A.L.	PRE-SURE P.S.J.	TIME IN MIN. IN P. MINUTES											
6" AUGER								0			0.0-5.0': SILTY SAND (SMA. FILL AND INDIGENOUS MATERIAL 0.5-5.0). COLOR STRATIFIED; FINE - MEDIUM GRAINED WITH FEW - NUMEROUS PIECES OF SUBANGULAR - ROUNDED GRAVEL OF VARIOUS LITHOLOGIES; SOFT; UNCONSOLIDATED; SOMETIMES CLAYEY (SC-0M); MOIST.	SITE CHECKED FOR RADIOACTIVE CONTAMINATION AND HOLE GAMMA LOGGED BY EBERLINE ANALYTICAL CORPORATION. NO GROUND WATER OBSERVED, 2/27/87.					
							5			0.0-0.5': GRAYISH BLACK (M2); NUMEROUS GRASS ROOTS AND ORGANICS. 0.5-3.0': DARK YELLOWISH ORANGE (OYR6/6); SOIL HORIZON. 1.0': PIECE OF METAL. 3.0-5.0': DARK YELLOWISH BROWN (OYR4/2); DECOMPOSED SANDSTONE.							
								10			BOTTOM OF HOLE AT 5.0 FT.						
								15			HOLE WAS IMMEDIATELY BACKFILLED WITH CLEAN AUGER SPOILS, 2-27-87.						
								20									
								25									
								30									
								35									

* DESCRIPTION AND CLASSIFICATION BY VISUAL EXAMINATION OF CUTTINGS.
** NOT AVAILABLE