134032 m-438

Formerly Utilized Sites Remedial Action Program (FUSRAP)

ADMINISTRATIVE RECORD

for Maywood, New Jersey



U.S. Department of Energy

DOE F 1325.8 (8-45) EFG (07-90) United States Government

Department of Energy

memorandum

DATE: AUG 3 1 1995

TO:

SEP 6 9 33 AN '95

REPLY TO EM-421 (W. A. Williams, 301-903-8149) ATTN OF:

Elimination of Maywood Vicinity Property

L. Price, OR

The attached radiological survey report, entitled <u>Radiological Survey</u> <u>Results at 1 Shady Lane, Lodi, New Jersey (LJ095)</u>, identifies background levels of radioactive substances at that property. Accordingly, the property is not designated for remedial action under the Formerly Utilized Sites Remedial Action Program.

James W. Wagoner

Director Off-Site/Savannah River Program Division Office of Eastern Area Programs Office of Environmental Restoration

Attachment

cc:

S. Price, DOE Maywood Information Center

R. Foley, Oak Ridge National Laboratory

S. Cange, DOE/OR

134032

ORNL/RASA-95/13

RADIOLOGICAL SURVEY RESULTS at

and the second states and the second states and the second states and the

1 SHADY LANE, LODI, NEW JERSEY (LJ095)

> R. D. Foley C. A. Johnson

MANAGED BY Martin Marietta Enebgy Systems, inc. For the United States

Ì

ļ

»)AKCRIDICE NATIONAL

ARTIN MARIE

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL/RASA-95/13

HEALTH SCIENCES RESEARCH DIVISION Environmental Restoration and Waste Management Non-Defense Programs (Activity No. EX 20 20 01 0; ADS317AEX))

Radiological Survey Results at 1 Shady Lane, Lodi, New Jersey (LJ095)

R. D. Foley and C. A. Johnson

Date issued --- July 1995

Investigation Team

R. D. Foley — Measurement Applications and Development Manager M. E. Murray - FUSRAP Project Director R. D. Foley— Survey Team Leader

> Survey Team Members R. D. Foley P. F. Tiner W. A. Williams*

*U. S. Department of Energy

Work performed by the Measurement Applications and Development Group

> Prepared by the OAK RIDGE NATIONAL LABORATORY Oak Ridge, Tennessee 37831-6285 managed by LOCKHEED MARTIN ENERGY SYSTEMS, INC. for the U.S. DEPARTMENT OF ENERGY under contract DE-AC05-84OR21400

CONTENTS

¢	LIST OF FIGURES	v
•	LIST OF TABLES	vii
	ACKNOWLEDGMENTS	ix
	ABSTRACT	xi
r	INTRODUCTION	1
٢	SURVEY METHODS SURFACE RADIATION MEASUREMENTS SOIL SAMPLING AND ANALYSIS	2 2 2
r	SURVEY RESULTS SURFACE RADIATION MEASUREMENTS SOIL SAMPLING AND ANALYSIS	2 2 3
	SIGNIFICANCE OF FINDINGS	3
r'	REFERENCES	4

iii

LIST OF FIGURES

1	Diagram showing the general location of Lodi, New Jersey relative to the Maywood Interim Storage Site (MISS)	5
2	Diagram showing gamma measurements and soil sampling locations at 1 Shady Lane, Lodi, New Jersey	6
3	Photograph of the property at 1 Shady Lane, Lodi, New Jersey, facing north towards the front of the house	7
4	Photo of the back of the house and yard, facing south. An above-ground swimming pool is in the left foreground	8
5	Photo of the back yard facing the southwest end of the house at 1 Shady Lane, Lodi, New Jersey	8

v

LIST OF TABLES

والمستندي والمستندين والمتعيد والمتحافي المحتوي المحتوي والمحتوي والمتحافظ والمتحاف والمتحاف والمتحاف

a l'arrente

`~ ----

I

I

I

T

I

T

I

F

Ĩ

Ţ

I

T

T

T

I

T

Γ

ſ

T

1	Applicable guidelines for protection against radiation	9
2	Average background radiation levels for the northern New Jersey area	11
3	Concentrations of radionuclides in soil at 1 Shady Lane, Lodi, New Jersev (LJ095)	12

ACKNOWLEDGMENTS

Research for this project was sponsored by the Office of Environmental Restoration, U. S. Department of Energy, under contract DE-AC05-840R21400 with Martin Marietta Energy Systems, Inc. The authors wish to acknowledge the contributions of D. A. Roberts, D. A. Rose, and J. M. Lovegrove of the Measurement Applications and Development Group for participation in the sample preparation and analyses, editing, graphics, and reporting of data for this survey. The surveying assistance of the staff on the survey team is also gratefully acknowledged.

T

Ţ

Ì

ABSTRACT

The U. S. Department of Energy (DOE) conducted remedial action at the Stepan property in Maywood, New Jersey and several vicinity properties in Lodi, New Jersey as part of the Formerly Utilized Sites Remedial Action Program (FUSRAP). These properties are in the vicinity of the DOE-owned Maywood Interim Storage Site (MISS), adjacent to the former Maywood Chemical Works facility. The property at One Shady Lane, Lodi, New Jersey was not one of these vicinity properties but was surveyed by DOE at the request of the owner.

At the request of DOE, a team from Oak Ridge National Laboratory conducted a radiological survey at this property. The purpose of the survey, conducted in November 1994, was to confirm whether remedial actions were to be performed on the property in order to be in compliance with the identified guidelines. The radiological survey included surface gamma scans and gamma readings at 1 meter, and the collection of soil samples for radionuclide analysis.

|__

Results of the survey demonstrated that all radiological measurements on the property at One Shady Lane, Lodi, New Jersey, were comparable to background levels in the area, and well within the limits prescribed by DOE radiological guidelines. Based on the results of the radiological survey data, this property does not meet guidelines for inclusion under FUSRAP.

xì

RADIOLOGICAL SURVEY RESULTS AT 1 SHADY LANE, LODI, NEW JERSEY (LJ095)*

INTRODUCTION

Thorium ores were processed by the Maywood Chemical Works (MCW)¹, Maywood, New Jersey, between 1916 and 1959. The MCW ceased thorium processing in 1959 and the 30-acre property was sold that same year to Stepan Chemical Company. During the early years of operation, MCW stored wastes and residues in low-lying areas west of the processing facilities, now called the Maywood Interim Storage Site (MISS). Subsequently, residuals containing radioactive materials migrated off-site to the surrounding area, and the Stepan property and several vicinity properties were designated by Congress for remedial action as a result of the 1984 Energy and Water Development Appropriations Act, along with other sites.

The waste produced by the thorium extraction process was a sand-like material containing residual amounts of thorium and its decay products, with smaller quantities of uranium and its decay products. Because some of the wastes had been carried downstream by Lodi Brook, and some area residents had also used the sand-like wastes as mulch in their yards, the properties in the vicinity of the MCW were included as a decontamination research and development project under the DOE Formerly Utilized Sites Remedial Action Program (FUSRAP). Figure 1 shows the location of Lodi, New Jersey, relative to the former MCW, now the DOE-owned Maywood Interim Storage Site.

At the request of the DOE, a group from Oak Ridge National Laboratory (ORNL) conducted investigative radiological surveys of several properties surrounding the former processing plant. The property at One Shady Lane, Lodi, New Jersey, was not included in the earlier investigations; however, since the property was adjacent to a park which had been surveyed and found to contain some areas above guidelines, the owner requested that his property be surveyed also.

In November 1994, ORNL conducted an ad hoc radiological survey at the request of DOE. A complete gamma scan was performed and four soil samples were collected and analyzed for radionuclide concentrations.

A drawing of the property at One Shady Lane is shown in Fig. 2. Photographs taken in November 1994 of the property are shown in Figs. 3-5.

*The survey was performed by members of the Measurement Applications and Development Group of the Health Sciences Research Division of Oak Ridge National Laboratory (ORNL) under DOE contract DE-AC05-84OR21400.

SURVEY METHODS

A comprehensive description of the survey methods and instrumentation used in this survey is given in Procedures Manual for the ORNL Radiological Survey Activities (RASA) Program, ORNL/TM-8600 (April 1987)², and Measurement Applications and Development Group Guidelines, ORNL-6782 (January 1995)³.

SURFACE RADIATION MEASUREMENTS

Gamma radiation levels were determined using a portable sodium iodide (NaI) gamma scintillation probe connected to a Victoreen ratemeter. Measurements were recorded and converted to microroentgens per hour (μ R/h). Because NaI gamma scintillators are energy dependent, measurements of gamma radiation levels in counts per minute (cpm) are normalized to pressurized ionization chamber (PIC) measurements to estimate gamma exposure rates in μ R/h.

SOIL SAMPLING AND ANALYSIS

Surface and subsurface soil samples were systematically collected over the back and front yards of the property. Two samples were taken from the front yard and two from the backyard (locations of the samples are shown in Fig. 2). All samples were analyzed for thorium, radium and uranium. At each sampling location, the gamma radiation levels are measured at each six-inch increment in the sample hole. The gamma radiation levels give an indication of possible nearby radioactive materials and their location.

SURVEY RESULTS

Current DOE guidelines for sites included within the FUSRAP are included in Table 1.4.5 Typical background radiation levels for the northern New Jersey area are given in Table 2.6.7 These data are provided for comparison with survey results presented in this section. All direct measurement results presented in this report are gross readings; background radiation levels have not been subtracted. Similarly, background concentrations have not been subtracted from radionuclide concentrations in soil samples.

SURFACE RADIATION MEASUREMENTS

A gamma scan was conducted over the grassy areas of the front and back yards, sidewalks, and driveway. Gamma exposure measurements generally ranged from 7-13 μ R/h at the surface in the front, side and back yards. A maximum range of 10 to 16 μ R/h was measured between the sidewalk and the front of the brick house, where natural constituents in the building materials can influence gamma measurements (see Fig. 2). All the measurements are comparable to the typical background radiation levels found in the northern New Jersey area (Table 2).

SOIL SAMPLING AND ANALYSIS

Systematic soil samples were collected from the front and back yards. All samples were analyzed for uranium, radium and thorium concentrations. Results of the soil analysis showed that radionuclide concentrations in both surface and subsurface samples ranged from 0.71 to 1.1 pCi/g, 0.81 to 1.1 pCi/g, and 0.70 to 2.4 pCi/g for 226Ra, 232Th, and 238U, respectively. Concentrations of radium and thorium are comparable to background levels for the northern New Jersey area (Table 2), and well below DOE guidelines in surface and subsurface soil of 5 and 15 pCi/g, respectively. Concentrations of 238U are also well below the site specific limits prescribed for uranium (Table 1). Sample locations are shown on Fig. 2 and results of radionuclide analysis are listed in Table 3.

SIGNIFICANCE OF FINDINGS

Gamma exposure levels on the property ranged from 7 to 16 μ R/h. For comparison, background levels for the northern New Jersey area average ~9 μ R/h. Concentrations of uranium, thorium, and radium found in the soil samples taken from the front and back yards were comparable to background levels in the area and are well below DOE guidelines for these radionuclides.

The measurements taken during this radiological survey at One Shady Lane, Lodi, New Jersey indicate results that are well within the limits prescribed by DOE radiological guidelines. Therefore, based on these findings, this property does not meet guidelines for inclusion under FUSRAP.

REFERENCES

- L. W. Cole, J. Berger, P. Cotten, R. Gosslee, L. Sowell, and C. Weaver, Radiological Assessment of Ballod Associates Property (Stepan Chemical Company), Maywood, New Jersey, Oak Ridge Associated Universities, Oak Ridge, Tenn., July 30, 1981.
- T. E. Myrick, B. A. Berven, W. D. Cottrell, W. A. Goldsmith, and F. F. Haywood, Procedures Manual for the ORNL Radiological Survey Activities (RASA) Program, ORNL/TM-86090, Martin Marietta Energy Systems, Inc., Oak Ridge Natl Lab., April 1987.
- 3. Oak Ridge National Laboratory, Health Sciences Research Division, Measurement Applications and Development Group Guidelines, ORNL-6782, Martin Marietta Energy Systems, Inc., January 1995.
- 4. U. S. Department of Energy, Guidelines for Residual Radioactive Material at Formerly Utilized Sites Remedial Action Program and Remote Surplus Facilities Management Program Sites, Rev 2, March 1987.
- 5. U. S. Department of Energy, Radiation Protection of the Public and the Environment, DOE Order 5400.5, April 1990.
- 6. T. E. Myrick, B. A. Berven, and F. F. Haywood, State Background Radiation Levels: Results of Measurements Taken During 1975-1979, ORNL/TM-7343, Martin Marietta Energy Systems, Inc., Oak Ridge Natl Lab., November 1981.
- 7. S. G. Levin, R. K. Stoms, E. Kuerze, and W. Huskisson, "Summary of Natural Environmental Gamma Radiation Using a Calibrated Portable Scintillation Counter," *Radiological Health Data Report* 9:679-695 (1968).

.T

 \mathbf{r}

Г

Г

17

Γ



Fig. 1. Diagram showing the general location of Lodi, New Jersey relative to the Maywood Interim Storage Site (MISS).

1

(Jr



1

i

ţ

_

ł

Fig. 2. Diagram showing gamma measurements and soil sampling locations at 1 Shady Lane, Lodi, New Jersey.



Fig. 3. Photograph of the property at 1 Shady Lane, Lodi, New Jersey facing north towards the front of the house.

-



Fig. 4. Photo of the back of the house and yard, facing south. An above-ground swimming pool is in the left foreground.



Fig. 5. Photo of the back yard facing the southwest end of the house at 1 Shady Lane, Lodi, New Jersey.

Mode of exposure	Exposure conditions	Guideline value
		1
Gamma radiation	Indoor gamma radiation level (above background)	20 µR/h ^a
Total residual surface contamination ^b	238U, 235U, U-natural (alpha emitters) or	
	Beta-gamma emitters ^c	15 000 dpm/100 am'
		5 000 dpm/100 cm
	Removable	1,000 dpm/100 cm ²
	232Th, Th-natural (alpha emitters)	
	or	
	90Sr (beta-gamma emitter)	
	Maximum	3,000 dpm/100 cm ²
	Average	1,000 dpm/100 cm ²
	Removable	200 dpm/100 cm ²
	²²⁶ Ra, ²³⁰ Th, transuranics	
	Maximum	300 dpm/100 cm ²
	Average	100 dpm/100 cm ²
	Removable	20 dpm/100 cm ²
eta-gamma dose	Surface dose rate averaged	
rates	over not more than 1 m^2	0.20 mrad/h
	Maximum dose rate in any	
	100-cm ² area	1.0 mrad/h
Podionuolido con	Man January 1 - 12 1	
Caulonucinde con-	Maximum permissible con-	5 pCi/g averaged over
centrations in soil	centration of the following	the first 15 cm of soil
generic)	radionuclides in soil above	below the surface; 15
	background levels, averaged	pCi/g when averaged
	over a 100-m ² area	over 15 cm-thick soil
	226 D. a	layers > 15 cm below
	220 Ka	the surface
	2321 h	

Table 1. Applicable guidelines for protection against radiation(Limits for uncontrolled areas)

9

Site specific^d

Derived concentrations

238U

أله مرة المرام ا

14 A.

....

Table 1. (continued)

Mode of exposure	Exposure conditions	Guideline value	
Guideline for non- homogeneous con- tamination (used in addition to the 100-m ² guideline) ^e	Applicable to locations with an area $\leq 25 \text{ m}^2$. with signifi- cantly elevated concentrations of radionuclides ("hot spots")	$G_A = G_i(100/A)^{1/2}$, where $G_A =$ guideline for that spot of area (A) $G_i =$ guideline averaged over a 100-m ² area	

^aThe 20 μ R/h shall comply with the basic dose limit (100 mrem/yr) when an appropriate-use scenario is considered.

^bDOE surface contamination guidelines are consistent with NRC Guidelines for Decontamination at Facilities and Equipment Prior to Release for Unrestricted Use or Termination of Licenses for By-Product, Source, or Special Nuclear Material, May 1987.

eBeta-gamma emitters (radionuclides with decay modes other than alpha emission or spontaneous fission) except 90Sr, 228Ra, 223Ra, 227Ac, 1331, 1291, 1261, 1251.

^dDOE guidelines for uranium are derived on a site-specific basis. Guidelines of 35-40 pCi/g have been applied at other FUSRAP sites. Sources: J. L. Marley and R. F. Carrier, Results of the Radiological Survey at 4 Elmhurst Avenue, Colonie, New York (AL219), ORNL/RASA-87/117, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab., February 1988; B. A. Berven et. al., Radiological Survey of the Former Kellex Research Facility, Jersey City, New Jersey, DOE/EV-0005/29, ORNL-5734, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab., February 1982.

•DOE guidelines specify that every reasonable effort shall be made to identify and to remove any source that has a concentration exceeding 30 times the guideline value, irrespective of area (adapted from *Revised Guidelines for Residual Radioactive Material at FUSRAP and Remote SFMP Sites, April 1987*).

Sources: Adapted from U.S. Department of Energy, Radiation Protection of the Public and the Environment, DOE Order 5400.5, April 1990, and U.S. Department of Energy, Guidelines for Residual Radioactive Material at Formerly Utilized Sites Remedial Action Program and Remote Surplus Facilities Management Program Sites, Rev. 2, March 1987; and U.S. Department of Energy Radiological Control Manual, DOE N 5480.6 (DOE/EH-256T), June 1992.

Type of radiation measurement or sample	Radiation level or radionuclide concentration ^a	ł
Gamma exposure at 1 m above ground surface (µR/h)	96	
Concentration of radionuclides in soil (pCi/g) ^c		
²²⁶ Ra	0.9	
232Th	0.9	
238U	0.9	

Table 2. Average background radiation levels for the northern New Jersey area

^aThese values represent an average of normal radionuclide concentrations in this part of the state. Actual values may fluctuate.

^bSource: U. S. Department of Energy, *Radiological Survey of the Middlesex Municipal Landfill, Middlesex, New Jersey*, DOE/EV-00005/20, April 1980. Values ranging from 8-11 μ R/h (average 9 μ R/h) were obtained from 35 locations in the Rochelle Park, New Jersey area (Ref. 7).

cSource: T. E. Myrick, and B. A. Berven, State Background Radiation Levels: Results of Measurements Taken During 1975-1979, ORNL/TM-7343, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab., November 1981 (Ref. 6).

÷...

i.__

number ²	(cm)	226D o		2381 1	
		Systematic sol	il samples ^c		
SIA	0-15	0.71 ±0.06	0.85 ±0.1	1.5 ±0.5	
S1B	15-30	0.92 ±0.07	1.1 ±0.1	0.72±0.4	
S1C	30-45	0.94 ±0.07	0.98 ±0.1	1.2 ±0.3	
S2	0-15	0.76 ±0.06	0.82 ±0.1	0.70±0.2	
\$3	0-15	1.1 ±0.07	0.93 ±0.1	2.4 ±0.3	
S4	0-15	0.85 ±0.07	0.81 ± 0.1	1.3 ±0.2	

Table 3. Concentrations of radionuclides in soilat 1 Shady Lane, Lodi, New Jersey (LJ095)

^aLocations of soil samples are shown on Fig. 2.

^bIndicated counting error is at the 95% confidence level ($\pm 2\sigma$).

cSystematic samples are taken at locations irrespective of gamma exposure rates.

ORNL/RASA-95/13

INTERNAL DISTRIBUTION

1. B. A. Berven 13. R. E. Swaja 2. K. J. Brown 14. M. S. Uziel 3. R. F. Carrier 15. J. K. Williams 4-6. R. D. Foley 16. Central Research Library 7-9. C. A. Johnson 17-18. Laboratory Records 10. M. E. Murray 19. Laboratory Records-RC 11. P. T. Owen 20. ORNL Patent Section 21. ORNL Technical Library, Y-12 12. R. E. Rodriguez 22-27. MAD Records Center

EXTERNAL DISTRIBUTION

- 28. W. L. Beck, Oak Ridge Associated Universities, E/SH Division, Environmental Survey and Site Assessment Program, P.O. Box 117, Oak Ridge, TN 37831-0117
- 29. Jack Russell, Booz-Allen & Hamilton, Inc., Trevion I Bldg., Suite 210, 12850 Middlebrook Rd., Bethesda, MD 20814
- 30. James J. Fiore, Director, Office of Eastern Area Programs, Office of Environmental Restoration, EM-24, U.S. Department of Energy, 19901 Germantown Rd., Germantown, MD 20874-1290
- 31-33. R. R. Harbert, Bechtel National, Inc., FUSRAP Department, Oak Ridge Corporate Center, 151 Lafayette Drive, P.O. Box 350, Oak Ridge, TN 37831-0350
- 34-36. J. King, Science Applications International Corporation, P.O. Box 2501, 301 Laboratory Road, Oak Ridge, TN 37831
 - 37. L. K. Price, Director, Former Sites Restoration Division, Oak Ridge Field Office, U.S. Department of Energy, P.O. Box 2001, Oak Ridge, TN 37831-8723
- 38. James W. Wagoner II, Director, Division of Off-Site Programs, Office of Eastern Area Programs, Office of Environmental Restoration, EM-421, U.S. Department of Energy, 19901 Germantown Rd., Germantown, MD 20874-1290
- 39-43. W. Alexander Williams, Designation and Certification Manager, Division of Off-Site Programs, Office of Eastern Area Programs, Office of Environmental Restoration, EM-421, U.S. Department of Energy, 19901 Germantown Rd., Germantown, MD 20874-1290
- 44-45. Office of Scientific and Technical Information, U.S. Department of Energy, P.O. Box 62, Oak Ridge, TN 37831
 - 46. Office of Assistant Manager, Energy Research and Development, U.S. Department of Energy, DOE Field Office, P.O.Box 2008, Oak Ridge, TN 37831-6269