M-737

Formerly Utilized Sites Remedial Action Program (FUSRAP)

ADMINISTRATIVE RECORD

for the Maywood Site, New Jersey



US Army Corps of Engineers.

M-737

RESULTS OF THE RADIOLOGICAL SURVEY AT 8 MILL STREET, LODI, NEW JERSEY

INTRODUCTION

A radiological survey of 8 Mill Street, Lodi, New Jersey, was conducted by Oak Ridge National Laboratory (ORNL) on August 22, 1984 at the request of the Department of Energy (DOE). Contaminated material was discovered during mobile gamma scan of Lodi, New Jersey.

The radiological survey conducted on this property was for the purpose of determining whether the property had any radioactive material onsite in excess of background radiation levels, and, if so, were these radioactive materials in excess of remedial action guidelines established by DOE such that the property could be "designated" for further investigation. This report summarizes the results of the "designation" survey performed on this property.

SURVEY METHODS

The radiological survey of the property included: (1) a gamma scan of the entire property outdoors; and (2) sampling of surface (0-15 cm) soil. No indoor survey measurements were performed. These survey methods followed the plan outlined in Reference 2. A comprehensive description of the survey methods and instrumentation have been presented in another report.³

SURVEY RESULTS

Applicable federal guidelines have been summarized in Table 1. The normal background levels for the northern New Jersey area are presented in Table 2. These data are provided for comparison with the survey results presented in this section. All direct measurement results presented in this report are gross readings at ground surface; background radiation levels have not been subtracted. Similarly, background

^{*} The survey was performed by members of the Radiological Survey Activities Group of the Health and Safety Research Division at Oak Ridge National Laboratory under DOE contract DE-AC05-840R21400.

concentrations have not been subtracted from radionuclide concentrations measured in environmental samples.

Systematic and Biased Soil Samples

Systematic and biased soil samples were taken from various locations on the property for radionuclide analyses. Locations of the systematic (LJ7S) and biased (LJ7B) samples are shown in Fig. 1, with results of laboratory analyses provided in Table 3. Concentrations of $232_{\rm Th}$ exceeded the background concentrations of $232_{\rm Th}$ anticipated for northern New Jersey in the biased soil samples collected at 8 Mill Street (LJ7B1 - LJ7B3). These results indicate that $232_{\rm Th}$ -bearing residues exist on this site. The amount of material present is in excess of DOE guidelines (Table 1).

Gamma Radiation Levels

Results of the gamma scan of the surface of the property show areas where gamma exposure rates are in excess of background radiation levels. These locations are shown in Fig. 2, and the measurements are quantified. These locations suggest where potential 232 Th contamination exists. Gamma exposure rate levels up to 26 μ R/h exist on the ground surface at this property.

SUMMARY

Measurements taken at 8 Mill Street indicate that the property contains radioactive contamination primarily from the ²³²Th decay chain, and to a lesser extent from the ²³⁸U decay chain. This material is found in the locations shown in Fig. 2. Concentrations of these radionuclides were elevated significantly above background, and the levels are in excess of DOE remedial action guidelines. It is recommended that this property be designated for further evaluation. A comprehensive radiological survey will be required to delineate the extent of contamination to plan for any necessary remedial action.

2

REFERENCES

- R. W. Doane and B. A. Berven, "Results of the Mobile Gamma Scanning Activities in Lodi, New Jersey," Oak Ridge National Laboratory, ORNL/RASA-84/3 (October 1984).
- W. D. Cottrell, ORNL, to A. J. Whitman, DOE/HQ, correspondence, "Radiological Survey of Private Properties in Lodi, New Jersey" (August 15, 1984).
- 3. Oak Ridge National Laboratory, <u>Procedures Manual for the ORNL</u> <u>Remedial Action Survey and Certification Activities (RASCA)</u> <u>Program</u>, ORNL/TM-8600 (October 1982).
- 4. U.S. Department of Energy, <u>Radiological Survey of the Middlesex</u> <u>Municipal Landfill</u>, <u>Middlesex</u>, <u>New Jersey</u>, DOE/EV-0005/20, April 1980.
- 5. T. E. Myrick and B. A. Berven, <u>State Background Radiation Levels</u>: <u>Results of Measurements Taken During 1975-1979</u>, Oak Ridge National Laboratory, ORNL/TM-7343 (November 1981).

• systematic samples'

biased samples



Fig. 1. Diagram showing locations of soil samples taken at 8 Mill Street.



~ >

Fig. 2. Location of elevated gamma radiation levels at 8 Mill Street.

S

Mode of exposure **Exposure** conditions Guideline value Guideline source 1. External gamma radiation Continuous exposure to 60 µR/h Nuclear Regulatory Commission (NRC) individual in general Standards for Protection Against population (whole body) Radiation (10 CFR 20.105) 2. Radionuclide concentrations Maximum permissible concen-DOE Interim Residual Contamination in soil tration of the following and Waste Control Guidelines radionuclides in soil for FUSRAP and SFMP Sites above background levels (April 1984) averaged over 100 m² area 226_{Ra} 5 pCi/g averaged 232_{Th} over the first 15 cm σ of soil below the surface; 15 pCi/g when averaged over 15-cm thick soil layers more than 15 cm below the surface.

Table 1. A summary of proposed applicable radiation guidelines for the FUSRAP program (April 1984).

| Type or radiation measurement or sample | Radiation level or radionuclide concentration |
|--|---|
| Gamma exposure rate at 1 m above floor or ground surface (µR/h) | ga |
| Concentration of radionuclides in soil | |
| (pCi/g) 232m | đe n |
| 23 8 _U | 0.9b |
| 226 _{Ra} | 0.9b |

^aReference 4. ^bReference 5.

:

5

Table 2. Background radiation levels for the northern New Jersey area.

| Sample ^a | | Radionuclide concentration (pCi/g) | | |
|---------------------|-----------------|------------------------------------|-------------------|--------------------|
| | Depth - (cm) | 226 _{Ra} b | 232 _{Th} | 238 _U c |
| | Systemat | ic samples | | |
| LJ7S1 | 0 - 15 | 0.57 ± 0.08 | 0.68 ± 0.2 | 0.47 |
| LJ7S2 | 0 - 15 | 0.68 ± 0.2 | 0.84 ± 0.3 | 0.72 |
| | Biased | samples ^d | | |
| LJ 7B1 A | 0 - 10 | 2.0 ± 0.1 | 9.7 ± 3 | 4.9 |
| LJ7B1B | 10 - 20 | 2.8 ± 0.2 | 23 <u>+</u> 5 | 6.2 |
| LJ7B1C | 20 - 30 | 5.7 ± 0.4 | 25 <u>+</u> 6 | 22 |
| LJ7B2A | 0 - 10 | 1.7 ± 0.2 | 7 <u>+</u> 2 | 4.1 |
| LJ7B2B | 10 - 20 | 1.7 ± 0.2 | 6.8 <u>+</u> 2 | 5.1 |
| LJ7B2C | 20 - 30 | 2.0 ± 0.3 | 8.9 <u>+</u> 2 | 5.5 |
| LJ7B2D | 30 - 40 | 3.9 ± 0.2 | 17 <u>+</u> 4 | 10 |
| LJ7B3A | 0 - 10 | 1.6 ± 0.2 | 6.4 <u>+</u> 1 | 3.7 |
| LJ7B3B | 10 - 20 | 1.5 ± 0.2 | 6.5 ± 2 | 3.7 |

Table 3. Results of soil sample analyses at property LJ007.

^aLocations of soil samples are shown on Fig. 1.

^bIndicated counting error is at the 95% confidence level $(\pm 2 \sigma)$.

^c Total analytical error of measurement results is less than \pm 3% (95% confidence level).

^dBiased samples are taken from areas shown to have elevated gamma exposure rates.

